

Printing date 22.09.2017 Version number 39 Revision: 05.09.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Product code HAC6
- · Trade name: HYDROCOAT CL. WB MOBIK SEALER
- · 1.2. Relevant identified uses of the substance or mixture and uses advised against

A coating composition for water-based coating and / or decoration of wooden artefacts

· Application of the substance / the mixture For professional use

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Further information obtainable from:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· 1.4 Emergency telephone number:

From 8.30 to 17.30 0039 038 425 441

Out of the above mentioned hours, Saturdays and Sundays and during periods of closure for holidays please call: 0039 0384 254491

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

The product is not classified according to the CLP regulation.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008 Void
 - · Hazard pictograms Void
 - · Signal word Void
 - · Hazard statements Void
- · Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1). May produce an allergic reaction.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
 - · Description: Mixture: consisting of the following components.

· Dangerous components:	
CAS: 34590-94-8	(2-methoxymeth
EINECS: 252-104-2	substance with

(2-methoxymethylethoxy)propanol substance with a Community workplace exposure

Reg.nr.: 01-2119450011-60-XXXX limit

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

No special measures required.

(Contd. on page 2)

1-<5%



Printing date 22.09.2017 Version number 39 Revision: 05.09.2017

Product code HAC6

Trade name: HYDROCOAT CL. WB MOBIK SEALER

(Contd. of page 1)

personal protective equipment for first aid responders is recommended. (please see section 8)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, see chap. 11th

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
 - · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures See section 7.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special measures required.
 - · Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
 - · Storage:
 - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if indicated, is from delivery date.

In cases there is no reported deadline, it means that the product must be used within 8 months.

Take on temperature greater than 5 ° C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- 7.3 Specific end use(s)

Those typical of the product and the instructions in the data sheet if required.



Printing date 22.09.2017 Version number 39 Revision: 05.09.2017

Product code HAC6

Trade name: HYDROCOAT CL. WB MOBIK SEALER

(Contd. of page 2)

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

· 8.1 Control paran	neters
· Ingredients with	limit values that require monitoring at the workplace:
34590-94-8 (2-me	thoxymethylethoxy)propanol
WEL Long-term v Sk	alue: 308 mg/m³, 50 ppm
· DNELs	
34590-94-8 (2-me	thoxymethylethoxy)propanol
Inhalative D	NEL 310 mg/mc (Workers)
Irritation of skin D	NEL 65 mg/kg bw/d (Workers)
· PNECs	
34590-94-8 (2-me	thoxymethylethoxy)propanol
PNEC Acqua dolc	e/water/woda słodka/eau/agua 19 mg/L (_)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

PNEC Suolo/earth/suelo/sol/gleba/

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product and in accordance with EN 374 and Directive 89/686/EEC.

2.74 mg/kg (_)

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

- · General Information
 - · Appearance:

· Form: Fluid

· Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 4)



Printing date 22.09.2017 Version number 39 Revision: 05.09.2017

Product code HAC6

Trade name: HYDROCOAT CL. WB MOBIK SEALER

	(Contd. of pa
 Change in condition Melting point/freezing point: Initial boiling point and boiling rang 	Undetermined. re: 100°C
· Flash point:	Not applicable.
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	270°C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits: · Lower: · Upper:	0.6 Vol % 20.4 Vol %
· Vapour pressure at 20°C:	0.4 hPa
 Density at 20°C: Relative density Vapour density Evaporation rate 	1.031 g/cm³ Not determined. Not determined. Not determined.
· Solubility in / Miscibility with · water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
 · Viscosity: · Dynamic: · Kinematic at 20°C: · Oxidising properties: 	Not determined. 60 s (ISO 6 mm) N.A.
· Solvent content: · VOC and Total VOC (organic solvents + reactive solvents · Water: · VOC (EC)	if any) 5.25 % 61.8 % 54.1 g/l
· Solids content: 9.2 Other information	32.9 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Typical of the product as indicated in the data sheet
- 10.2 Chemical stability

The product is stable in normal conditions of storage and use recommended

- Thermal decomposition / conditions to be avoided:
 No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.



Printing date 22.09.2017 Version number 39 Revision: 05.09.2017

Product code HAC6

Trade name: HYDROCOAT CL. WB MOBIK SEALER

(Contd. of page 4)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

$\cdot L$	D/LC50	0 values relevant for classification:
34590-9	94-8 (2·	-methoxymethylethoxy)propanol
Oral	LD50	5,135 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	19,020 mg/kg (rab)
2634-33	3-5 1,2	benzisothiazol-3(2H)-one
Oral	LD50	1,193 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	4,115 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

- · Primary irritant effect:
 - · Skin corrosion/irritation Based on available data, the classification criteria are not met.
 - $\cdot \textit{ Serious eye damage/irritation }$

Based on available data, the classification criteria are not met.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 - · Germ cell mutagenicity Based on available data, the classification criteria are not met.
 - · Carcinogenicity Based on available data, the classification criteria are not met.
 - · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic t	oxicity:
34590-94-8	(2-methoxymethylethoxy)propanol
EC50	970 mg/l (algae) (72 h)
	1,919 mg/l (daphnia) (48 h)
LC50 (96h)	1,001 mg/l (Fish)
2634-33-5 1	,2-benzisothiazol-3(2H)-one
EC50	2.94 mg/l (daphnia) (48 h)
LC50 (96h)	2.18 mg/l (Fish)
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-
	methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.027 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.19 mg/l (Fish)
40.0 Davaia	tongo and dogradability. No further relevant information available

- 12.2 Persistence and degradability No further relevant information available.
 - · Substances Easily biodegradable

34590-94-8 (2-methoxymethylethoxy)propanol .

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)



Printing date 22.09.2017 Version number 39 Revision: 05.09.2017

Product code HAC6

Trade name: HYDROCOAT CL. WB MOBIK SEALER

(Contd. of page 5)

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - · Recommendation

Hand over to hazardous waste disposers.

The code number of the product as it is: 080112

- · Uncleaned packaging:
 - · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
· ADR, ADN, IMDG, IATA	Not classified	
14.2 UN proper shipping name		
· ADR, ADN, IMDG, IATA	Not classified	
14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
· Class	Not classified	
14.4 Packing group		
· ADR, IMDG, IATA	Not classified	
14.5 Environmental hazards:		
· Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to An	nex II	
of Marpol and the IBC Code	Not applicable.	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive n.: 80/1107/CEE, n. 82/605/CEE, n. 83/477/CEE, n. 86/188/CEE e n. 88/642/CEE, 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2002/44,2003/10/CE, 2003/18/CE, 2004/40/CE,2006/25

(Contd. on page 7)



Printing date 22.09.2017 Version number 39 Revision: 05.09.2017

Product code HAC6

Trade name: HYDROCOAT CL. WB MOBIK SEALER

(Contd. of page 6)

· Various regulations

Dir 2004/42/EC - EU limit value for this product (Cat A / e): 130 g / l. This product contains a maximum of 73 g / l VOC - Paint and wood impregnation for interior / exterior trim. For professional use only

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: Carlo Porta
 - · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

· * Data compared to the previous version altered.

GE