

Printing date 09/18/2015

Version number 33

Reviewed on 09/18/2015

1 Identification

- · Product identifier
 - · Product number CKT330
 - · Trade name: Kromostain conc. Mahogany
 - · Relevant identified uses of the substance or mixture and uses advised against

Paint and relative material only for wood

- · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
 - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

acetone

butanone

· Hazard statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment. P241

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 2)



Printing date 09/18/2015 Version number 33 Reviewed on 09/18/2015

Product number CKT330

Trade name: Kromostain conc. Mahogany

(Contd. of page 1)

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 0

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - · Description: Mixture: consisting of the following components.

· Dang	· Dangerous components:		
67-64-1	acetone	 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 	30-49.9%
78-93-3	butanone	 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 	30-49.9%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
 - · For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

(Contd. on page 3)



Printing date 09/18/2015 Version number 33 Reviewed on 09/18/2015

Product number CKT330

Trade name: Kromostain conc. Mahogany

(Contd. of page 2)

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- $\cdot \textit{Further information about storage conditions:} \\$

Keep receptacle tightly sealed.

(Contd. on page 4)



Printing date 09/18/2015 Version number 33 Reviewed on 09/18/2015

Product number CKT330

Trade name: Kromostain conc. Mahogany

(Contd. of page 3)

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm
REL Long-term value: 590 mg/m³, 250 ppm
TLV Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
BEI

78-93-3 butanone

PEL Long-term value: 590 mg/m³, 200 ppm
REL Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
TLV Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
BEI

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- Personal protective equipment:
 - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is

(Contd. on page 5)



Printing date 09/18/2015 Version number 33 Reviewed on 09/18/2015

Product number CKT330

Trade name: Kromostain conc. Mahogany

(Contd. of page 4)

a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



· Viscosity:
· Dynamic:

· *Kinematic at 20 °C (68 °F):*

· Oxidising properties:

Tightly sealed goggles

Information on basic physical and	chemical properties		
· General Information			
\cdot Appearance:			
· Form:	Fluid		
· Color:	According to product specification		
· Odor:	Characteristic		
· Odour threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
· Melting point/Melting range:	Undetermined.		
· Boiling point/Boiling range:	55 °C (131 °F)		
· Flash point:	-17 °C (1 °F)		
· Flammability (solid, gaseous):	Not applicable.		
· Ignition temperature:	> 370 °C (> 698 °F)		
· Decomposition temperature:	Not determined.		
· Auto igniting:	Product is not selfigniting.		
· Danger of explosion:	Product is not explosive. However, formation of explosi		
~ · ·	air/vapor mixtures are possible.		
· Explosion limits:			
· Lower:	1.8 Vol %		
· Upper:	13.0 Vol %		
· Vapor pressure at 20 °C (68 °F):	233 hPa (175 mm Hg)		
· Density at 20 °C (68 °F):	0.805 g/cm³ (6.718 lbs/gal)		
· Relative density	Not determined.		
· Vapour density	Not determined.		
Evaporation rate	Not determined.		
· Solubility in / Miscibility with			
· Water:	Not miscible or difficult to mix.		

Not determined. 29 s (ISO 3 mm)

N.A.

(Contd. on page 6)



Printing date 09/18/2015 Version number 33 Reviewed on 09/18/2015

Product number CKT330

Trade name: Kromostain conc. Mahogany

(Contd. of page 5)

· Solvent content:
· VOC content:

· Solids content:

· Solids content:

· Other information (HAPS)

None of the ingredients is listed.

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
 - · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Vapours may form explosive mixtures with air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

in case of possible formation of combustion:

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
67-64-1 ad	67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	20000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
Inhalative	LC50/4 h	76 mg/l (rat/szczur/mouse/souris/Maus/ratón)	
78-93-3 butanone			
Oral	LD50	2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
Inhalative	LC50	21 mg/l (rat/szczur/mouse/souris/Maus/ratón)	

- · Primary irritant effect:
 - · on the skin: No irritant effect.
 - · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- $\cdot \textit{Additional toxicological information:}$

Causes serious eye irritation.

May cause drowsiness or dizziness.

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

(Contd. on page 7)



Printing date 09/18/2015 Version number 33 Reviewed on 09/18/2015

Product number CKT330

Trade name: Kromostain conc. Mahogany

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:			
67-64-1 acetone			
EC50	8800 mg/l (daphnia)		
LC50 (96h)	5540 mg/l (Fish)		
78-93-3 butanone			
EC50	2029 mg/l (algae) (96 h)		
	308 mg/l (daphnia) (48 h)		
LC50 (96h)	2993 mg/l (Fish)		

- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

UN1263

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

14 Transport Information			
· UN-Number			
$\cdot DOT$	NA 1263		

· UN proper shipping name

· IMDG, IATA

· DOT Paint · IMDG, IATA PAINT

(Contd. on page 8)



Printing date 09/18/2015 Version number 33 Reviewed on 09/18/2015

Product number CKT330

Trade name: Kromostain conc. Mahogany

(Contd. of page 7)

· Transport hazard class(es)

 $\cdot DOT$



· Class

· Label

· Class

· Label

3 Flammable liquids

3 Flammable liquids

3

· IMDG, IATA



· Class · Label 3 Flammable liquids

Packing group

· DOT, IMDG, IATA

II

· Environmental hazards:

· Marine pollutant:

No

· Special precautions for user · Danger code (Kemler):

Warning: Flammable liquids 33

· EMS Number:

F-E,<u>S-E</u>

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· Limited quantities (LQ)

5L

Code: E2 · Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30

Maximum net quantity per outer packaging:

500 ml

· UN "Model Regulation": UN1263, Paint, special provision 640D, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

78-93-3 butanone

30-49.9% (Contd. on page 9)



Printing date 09/18/2015

Version number 33

Reviewed on 09/18/2015

Product number CKT330

Kromostain conc. Mahogany Trade name:

(Contd. of page 8)

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
 - · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)			
67-64-1	acetone	1	30-49.9%
78-93-3	butanone	1	30-49.9%

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - Date of preparation / last revision 09/18/2015 / 32
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Sources

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

Page 10/10



Safety Data Sheet 29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 33

Reviewed on 09/18/2015

Product number CKT330

Trade name: Kromostain conc. Mahogany

(Contd. of page 9)

IARC International agency for research on cancer

* Data compared to the previous version altered.

He