

Printing date 09/18/2015

## Version number 40

Reviewed on 09/18/2015

## **1** Identification

- · Product identifier
  - · Product number CLT11
  - Trade name: Kromolux conc. Yellow

• Relevant identified uses of the substance or mixture and uses advised against Paint and relative material only for wood • Application of the substance / the mixture For professional use

### · Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals srl Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

#### · Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapor.

GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



STOT SE 3 H336 May cause drowsiness or dizziness.

### · Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

 Hazard-determining components of labeling: sodium 3-(p-anilinophenylazo)benzenesulphonate 1-methoxy-2-propanol
 Hazard statements

H226 Flammable liquid and vapor. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness.

(Contd. on page 2)

<sup>–</sup> us



Printing date 09/18/2015

Version number 40

Reviewed on 09/18/2015

Product number CLT11 Trade name: Kromolux conc. Yellow		
	(Contd. of page 1)	
· Precautional	ry statements	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
P303+P361	+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P305+P351	+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a poison center/doctor.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.	
· Classification sy	stem:	
· NFPA ratings (s	scale $0 - 4$ )	
F	$\begin{aligned} \text{lealth} &= 1\\ \text{ire} &= 3\\ \text{leactivity} &= 0 \end{aligned}$	
· HMIS-ratings (s	scale 0 - 4)	
FIRE 3	$\begin{aligned} Health &= 1\\ Fire &= 3\\ Reactivity &= 0 \end{aligned}$	

## 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Danger	rous components:	
107-98-2	1-methoxy-2-propanol	75-100%
	<ul> <li>Flam. Liq. 3, H226</li> <li>STOT SE 3, H336</li> </ul>	
587-98-4	sodium 3-(p-anilinophenylazo)benzenesulphonate	5-9.99%
	Eye Dam. 1, H318 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	

## 4 First-aid measures

#### · Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - · Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

(Contd. on page 3)

US



## Printing date 09/18/2015

# Safety Data Sheet 29 CFR Parts 1910 1915 1926

Version number 40

Reviewed on 09/18/2015

Product number CLT11

Trade name: Kromolux conc. Yellow

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. of page 2)

## 5 Fire-fighting measures

### · Extinguishing media

- · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.
- Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.

#### Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

## 6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation Keep away from ignition sources
 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
   Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## 7 Handling and storage

### · Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Protect against electrostatic charges.
- Use explosion-proof apparatus / fittings and spark-proof tools.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 4)

US -



Printing date 09/18/2015

# Safety Data Sheet 29 CFR Parts 1910 1915 1926

Version number 40

Reviewed on 09/18/2015

#### Product number CLT11 Trade name: Kromolux conc. Yellow

(Contd. of page 3)

# · Conditions for safe storage, including any incompatibilities

- · Storage:
  - · Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

• Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

· Components with limit values that require monitoring at the workplace:

#### 107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m<sup>3</sup>, 150 ppm Long-term value: 360 mg/m<sup>3</sup>, 100 ppm

TLV Short-term value: 369 mg/m<sup>3</sup>, 100 ppm Long-term value: 184 mg/m<sup>3</sup>, 50 ppm

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- · Personal protective equipment:
  - General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
  - · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

US



Reviewed on 09/18/2015

Printing date 09/18/2015

Version number 40

Product number	CLT11	
Trade name:	Kromolux conc.	Yellow

· Eye protection:	(Contd. of page
Tightly sealed goggle	es
9 Physical and chemical prope	rties
• Information on basic physical and • General Information	chemical properties
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
• Melting point/Melting range:	Undetermined.
• Boiling point/Boiling range:	120 °C (248 °F)
· Flash point:	35 °C (95 °F)
· Flammability (solid, gaseous):	Not applicable.
• Ignition temperature:	270 °C (518 °F)
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	2.3 Vol %
· Upper:	20.0 Vol %
· Vapor pressure at 20 °C (68 °F):	12 hPa (9 mm Hg)
• Density at 20 •C (68 •F):	0.967 g/cm³ (8.07 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
• Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
• <i>Kinematic at 20 •C (68 •F):</i>	29 s (ISO 3 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· VOC content:	90.8 %
	877.9 g/l / 7.33 lb/gl
· Solids content:	9.2 %

(Contd. on page 6)

US



Printing date 09/18/2015

Version number 40

Reviewed on 09/18/2015

Product number CLT11

Trade name: Kromolux conc. Yellow

(Contd. of page 5)

- · Other information (HAPS)
- None of the ingredients is listed.
- · Other information

No further relevant information available.

## 10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- Chemical stability The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions Vapours may form explosive mixtures with air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

### · Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

107-98-2	1-methoxy	y-2-propanol	
Oral	LD50	4016 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	2001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
Inhalative	LC50/4 h	54.6 mg/l (rat/szczur/mouse/souris/Maus/ratón)	
· Sen · Additio Cause	on the eye: Strong cau Strong irrita Irritating ef sitization: I nal toxicolo s serious e ause drows	: No irritant effect. Istic effect. ant with the danger of severe eye injury.	
· Car	cinogenic c	categories	
		rnational Agency for Research on Cancer)	
None of th	ne ingredie	ents is listed.	
·j	NTP (Natio	onal Toxicology Program)	
None of th	ne ingredie	ents is listed.	
	OSHA-Ca (	(Occupational Safety & Health Administration)	
. (	```		

(Contd. on page 7)



Printing date 09/18/2015

Version number 40

Reviewed on 09/18/2015

Product number CLT11 Trade name: Kromolux conc. Yellow

(Contd. of page 6)

## 12 Ecological information

· Toxicity

#### • Aquatic toxicity:

#### 107-98-2 1-methoxy-2-propanol

EC50 23300 mg/l (daphnia) (48 h)

LC50 (96h) 6812 mg/l (Fish)

· Persistence and degradability No further relevant information available.

#### · Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
  - · General notes:
  - Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

## **13 Disposal considerations**

#### · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

#### · Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number	
·DOT	NA 1263
· IMDG, IATA	UN3092
· UN proper shipping name	
·DOT	Paint
· IMDG, IATA	1-METHOXY-2-PROPANOL mixture
· Transport hazard class(es)	
·DOT	
3	
· Class	3 Flammable liquids
	3
· Label	



Reviewed on 09/18/2015

Printing date 09/18/2015

Version number 40

Product number	CLT11	
Trade name:	Kromolux conc.	Yellow

	(Contd. of page
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group · DOT, IMDG, IATA	<i>III</i>
• Environmental hazards: • Marine pollutant:	No
• Special precautions for user • Danger code (Kemler): • EMS Number:	Warning: Flammable liquids 30 F-E,S-D
<ul> <li>Transport in bulk according to Annex I MARPOL73/78 and the IBC Code</li> </ul>	ll of Not applicable.
• Transport/Additional information: • Remarks:	Classification: 3 ADR P.G. III UN 186 RESIN SOLUTION when packages > 45 liters IMDG 3 P.G. III UN 186 RESIN SOLUTION when packages > 30 liters
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 3 ml Maximum net quantity per outer packaging 1000 ml

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 9)

US

< 0.1%



# Safety Data Sheet 29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

· Proposition 65

Version number 40

Product number CLT11 Kromolux conc. Yellow Trade name:

> (Contd. of page 8) · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

1589-47-5 2-methoxypropanol

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone · Date of preparation / last revision 09/18/2015 / 39 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Liq. 3: Flammable liquids, Hazard Category 3 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Aquatic Acute 3: Hazardous to the aquatic environment - AcuteHazard, Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 Sources Directive 1999/45/EC and following amendments Directive 67/548/EEC and following amendments and adjustments Agency ECHA web site **INRS Fiche Toxicologique** IARC International agency for research on cancer  $\cdot$  \* Data compared to the previous version altered.