

Printing date 09/18/2015

Version number 44

Reviewed on 09/18/2015

1 Identification

- · Product identifier
 - · Product number CLT1
 - · Trade name: Kromolux conc. Yellow Int.

• Relevant identified uses of the substance or mixture and uses advised against Paint and relative material only for wood • Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals srl Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- Emergency telephone number: ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 1B H360 May damage fertility or the unborn child.

GHS07

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

 Hazard-determining components of labeling: 1-methoxy-2-propanol
 C.I. Acid Yellow 151
 2-methoxypropanol

• Hazard statements H226 Flammable liquid and vapor.

(Contd. on page 2)

US



Reviewed on 09/18/2015

Printing date 09/18/2015

Version number 44

| Product number | CLT1 | |
|----------------|----------------|-------------|
| Trade name: | Kromolux conc. | Yellow Int. |

| | (Contd. of pa |
|---|--|
| H319 Causes seri | |
| H351 Suspected of | |
| | e fertility or the unborn child. |
| | drowsiness or dizziness. |
| Precautionary state | |
| P210 | Keep away from heat/sparks/open flames/hot surfaces No smoking. |
| P241 | Use explosion-proof electrical/ventilating/lighting/equipment. |
| P303+P361+P353 | 3 IF ON SKIN (or hair): Remove/Take off immediately all contamination clothing. Rinse skin with water/shower. |
| P305+P351+P338 | 3 If in eyes: Rinse cautiously with water for several minutes. Rem contact lenses, if present and easy to do. Continue rinsing. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container in accordance with local/regional/nation international regulations. |
| Classification system: | č |
| · NFPA ratings (scale 0 | - 4) |
| Health = Fire = 3 Reactive | |
| · HMIS-ratings (scale 0 | - 4) |
| HEALTH 1 Health | = 1 |
| FIRE 3 Fire = 3 | 3 |
| | vity = 0 |
| REACTIVITY O Reactiv | |

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

| · Dangeroi | is components: | |
|------------|--|-----------|
| 107-98-2 | 1-methoxy-2-propanol | 75-100% |
| | Flam. Liq. 3, H226 STOT SE 3, H336 | |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol | 10-12.49% |
| | 🚸 Eye Irrit. 2, H319 | |
| 72496-88-9 | C.I. Acid Yellow 151 | 5-9.99% |
| | Carc. 2, H351 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 | |
| 1589-47-5 | 2-methoxypropanol | 0.1-<0.5% |
| | Flam. Liq. 3, H226 Repr. 1B, H360 Eye Dam. 1, H318 | |
| | Skin Irrit. 2, H315; STOT SE 3, H335 | |

4 First-aid measures

· Description of first aid measures

· General information:

Symptom's of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

US

(Contd. of page 2)



Printing date 09/18/2015

Safety Data Sheet 29 CFR Parts 1910 1915 1926

Version number 44

Reviewed of

Reviewed on 09/18/2015

Product number CLT1 Trade name: Kromolux conc. Yellow Int.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 - For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed
 - No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
 - · For safety reasons unsuitable extinguishing agents:
 - Do not use a jet water stream as it may scatter and spread fire.
- · Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Keep away from ignition sources
 Environmental precautions:
 Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

• Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

US



Printing date 09/18/2015

Version number 44

Reviewed on 09/18/2015

Product number CLT1

Kromolux conc. Yellow Int. Trade name:

(Contd. of page 3)

Prevent formation of aerosols. Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

- · Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor,

Observe the label precautions, the expiration date for the use, if not indicated, is from deliverv date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm

TLV Short-term value: 369 mg/m³, 100 ppm Long-term value: 184 mg/m³, 50 ppm

112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 67.5* mg/m³, 10* ppm *Inhalable fraction and vapor

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures: Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

(Contd. on page 5)

US



Printing date 09/18/2015

Safety Data Sheet 29 CFR Parts 1910 1915 1926

Version number 44

Reviewed on 09/18/2015

Product number CLT1

Trade name: Kromolux conc. Yellow Int.

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

| Information on basic physical and chemica | al properties |
|--|--|
| · General Information | |
| · Appearance: | |
| · Form: | Fluid |
| · Color: | According to product specification |
| · Odor: | Characteristic |
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| • Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | 100 °C (212 °F) |
| · Flash point: | 35 °C (95 °F) |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 225 °C (437 °F) |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: | |
| · Lower: | 0.9 Vol % |
| · Upper: | 20.0 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 12 hPa (9 mm Hg) |
| • Density at 20 •C (68 •F): | 0.967 g/cm³ (8.07 lbs/gal) |
| · Relative density | Not determined. |
| • Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| · Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| · Dynamic: | Not determined. |



Reviewed on 09/18/2015

Printing date 09/18/2015

Version number 44

Product number CLT1

| Trade name: | Kromolux conc. | Yellow Int. |
|-------------|----------------|-------------|
| | | |

| | | (Contd. of page |
|------------------------------------|-----------------------------------|-----------------|
| • Kinematic at 20 •C (68 •F): | 29 s (ISO 3 mm) | |
| • Oxidising properties: | N.A. | |
| · Solvent content: | | |
| • Water: | 0.8 % | |
| · VOC content: | 93.2 % | |
| | 900.8 g/l / 7.52 lb/gl | |
| · Solids content: | 6.0 % | |
| • Other information (HAPS) | | |
| 112-34-5 2-(2-butoxyethoxy)ethanol | | 10-12,49% |
| · Other information | No further relevant information a | vailable. |

10 Stability and reactivity

· Reactivity typical of the product as indicated in the data sheet

- Chemical stability The product is stable in normal conditions of storage and use recommended • Thermal decomposition / conditions to be avoided:
 - No decomposition if used according to specifications.
- · Possibility of hazardous reactions Vapours may form explosive mixtures with air

· Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

• Information on toxicological effects May damage fertility or the unborn child.

| • Acute | toxicity: |
|---------|-----------|
| | |

| • <i>LD</i> /. | LC50 value | es that are relevant for classification: | |
|-----------------------|-------------------------------|---|--------------------|
| 107-98-2 ⁻ | 1-methoxy | /-2-propanol | |
| Oral | LD50 | 4016 mg/kg (rat/szczur/mouse/souris/Maus/ratón) | |
| Dermal | LD50 | 2001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin) | |
| Inhalative | LC50/4 h | 54.6 mg/l (rat/szczur/mouse/souris/Maus/ratón) | |
| 112-34-5 | 2-(2-butox | yethoxy)ethanol | |
| Oral | LD50 | 2410 mg/kg (rat/szczur/mouse/souris/Maus/ratón) | |
| Dermal | LD50 | 2764 mg/kg (rabbit/królik/Kaninchen/conejo/lapin) | |
| 72496-88- | 9 C.I. Acio | d Yellow 151 | |
| Oral | LD50 | 5001 mg/kg (rat/szczur/mouse/souris/Maus/ratón) | |
| | nary irritan | | |
| | | No irritant effect. | |
| | on the eye: Irritating efi | fect | |
| | | rious eye irritation. | |
| · Sens | sitization: N | Vo sensitizing effects known. | |
| | | ogical information: | |
| | | ye irritation. | |
| | | siness or dizziness. | |
| May ca | ause drows | siness or dizziness. | |
| | | | (Contd. on page 7) |



Version number 44

Reviewed on 09/18/2015

Printing date 09/18/2015

Product number CLT1 Trade name: Kromolux conc. Yellow Int.

(Contd. of page 6)

2B

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

72496-88-9 C.I. Acid Yellow 151

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

| 12 Ecolo | gical | infor | mation |
|----------|-------|-------|--------|
| | | | |

· Toxicity

• Aquatic toxicity:

107-98-2 1-methoxy-2-propanol

EC50 23300 mg/l (daphnia) (48 h)

LC50 (96h) 6812 mg/l (Fish)

112-34-5 2-(2-butoxyethoxy)ethanol

- EC50 101 mg/l (algae) (48 h)
 - 101 mg/l (daphnia) (48 h)
- LC50 (96h) 1300 mg/l (Leuciscus idus melanotus)

· Persistence and degradability No further relevant information available.

- · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

- · Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

| · UN-Number | | |
|--------------|---------|--|
| $\cdot DOT$ | NA 1263 | |
| · IMDG, IATA | UN3092 | |



Reviewed on 09/18/2015

Printing date 09/18/2015

Version number 44

| Product number | r CLT1 | |
|----------------|----------------|-------------|
| Trade name: | Kromolux conc. | Yellow Int. |

| | (Contd. of page |
|---|---|
| · UN proper shipping name | |
| · DOT · IMDG, IATA | Paint 1-METHOXY-2-PROPANOL mixture |
| • Transport hazard class(es) | |
| · DOT | |
| | |
| <u>.</u> | |
| FLAMMABLE LOUD | |
| | 2 Flommable liquida |
| · Class · Label | 3 Flammable liquids 3 |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
| | |
| | |
| 3 | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| Packing group | |
| · DOT, IMDG, IATA | <i>III</i> |
| Environmental hazards: | No |
| · Marine pollutant: | |
| • Special precautions for user • Danger code (Kemler): | Warning: Flammable liquids 30 |
| • EMS Number: | 50 F-E,S-D |
| • Transport in bulk according to Anne» | |
| MARPOL73/78 and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| · Remarks: | Classification: 3 ADR P.G. III UN 186 |
| | RESIN SOLUTION when packages > 45 |
| | liters IMDG 3 P.G. III UN 186 |
| | RESIN SOLUTION when packages > 30 liter |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| | Code: E1 |
| • Excepted quantities (EQ) | |
| | Maximum net quantity per inner packaging: 3 |
| | Maximum net quantity per inner packaging: 3 ml |
| | Maximum net quantity per inner packaging: 3 |

(Contd. on page 9)



Reviewed on 09/18/2015

Printing date 09/18/2015

Version number 44

Product number CLT1

Trade name: Kromolux conc. Yellow Int.

(Contd. of page 8)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

72496-88-9 C.I. Acid Yellow 151

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

1589-47-5 2-methoxypropanol

0.1-<0.5%

5-9.99%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

·NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone

- · Date of preparation / last revision 09/18/2015 / 43
- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

(Contd. on page 10)



Printing date 09/18/2015

Safety Data Sheet 29 CFR Parts 1910 1915 1926

Version number 44

Reviewed on 09/18/2015

Product number CLT1 Trade name: Kromolux conc. Yellow Int.

| HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Liq. 3: Flammable liquids, Hazard Category 3 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 5: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 5: Serious eye Irritation eye Irritation, Hazard Category 1 Eye Irrit. 5: Serious eye Irritation eye Irritation, Hazard Eye Irritatir Eye Irritation, Hazard Eye Irritation, Hazard Eye Irritation, | (Contd. of page 9) |
|---|--------------------|
| Directive 1999/45/EC and following amendments | |
| Directive 67/548/EEC and following amendments and adjustments Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer • * Data compared to the previous version altered. | |

US -