

1 Identification

- **Product identifier**
 - *Product number* CLT7
 - *Trade name:* **Kromolux conc. Classic Walnut**
 - *Relevant identified uses of the substance or mixture and uses advised against*
Paint and relative material only for wood
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Repr. 1B H360 May damage fertility or the unborn child.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

- *Hazard pictograms*



GHS02



GHS05



GHS07



GHS08

- *Signal word* Danger

(Contd. on page 2)

Product number CLT7

Trade name: Kromolux conc. Classic Walnut

(Contd. of page 1)

· **Hazard-determining components of labeling:**

1-methoxy-2-propanol
sodium 3-(p-anilinophenylazo)benzenesulphonate
C.I. ACID BLACK 194
2-methoxypropanol

· **Hazard statements**

H226 Flammable liquid and vapor.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

| | | |
|------------|--------------------------------------------------------------------------------------------------------------------------|-----------|
| 107-98-2 | 1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 | 75-100% |
| 112-34-5 | 2-(2-butoxyethoxy)ethanol ⚠ Eye Irrit. 2, H319 | 5-9.99% |
| 57693-14-8 | C.I. ACID BLACK 194 ⚠ Aquatic Chronic 2, H411 ⚠ Eye Irrit. 2A, H319; Skin Sens. 1, H317 ⚠ Aquatic Acute 2, H401 | 2.5-4.99% |

(Contd. on page 3)

Product number CLT7

Trade name: Kromolux conc. Classic Walnut

| | | |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| (Contd. of page 2) | | |
| 587-98-4 | sodium 3-(p-anilinophenylazo)benzenesulphonate | 2.5-4.99% |
| | <div> <div></div> <div>Eye Dam. 1, H318</div> </div> <div> <div></div> <div>Aquatic Acute 3, H402; Aquatic Chronic 3, H412</div> </div> | |
| 72275-69-5 | C.I. ACID ORANGE 139 | 1-2.49% |
| | <div> <div></div> <div>Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335</div> </div> | |
| 1589-47-5 | 2-methoxypropanol | 0.1-<0.5% |
| | <div> <div></div> <div>Flam. Liq. 3, H226</div> </div> <div> <div></div> <div>Repr. 1B, H360</div> </div> <div> <div></div> <div>Eye Dam. 1, H318</div> </div> <div> <div></div> <div>Skin Irrit. 2, H315; STOT SE 3, H335</div> </div> | |

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

(Contd. on page 4)

Product number CLT7

Trade name: Kromolux conc. Classic Walnut

(Contd. of page 3)

Keep away from ignition sources

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m , 150 ppm

Long-term value: 360 mg/m , 100 ppm

TLV Short-term value: 369 mg/m , 100 ppm

Long-term value: 184 mg/m , 50 ppm

112-34-5 2-(2-butoxyethoxy)ethanol

TLV Long-term value: 67.5* mg/m , 10* ppm

*Inhalable fraction and vapor

(Contd. on page 5)

Product number CLT7

Trade name: Kromolux conc. Classic Walnut

(Contd. of page 4)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

100 °C (212 °F)

· **Flash point:**

35 °C (95 °F)

· **Flammability (solid, gaseous):**

Not applicable.

(Contd. on page 6)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 60

Reviewed on 09/18/2015

Product number CLT7**Trade name:** Kromolux conc. Classic Walnut

(Contd. of page 5)

| | |
|---------------------------------------------------|--------------------------------------------------------------------------------------------|
| · Ignition temperature: | 225 °C (437 °F) |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: | |
| · Lower: | 0.9 Vol % |
| · Upper: | 20.0 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 12 hPa (9 mm Hg) |
| · Density at 20 °C (68 °F): | 0.983 g/cm (8.203 lbs/gal) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| · Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| · Dynamic: | Not determined. |
| · Kinematic at 20 °C (68 °F): | 29 s (ISO 3 mm) |
| · Oxidising properties: | N.A. |
| · Solvent content: | |
| · Water: | 1.0 % |
| · VOC content: | 90.2 % |
| | 886.5 g/l / 7.40 lb/gl |
| · Solids content: | 8.9 % |
| · Other information (HAPS) | |
| 112-34-5 2-(2-butoxyethoxy)ethanol | 5-9,99% |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects** May damage fertility or the unborn child.

(Contd. on page 7)

US

Product number CLT7

Trade name: Kromolux conc. Classic Walnut

(Contd. of page 6)

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

107-98-2 1-methoxy-2-propanol

| | | |
|------------|----------|---------------------------------------------------|
| Oral | LD50 | 4016 mg/kg (rat/szczur/mouse/souris/Maus/ratón) |
| Dermal | LD50 | 2001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin) |
| Inhalative | LC50/4 h | 54.6 mg/l (rat/szczur/mouse/souris/Maus/ratón) |

112-34-5 2-(2-butoxyethoxy)ethanol

| | | |
|--------|------|---------------------------------------------------|
| Oral | LD50 | 2410 mg/kg (rat/szczur/mouse/souris/Maus/ratón) |
| Dermal | LD50 | 2764 mg/kg (rabbit/królik/Kaninchen/conejo/lapin) |

72275-69-5 C.I. ACID ORANGE 139

| | | |
|------|------|-------------------------------------------------|
| Oral | LD50 | 5001 mg/kg (rat/szczur/mouse/souris/Maus/ratón) |
|------|------|-------------------------------------------------|

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

Irritating effect.

Causes serious eye irritation.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

Causes serious eye damage.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Irritant

Harmful if inhaled.

May cause drowsiness or dizziness.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity** Harmful to aquatic life with long lasting effects.

· **Aquatic toxicity:**

107-98-2 1-methoxy-2-propanol

| | |
|------------|-----------------------------|
| EC50 | 23300 mg/l (daphnia) (48 h) |
| LC50 (96h) | 6812 mg/l (Fish) |

112-34-5 2-(2-butoxyethoxy)ethanol

| | |
|------------|--------------------------------------|
| EC50 | 101 mg/l (algae) (48 h) |
| | 101 mg/l (daphnia) (48 h) |
| LC50 (96h) | 1300 mg/l (Leuciscus idus melanotus) |

· **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

Product number CLT7

Trade name: Kromolux conc. Classic Walnut



(Contd. of page 7)

- **Behavior in environmental systems:**
 - *Bioaccumulative potential* No further relevant information available.
 - *Mobility in soil* No further relevant information available.
- **Ecotoxicological effects:**
 - *Remark:* Harmful to fish
- **Additional ecological information:**
 - *General notes:*
 - Water hazard class 1 (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
 - Harmful to aquatic organisms
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - *Recommendation:*
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Hand over to hazardous waste disposers.
 - Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
 - *Recommendation:* Disposal must be made according to official regulations.

14 Transport information

- | | |
|-------------------------------------------------------------------------------------|---------------------|
| · UN-Number | |
| · DOT | NA1263 |
| · IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · IMDG, IATA | PAINT |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |

(Contd. on page 9)

Product number CLT7

Trade name: Kromolux conc. Classic Walnut

(Contd. of page 8)

| | |
|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| · Packing group | III |
| · DOT, IMDG, IATA | |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · Danger code (Kemler): | 30 |
| · EMS Number: | F-E, S-E |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · Remarks: | Classification: 3 ADR P.G. III UN 1866 RESIN SOLUTION when packages > 450 liters IMDG 3 P.G. III UN 1866 RESIN SOLUTION when packages > 30 liters |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN1263, Paint, special provision 640E, 3, III |

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

1589-47-5 2-methoxypropanol

0.1-<0.5%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

Product number CLT7

Trade name: Kromolux conc. Classic Walnut

(Contd. of page 9)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 09/18/2015 / 59

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Repr. 1B: Reproductive toxicity, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Acute 2: Hazardous to the aquatic environment - AcuteHazard, Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - AcuteHazard, Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· **Sources**

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

· *** Data compared to the previous version altered.**