

1 Identification

- **Product identifier**
 - *Product number* CLT9
 - *Trade name:* **Kromolux conc. Black**
 - *Relevant identified uses of the substance or mixture and uses advised against*
Paint and relative material only for wood
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Repr. 1B H360 May damage fertility or the unborn child.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

- *Hazard pictograms*



GHS02



GHS07



GHS08

- *Signal word* Danger

- *Hazard-determining components of labeling:*

1-methoxy-2-propanol

2-methoxypropanol

C.I. ACID BLACK 164

- *Hazard statements*

H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

Product number CLT9

Trade name: Kromolux conc. Black

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture: consisting of the following components.

Dangerous components:

107-98-2	1-methoxy-2-propanol	75-100%
	Flam. Liq. 3, H226	
	STOT SE 3, H336	
85958-90-3	C.I. ACID BLACK 164	5-9.99%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
112-34-5	2-(2-butoxyethoxy)ethanol	2.5-4.99%
	Eye Irrit. 2, H319	
1589-47-5	2-methoxypropanol	0.1-<0.5%
	Flam. Liq. 3, H226	
	Repr. 1B, H360	
	Eye Dam. 1, H318	
	Skin Irrit. 2, H315; STOT SE 3, H335	

4 First-aid measures

Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

Product number CLT9

Trade name: Kromolux conc. Black

(Contd. of page 2)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed**
For symptoms and effects caused by substances, refer to Section 11.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:** Alcohol resistant foam, CO, powder, water spray/mist.
 - **For safety reasons unsuitable extinguishing agents:**
Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
 - **Protective equipment:**
Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to Section 13.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
 - **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.

(Contd. on page 4)

Product number CLT9

Trade name: Kromolux conc. Black

(Contd. of page 3)

- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
Provide solvent resistant, sealed floor.
Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
In cases where there is no reported expiration date, it means that the product must be used within 8 months.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:	
107-98-2 1-methoxy-2-propanol	
REL	Short-term value: 540 mg/m , 150 ppm Long-term value: 360 mg/m , 100 ppm
TLV	Short-term value: 369 mg/m , 100 ppm Long-term value: 184 mg/m , 50 ppm
112-34-5 2-(2-butoxyethoxy)ethanol	
TLV	Long-term value: 67.5* mg/m , 10* ppm *Inhalable fraction and vapor

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls

- **Personal protective equipment:**
 - **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
 - **Breathing equipment:** Not required.
 - **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Product number CLT9
Trade name: Kromolux conc. Black

(Contd. of page 4)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odour threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

120 °C (248 °F)

· Flash point:

35 °C (95 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

225 °C (437 °F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:

0.9 Vol %

· Upper:

20.0 Vol %

· Vapor pressure at 20 °C (68 °F):

12 hPa (9 mm Hg)

· Density at 20 °C (68 °F):

0.975 g/cm (8.136 lbs/gal)

· Relative density

Not determined.

· Vapour density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C (68 °F):

29 s (ISO 3 mm)

· Oxidising properties:

N.A.

· Solvent content:

· Water:

4.7 %

· VOC content:

85.7 %

836.1 g/l / 6.98 lb/gl

(Contd. on page 6)

Product number CLT9

Trade name: Kromolux conc. Black

(Contd. of page 5)

· Solids content:		9.6 %
· Other information (HAPS)		
112-34-5	2-(2-butoxyethoxy)ethanol	2,5-4,99%
· Other information		No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects** May damage fertility or the unborn child.
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
107-98-2 1-methoxy-2-propanol		
Oral	LD50	4016 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	54.6 mg/l (rat/szczur/mouse/souris/Maus/ratón)
112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	LD50	2410 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2764 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

- **Primary irritant effect:**
 - **on the skin:** Causes skin irritation.
 - **on the eye:**
Irritating effect.
Causes serious eye irritation.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause drowsiness or dizziness.

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)	
None of the ingredients is listed.	
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 50

Reviewed on 09/18/2015

Product number CLT9**Trade name: Kromolux conc. Black**

(Contd. of page 6)

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

107-98-2 1-methoxy-2-propanol	
EC50	23300 mg/l (daphnia) (48 h)
LC50 (96h)	6812 mg/l (Fish)
112-34-5 2-(2-butoxyethoxy)ethanol	
EC50	101 mg/l (algae) (48 h)
	101 mg/l (daphnia) (48 h)
LC50 (96h)	1300 mg/l (Leuciscus idus melanotus)

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

- Water hazard class 1 (Self-assessment): slightly hazardous for water

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Hand over to hazardous waste disposers.

- Dispose of contents and container in accordance with local state and federal regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- DOT

NA1263

- IMDG, IATA

UN3092

- **UN proper shipping name**

- DOT

Paint

- IMDG, IATA

1-METHOXY-2-PROPANOL mixture

(Contd. on page 8)

US

Printing date 09/18/2015

Version number 50

Reviewed on 09/18/2015

Product number CLT9

Trade name: Kromolux conc. Black

(Contd. of page 7)

· **Transport hazard class(es)**

· **DOT**



- **Class** 3 Flammable liquids
- **Label** 3
- **Class** 3 Flammable liquids
- **Label** 3

· **IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3

· **Packing group**

- **DOT, IMDG, IATA** III

· **Environmental hazards:**

- **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

- **Danger code (Kemler):** 30
- **EMS Number:** F-E, S-D

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

- **Remarks:** Classification: 3 ADR P.G. III UN 1866
RESIN SOLUTION when packages > 450 liters
IMDG 3 P.G. III UN 1866
RESIN SOLUTION when packages > 30 liters

· **IMDG**

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN1263, Paint, special provision 640E, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

(Contd. on page 9)

Product number CLT9

Trade name: Kromolux conc. Black

(Contd. of page 8)

· **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

1589-47-5	2-methoxypropanol	0.1-<0.5%
-----------	-------------------	-----------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 09/18/2015 / 49

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

(Contd. on page 10)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 50

Reviewed on 09/18/2015

Product number CLT9**Trade name: Kromolux conc. Black**

(Contd. of page 9)

*Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2**Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A**Repr. 1B: Reproductive toxicity, Hazard Category 1B**STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3***• Sources***Directive 1999/45/EC and following amendments**Directive 67/548/EEC and following amendments and adjustments**Agency ECHA web site**INRS Fiche Toxicologique**IARC International agency for research on cancer***• * Data compared to the previous version altered.**

US