

Printing date 01/20/2017

Version number 25

Reviewed on 01/20/2017

#### 1 Identification

- · Product identifier
  - · Product number HEC400
  - · Trade name: HYDROCOAT GLASS CLEAR TEX
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

### 2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified according to the Globally Harmonized System (GHS).

- · Label elements
  - · GHS label elements Not applicable
    - · Hazard pictograms Not applicable
    - · Signal word Not applicable
    - · Hazard statements Not applicable
- · Classification system:
  - · NFPA ratings (scale 0 4)



Health = 0

Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0

Fire = 0

Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerou	· Dangerous components:		
34590-94-8	(2-methoxymethylethoxy)propanol	1-<5%	
	Flam. Liq. 4, H227		
	acrylic polymer (72243/00/2008.0048, Germany)	1-2.49%	
	💠 Skin Irrit. 2, H315		
	propane-1,2-diol	1-2.49%	
111-76-2	2-butoxyethanol	1-2.49%	
	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Flam. Liq. 4, H227		



Printing date 01/20/2017

Version number 25

Reviewed on 01/20/2017

**Product number HEC400** 

Trade name: HYDROCOAT GLASS CLEAR TEX

(Contd. of page 1)

## 4 First-aid measures

#### · Description of first aid measures

- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
  - · Most important symptoms and effects, both acute and delayed For symptoms and effects caused by substances, refer to Section 11.
  - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

#### · Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment: No special measures required.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
34590-94-8 (	(2-methoxymethylethoxy)propanol	150 ppm
57-55-6 µ	propane-1,2-diol	30 mg/m3
7631-86-9	silicon dioxide, chemically prepared	18 mg/m3
112-34-5 2	2-(2-butoxyethoxy)ethanol	30 ppm
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m3
1344-28-1 á	aluminium oxide	15 mg/m3
9005-00-9	Octadecan-1-ol, ethoxylated	5.7 mg/m3
•		(Contd. on page 3

- US



Printing date 01/20/2017

Version number 25

Reviewed on 01/20/2017

**Product number HEC400** 

Trade name: HYDROCOAT GLASS CLEAR TEX

		(Contd. of page 2)
· PAC-2:		
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
<i>57-55-</i> 6	propane-1,2-diol	1,300 mg/m3
7631-86-9	silicon dioxide, chemically prepared	740 mg/m3
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
68439-49-6	c16-18 alcohols ethoxylated	42 mg/m3
1344-28-1	aluminium oxide	170 mg/m3
9005-00-9	Octadecan-1-ol, ethoxylated	63 mg/m3
· PAC-3:		
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
<i>57-55-</i> 6	propane-1,2-diol	7,900 mg/m3
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m3
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m3
1344-28-1	aluminium oxide	990 mg/m3
9005-00-9	Octadecan-1-ol, ethoxylated	380 mg/m3

## 7 Handling and storage

- · Handling:
  - · Precautions for safe handling No special measures required.
  - · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
  - · Storage:
    - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 °C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
  - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

34590-	94-8 (2-methoxymethylethoxy)propanol
PEL	Long-term value: 600 mg/m³, 100 ppm Skin

(Contd. on page 4)



Printing date 01/20/2017

Version number 25

Reviewed on 01/20/2017

**Product number HEC400** 

Trade name: HYDROCOAT GLASS CLEAR TEX

		(Contd. of page 3)
REL	Short-term value: 900 mg/m³, 150 ppm	
	Long-term value: 600 mg/m³, 100 ppm Skin	
TLV	Short-term value: 909 mg/m³, 150 ppm	
	Long-term value: 606 mg/m³, 100 ppm Skin	
<i>57-55-</i>	-6 propane-1,2-diol	
WEEL	Long-term value: 10 mg/m³	
111-76	6-2 2-butoxyethanol	
PEL	Long-term value: 240 mg/m³, 50 ppm Skin	
REL	Long-term value: 24 mg/m³, 5 ppm Skin	
TLV	Long-term value: 97 mg/m³, 20 ppm BEI	

### · Ingredients with biological limit values:

#### 111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine
Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

- · Breathing equipment: Not required.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
  - · General Information
    - · Appearance:
      - · Form:
      - · Color:

· Odor:

Fluid

According to product specification

Characteristic

(Contd. on page 5)



Printing date 01/20/2017

Version number 25

Reviewed on 01/20/2017

**Product number HEC400** 

Trade name: HYDROCOAT GLASS CLEAR TEX

	(Contd. of page 4)
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition · Melting point/Melting range: · Boiling point/Boiling range:	Undetermined. 100°C (212°F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:  · Lower:  · Upper:	1.1 Vol % 14.0 Vol %
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (1 mm Hg)
<ul> <li>Density at 20 °C (68 °F):</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	0.992 g/cm³ (8.278 lbs/gal) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with · Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity: · Dynamic: · Kinematic at 20 °C (68 °F): · Oxidising properties:	Not determined. 60 s (ISO 6 mm) N.A.
· Solvent content: · Water: · VOC content:	58.1 % 6.3 % 62.9 g/l / 0.53 lb/gl
· Solids content:	35.6 %
Other information (HAPS)    112-34-5 2-(2-butoxyethoxy)ethanol	0.1-<0.5%
· Other information	No further relevant information available.

# 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
  - · Chemical stability The product is stable in normal conditions of storage and use recommended
    - · Thermal decomposition / conditions to be avoided:
    - No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)



Printing date 01/20/2017

Version number 25

Reviewed on 01/20/2017

**Product number HEC400** 

Trade name: HYDROCOAT GLASS CLEAR TEX

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
  - · Acute toxicity:

$\cdot L$	· LD/LC50 values that are relevant for classification:		
	34590-94-8 (2-methoxymethylethoxy)propanol		
Oral	LD50	5135 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	19020 mg/kg (rab)	
57-55-6	57-55-6 propane-1,2-diol		
Oral	LD50	20000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
111-76-2 2-butoxyethanol			
Oral	LD50	1480 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	1100 mg/kg (rab)	

- · Primary irritant effect:
  - · on the skin: No irritant effect.
  - · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)			
	polyamide 12	3	
7631-86-9	7631-86-9 silicon dioxide, chemically prepared		
128-37-0	128-37-0 2,6-di-tert-butyl-p-cresol 3		
· NTP (National Toxicology Program)			
None of the ingredients is listed.			
· OSHA-Ca (Occupational Safety & Health Administration)			
None of the ingredients is listed.			

# 12 Ecological information

· Toxicity

· Aquatic t	· Aquatic toxicity:		
34590-94-8	34590-94-8 (2-methoxymethylethoxy)propanol		
EC50	970 mg/l (algae) (72 h)		
	1919 mg/l (daphnia) (48 h)		
LC50 (96h)	1001 mg/l (Fish)		
57-55-6 pro	pane-1,2-diol		
EC50	19000 mg/l (algae) (48 h) 18340 mg/l (daphnia) (48 h)		
	18340 mg/l (daphnia) (48 h)		
	(Contd. on page 7)		



Printing date 01/20/2017

Version number 25

Reviewed on 01/20/2017

**Product number HEC400** 

Trade name: HYDROCOAT GLASS CLEAR TEX

6)

	(Contd. of page 6)
LC50 (96h)	40613 mg/l (Fish)
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)

- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
  - · Bioaccumulative potential No further relevant information available.
  - · Mobility in soil No further relevant information available.
- · Additional ecological information:
  - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Smaller quantities can be disposed of with household waste.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.
  - · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
· DOT, ADN, IMDG, IATA	Not applicable	
UN proper shipping name		
· DOT, ADN, IMDG, IATA	Not applicable	
Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
· Class	Not applicable	
Packing group		
· DOT, IMDĠ, IATA	Not applicable	
Environmental hazards:		
· Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	· II of	
MARPOL73/78 and the IBC Code	Not applicable.	
UN "Model Regulation":	Not applicable	



Printing date 01/20/2017

Version number 25

Reviewed on 01/20/2017

**Product number HEC400** 

Trade name: HYDROCOAT GLASS CLEAR TEX

(Contd. of page 7)

### 15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

 111-76-2
 2-butoxyethanol
 1-2,49%

 112-34-5
 2-(2-butoxyethoxy)ethanol
 0.1-<0.5%</td>

 1344-28-1
 aluminium oxide
 <0.1%</td>

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
  - · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
111-76-2 2-butoxyethanol	NL 1-2,49%	
TIV/TI		

 • TLV (Threshold Limit Value established by ACGIH)

 111-76-2
 2-butoxyethanol
 A3

 112945-52-5
 silicon dioxide
 A4

 1344-28-1
 aluminium oxide
 A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - Date of preparation / last revision 01/20/2017 / 24
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances



Printing date 01/20/2017

Version number 25

Reviewed on 01/20/2017

**Product number HEC400** 

Trade name: HYDROCOAT GLASS CLEAR TEX

(Contd. of page 8)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

·Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site INRS Fiche Toxicologique

IARC International agency for research on cancer

\* Data compared to the previous version altered.

US