

Printing date 09/18/2015

Version number 26

Reviewed on 09/18/2015

1 Identification

- · Product identifier
 - · Product number HGA15
 - · Trade name: CLEAR WB TOPCOAT 2K 10GL
 - · Relevant identified uses of the substance or mixture and uses advised against

A coating composition for water-based coating and / or decoration of wooden artefacts

· Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified according to the Globally Harmonized System (GHS).

- · Label elements
 - · GHS label elements Not applicable
 - · Hazard pictograms Not applicable
 - · Signal word Not applicable
 - · Hazard statements Not applicable
- · Classification system:
 - · NFPA ratings (scale 0 4)



Health = 0 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH 0
FIRE 0
REACTIVITY 0

Health = 0Fire = 0

Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

Description: Mixture: consisting of the following components.

	· Dangerou	is components:	
Ī	111-76-2	2-butoxyethanol	2.5-4.99%
		Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 Flam. Liq. 4, H227	
	34590-94-8	(2-methoxymethylethoxy)propanol	1-<5%
		Flam. Liq. 4, H227	

(Contd. on page 2)



Printing date 09/18/2015

Version number 26

Reviewed on 09/18/2015

Product number HGA15

Trade name: CLEAR WB TOPCOAT 2K 10GL

1071-93-8	adipohydrazide	0.1-<0.5%
	Aquatic Chronic 2, H411 Aquatic Acute 2, H401	
68439-49-6	c16-18 alcohols ethoxylated	0.1-<0.5%
	Acute Tox. 3, H301 Aquatic Acute 1, H400 Eye Irrit. 2A, H319	
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) a mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC No 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC No 220-239-6] (3:1)	<0.0015%
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Skin Corr. 1B, H314 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	

4 First-aid measures

- · Description of first aid measures
 - · General information: No special measures required.
 - · After inhalation: Supply fresh air; consult doctor in case of complaints.
 - · After skin contact: Generally the product does not irritate the skin.
 - · After eye contact: Rinse opened eye for several minutes under running water.
 - · After swallowing: If symptoms persist consult doctor.
 - · Information for doctor:
 - Most important symptoms and effects, both acute and delayed

 For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Printing date 09/18/2015 Version number 26 Reviewed on 09/18/2015

Product number HGA15

Trade name: CLEAR WB TOPCOAT 2K 10GL

(Contd. of page 2)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
 - · Precautions for safe handling No special measures required.
 - · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 °C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with lin	it values that require	monitoring at the workplace:
-----------------------	------------------------	------------------------------

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 97 mg/m³, 20 ppm

BEI

34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m³, 100 ppm

Skin

REL Short-term value: 900 mg/m³, 150 ppm

Long-term value: 600 mg/m³, 100 ppm

Skin

TLV Short-term value: 909 mg/m³, 150 ppm

Long-term value: 606 mg/m³, 100 ppm

Skin

(Contd. on page 4)



Printing date 09/18/2015 Version number 26 Reviewed on 09/18/2015

Product number HGA15

Trade name: CLEAR WB TOPCOAT 2K 10GL

(Contd. of page 3)

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

- · Breathing equipment: Not required.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

Information on basic physical and	chemical properties
· General Information	The second secon
· Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	1.1 Vol %

(Contd. on page 5)



Printing date 09/18/2015 Version number 26 Reviewed on 09/18/2015

Product number HGA15

Trade name: **CLEAR WB TOPCOAT 2K 10GL**

	(Contd. of p	oage
· Upper:	14.0 Vol %	
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (1 mm Hg)	
· Density at 20 °C (68 °F):	1.037 g/cm³ (8.654 lbs/gal)	
Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· Water:	60.9 %	
· VOC content:	5.8 %	
	59.7 g/l / 0.50 lb/gl	
· Solids content:	33.2 %	
· Other information (HAPS)		
None of the ingredients is listed.		
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
 - · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects

· Acut	e toxici	ty:
$\cdot L$	D/LC50	O values that are relevant for classification:
111-76-	2 2-bu	toxyethanol
Oral	LD50	1480 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	1100 mg/kg (rab)
34590-9	94-8 (2·	methoxymethylethoxy)propanol
Oral	LD50	5135 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	19020 mg/kg (rab)
1071-93	3-8 adi _l	pohydrazide
Oral	LD50	2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
		(0 . 1 . 0)

(Contd. on page 6)



Printing date 09/18/2015

Version number 26

Reviewed on 09/18/2015

Product number HGA15

Trade name: **CLEAR WB TOPCOAT 2K 10GL**

(Contd. of page 5)

2634-33-5	1,2-benzisothiazol-3	(2H)-one
-----------	----------------------	----------

Oral LD50 1193 mg/kg (rat/szczur/mouse/souris/Maus/ratón) Dermal LD50 4115 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

- · Primary irritant effect:
 - on the skin: No irritant effect.
 - on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

· Additional toxicological information:

Contains 1,2-benzisothiazol-3(2H)-one, a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) a mixture of: 5chloro-2-methyl-4-isothiazolin-3-one [EC No 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC No 220-239-6] (3:1). May produce an allergic reaction.

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- · Carcinogenic categories
 - · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic t	oxicity:
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
34590-94-8	(2-methoxymethylethoxy)propanol
EC50	970 mg/l (algae) (72 h)
	1919 mg/l (daphnia) (48 h)
LC50 (96h)	1001 mg/l (Fish)
1071-93-8 a	ndipohydrazide
EC50	9.19 mg/l (algae) (72 h)
	101 mg/l (daphnia) (48 h)
LC50 (96h)	101 mg/l (Fish)
2634-33-5 1	,2-benzisothiazol-3(2H)-one
EC50	2.94 mg/l (daphnia) (48 h)
LC50 (96h)	2.18 mg/l (Fish)
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) a mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC No 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC No 220-239-6] (3:1)
EC50	0.1 mg/l (daphnia) (48 h)



Printing date 09/18/2015 Version number 26 Reviewed on 09/18/2015

Product number HGA15

Trade name: CLEAR WB TOPCOAT 2K 10GL

(Contd. of page 6)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Smaller quantities can be disposed of with household waste.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

UN-Number		
· DOT, ADN, IMDG, IATA	Not applicable	
UN proper shipping name		
· DOT, ADN, IMDG, IATA	Not applicable	
Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
· Class	Not applicable	
Packing group		
· DOT, IMDG, IATA	Not applicable	
Environmental hazards:		
· Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

(Contd. on page 8)



Printing date 09/18/2015

Version number 26

Reviewed on 09/18/2015

Product number HGA15

Trade name: CLEAR WB TOPCOAT 2K 10GL

(Contd. of page 7)

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

2,5-4,99%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

NL 2,5-4,99%

· TLV (Threshold Limit Value established by ACGIH)

111-76-2 2-butoxyethanol

*A*3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - Date of preparation / last revision 09/18/2015 / 25
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

(Contd. on page 9)



Printing date 09/18/2015

Version number 26

Reviewed on 09/18/2015

Product number HGA15

Trade name: **CLEAR WB TOPCOAT 2K 10GL**

(Contd. of page 8)

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - AcuteHazard, Category 2 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· Sources

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site INRS Fiche Toxicologique

IARC International agency for research on cancer

* * Data compared to the previous version altered.