

1 Identification

- **Product identifier**
 - Product number HGT6073
 - Trade name: **WB INT PIGM TOP-COAT 30 SH**
 - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
 - Manufacturer/Supplier:
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - Information department:
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - Emergency telephone number:
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification


- **Classification of the substance or mixture**
The product is not classified according to the Globally Harmonized System (GHS).

- **Label elements**

- GHS label elements Not applicable
 - Hazard pictograms Not applicable
 - Signal word Not applicable
 - Hazard statements Not applicable

- **Classification system:**

- NFPA ratings (scale 0 - 4)



Health = 0
Fire = 0
Reactivity = 0

- HMIS-ratings (scale 0 - 4)



Health = 0
Fire = 0
Reactivity = 0

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- Description: Mixture: consisting of the following components.

- **Dangerous components:**

111-76-2	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Flam. Liq. 4, H227	1-2.49%
34590-94-8	(2-methoxymethylethoxy)propanol Flam. Liq. 4, H227	1-<5%

4 First-aid measures

- **Description of first aid measures**

- General information: No special measures required.

(Contd. on page 2)

Product number HGT6073

Trade name: WB INT PIGM TOP-COAT 30 SH

(Contd. of page 1)

- *After inhalation:* Supply fresh air; consult doctor in case of complaints.
- *After skin contact:* Generally the product does not irritate the skin.
- *After eye contact:* Rinse opened eye for several minutes under running water.
- *After swallowing:* If symptoms persist consult doctor.
- *Information for doctor:*
 - *Most important symptoms and effects, both acute and delayed*
For symptoms and effects caused by substances, refer to Section 11.
 - *Indication of any immediate medical attention and special treatment needed*
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - *Suitable extinguishing agents:* Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
 - *Protective equipment:* No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to Section 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

7631-86-9	silicon dioxide, chemically prepared	18 mg/m3
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
21645-51-2	aluminium hydroxide	8.7 mg/m3
25322-69-4	Propane-1,2-diol, propoxylated	30 mg/m3
1314-23-4	zirconium dioxide	14 mg/m3
68439-49-6	c16-18 alcohols ethoxylated	3.8 mg/m3
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm

· PAC-2:

7631-86-9	silicon dioxide, chemically prepared	740 mg/m3
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
21645-51-2	aluminium hydroxide	73 mg/m3
25322-69-4	Propane-1,2-diol, propoxylated	330 mg/m3
1314-23-4	zirconium dioxide	110 mg/m3

(Contd. on page 3)

Product number HGT6073

Trade name: WB INT PIGM TOP-COAT 30 SH

(Contd. of page 2)

68439-49-6	c16-18 alcohols ethoxylated	42 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
· PAC-3:		
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm
21645-51-2	aluminium hydroxide	440 mg/m ³
25322-69-4	Propane-1,2-diol, propoxylated	2,000 mg/m ³
1314-23-4	zirconium dioxide	680 mg/m ³
68439-49-6	c16-18 alcohols ethoxylated	250 mg/m ³
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm

7 Handling and storage

· Handling:

- *Precautions for safe handling* No special measures required.
- *Information about protection against explosions and fires:* No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 °C

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: None.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm
Skin

REL Long-term value: 24 mg/m³, 5 ppm
Skin

TLV Long-term value: 97 mg/m³, 20 ppm
BEI

34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m³, 100 ppm
Skin

(Contd. on page 4)

Product number HGT6073

Trade name: WB INT PIGM TOP-COAT 30 SH

(Contd. of page 3)

REL Short-term value: 900 mg/m , 150 ppm
Long-term value: 600 mg/m , 100 ppm
Skin

TLV Short-term value: 909 mg/m , 150 ppm
Long-term value: 606 mg/m , 100 ppm
Skin

· **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: Butoxyacetic acid with hydrolysis

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

· **Breathing equipment:** Not required.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

100 °C (212 °F)

· **Flash point:**

Not applicable.

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

240 °C (464 °F)

(Contd. on page 5)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 03/13/2017

Version number 8

Reviewed on 03/12/2017

Product number HGT6073**Trade name:** WB INT PIGM TOP-COAT 30 SH

(Contd. of page 4)

· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	14.0 Vol %
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (1 mm Hg)
· Density at 20 °C (68 °F):	1.222 g/cm (10.198 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	60 s (ISO 6 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· Water:	50.8 %
· VOC content:	4.3 %
	52.2 g/l / 0.44 lb/gl
· Solids content:	44.9 %
· Other information (HAPS)	
112-34-5 2-(2-butoxyethoxy)ethanol	0.1-<0.5%
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
 - **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
111-76-2 2-butoxyethanol		
Oral	LD50	1480 mg/kg (rat/szczur/mouse/souris/Maus/ratón)

(Contd. on page 6)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 03/13/2017

Version number 8

Reviewed on 03/12/2017

Product number HGT6073**Trade name: WB INT PIGM TOP-COAT 30 SH**

(Contd. of page 5)

Dermal	LD50	1100 mg/kg (rab)
34590-94-8 (2-methoxymethylethoxy)propanol		
Oral	LD50	5135 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	19020 mg/kg (rab)

- **Primary irritant effect:**

- *on the skin:* No irritant effect.

- *on the eye:* No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- **Carcinogenic categories**

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- **Toxicity**

· Aquatic toxicity:	
111-76-2 2-butoxyethanol	
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
34590-94-8 (2-methoxymethylethoxy)propanol	
EC50	970 mg/l (algae) (72 h)
	1919 mg/l (daphnia) (48 h)
LC50 (96h)	1001 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)

Printing date 03/13/2017

Version number 8

Reviewed on 03/12/2017

Product number HGT6073

Trade name: WB INT PIGM TOP-COAT 30 SH

(Contd. of page 6)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**

· DOT, ADN, IMDG, IATA

Not applicable

· **UN proper shipping name**

· DOT, ADN, IMDG, IATA

Not applicable

· **Transport hazard class(es)**

· DOT, ADR, ADN, IMDG, IATA

· Class

Not applicable

· **Packing group**

· DOT, IMDG, IATA

Not applicable

· **Environmental hazards:**

· Marine pollutant:

No

· **Special precautions for user**

Not applicable.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **UN "Model Regulation":**

Not applicable

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

111-76-2 2-butoxyethanol

1-2,49%

112-34-5 2-(2-butoxyethoxy)ethanol

0.1-<0.5%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

(Contd. on page 8)

US

Printing date 03/13/2017

Version number 8

Reviewed on 03/12/2017

Product number HGT6073
Trade name: WB INT PIGM TOP-COAT 30 SH

(Contd. of page 7)

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	15-19.9%
------------	---	---------------	----------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

111-76-2	2-butoxyethanol	NL	1-2,49%
----------	-----------------	----	---------

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
111-76-2	2-butoxyethanol	A3
1314-23-4	zirconium dioxide	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	15-19.9%
------------	---	----------

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone

· Date of preparation / last revision 03/13/2017 / 7

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids . Category 4

Acute Tox. 4: Acute toxicity . Category 4

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

(Contd. on page 9)

Safety Data Sheet
29 CFR Parts 1910 1915 1926

Printing date 03/13/2017

Version number 8

Reviewed on 03/12/2017

Product number HGT6073**Trade name: WB INT PIGM TOP-COAT 30 SH**

(Contd. of page 8)

*INRS Fiche Toxicologique**IARC International agency for research on cancer**. * Data compared to the previous version altered.*

US