

## 1 Identification

- **Product identifier**
  - Product number KGA402
  - Trade name: **NEUTRAL ACRYLIC SELF S 50SH**
    - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
  - Manufacturer/Supplier:  
IVM Chemicals srl  
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
  - Information department:  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - Emergency telephone number:  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

 Flam. Liq. 2 H225 Highly flammable liquid and vapor.
 

---



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

 STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
 

---



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

 STOT SE 3 H336 May cause drowsiness or dizziness.
 

---

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

**Product number KGA402**  
**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*n*-butyl acetate  
xylene  
toluene  
ethylbenzene  
methyl methacrylate

· **Hazard statements**

H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

123-86-4	<i>n</i> -butyl acetate	50-74.99%
	Flam. Liq. 3, H226 STOT SE 3, H336	
110-19-0	isobutyl acetate	5-9.99%
	Flam. Liq. 2, H225 STOT SE 3, H336	

(Contd. on page 3)

**Product number KGA402**

**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

		(Contd. of page 2)
1330-20-7	<p>xylene</p> <p>Flam. Liq. 3, H226</p> <p>STOT RE 2, H373; Asp. Tox. 1, H304</p> <p>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335</p> <p>Aquatic Chronic 3, H412</p>	5-9.99%
67-63-0	<p>propan-2-ol</p> <p>Flam. Liq. 2, H225</p> <p>Eye Irrit. 2A, H319; STOT SE 3, H336</p>	1-2.49%
108-88-3	<p>toluene</p> <p>Flam. Liq. 2, H225</p> <p>Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304</p> <p>Skin Irrit. 2, H315; STOT SE 3, H336</p> <p>Aquatic Chronic 3, H412</p>	1-2.49%
78-83-1	<p>2-methylpropan-1-ol</p> <p>Flam. Liq. 3, H226</p> <p>Eye Dam. 1, H318</p> <p>Skin Irrit. 2, H315; STOT SE 3, H335-H336</p>	1-2.49%
100-41-4	<p>ethylbenzene</p> <p>Flam. Liq. 2, H225</p> <p>Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304</p> <p>Acute Tox. 4, H332</p>	1-2.49%
80-62-6	<p>methyl methacrylate</p> <p>Flam. Liq. 2, H225</p> <p>Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335</p>	≥0.1-<0.5%
131-56-6	<p>2,4-dihydroxybenzophenone</p> <p>Repr. 2, H361</p> <p>Aquatic Chronic 2, H411</p> <p>Eye Irrit. 2A, H319</p> <p>Aquatic Acute 2, H401</p>	≥0.25-<0.5%

## 4 First-aid measures

### · Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

#### · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact: Immediately wash with water and soap and rinse thoroughly.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · After swallowing: Do not induce vomiting; immediately call for medical help.

(Contd. on page 4)

**Product number KGA402**

**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 3)

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Alcohol resistant foam, CO, powder, water spray/mist.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-I:**

123-86-4	n-butyl acetate	5 ppm
110-19-0	isobutyl acetate	450 ppm
1330-20-7	xylene	130 ppm
67-63-0	propan-2-ol	400 ppm
108-88-3	toluene	67 ppm
78-83-1	2-methylpropan-1-ol	150 ppm

(Contd. on page 5)

**Product number KGA402****Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 4)

100-41-4	ethylbenzene	33 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
9002-88-4	Polyethylene low density	16 mg/m
80-62-6	methyl methacrylate	17 ppm

**· PAC-2:**

123-86-4	n-butyl acetate	200 ppm
110-19-0	isobutyl acetate	1300* ppm
1330-20-7	xylene	920* ppm
67-63-0	propan-2-ol	2000* ppm
108-88-3	toluene	560 ppm
78-83-1	2-methylpropan-1-ol	1,300 ppm
100-41-4	ethylbenzene	1100* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
9002-88-4	Polyethylene low density	170 mg/m
80-62-6	methyl methacrylate	120 ppm

**· PAC-3:**

123-86-4	n-butyl acetate	3000* ppm
110-19-0	isobutyl acetate	7500** ppm
1330-20-7	xylene	2500* ppm
67-63-0	propan-2-ol	12000** ppm
108-88-3	toluene	3700* ppm
78-83-1	2-methylpropan-1-ol	8000* ppm
100-41-4	ethylbenzene	1800* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
9002-88-4	Polyethylene low density	1,000 mg/m
80-62-6	methyl methacrylate	570 ppm

## 7 Handling and storage

**· Handling:****· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

**· Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 6)

US

**Product number KGA402**

**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 5)

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

<b>123-86-4 n-butyl acetate (50-74.99%)</b>	
PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 712 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm
<b>67-63-0 propan-2-ol (1-2.49%)</b>	
PEL	Long-term value: 980 mg/m , 400 ppm
REL	Short-term value: 1225 mg/m , 500 ppm Long-term value: 980 mg/m , 400 ppm
TLV	Short-term value: 984 mg/m , 400 ppm Long-term value: 492 mg/m , 200 ppm BEI
<b>78-83-1 2-methylpropan-1-ol (1-2.49%)</b>	
PEL	Long-term value: 300 mg/m , 100 ppm
REL	Long-term value: 150 mg/m , 50 ppm
TLV	Long-term value: 152 mg/m , 50 ppm
<b>100-41-4 ethylbenzene (1-2.49%)</b>	
PEL	Long-term value: 435 mg/m , 100 ppm

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2020

Version number 1

Reviewed on 01/16/2020

**Product number KGA402****Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 6)

REL Short-term value: 545 mg/m , 125 ppm  
 Long-term value: 435 mg/m , 100 ppm

TLV Long-term value: 87 mg/m , 20 ppm

BEI

**80-62-6 methyl methacrylate ( $\geq 0.1$ -<0.5%)**

PEL Long-term value: 410 mg/m , 100 ppm

REL Long-term value: 410 mg/m , 100 ppm

TLV Short-term value: 410 mg/m , 100 ppm  
 Long-term value: 205 mg/m , 50 ppm

DSEN

**· Ingredients with biological limit values:****1330-20-7 xylene (5-9.99%)**

BEI 1.5 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Methylhippuric acids

**67-63-0 propan-2-ol (1-2.49%)**

BEI 40 mg/L  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Acetone (background, nonspecific)

**108-88-3 toluene (1-2.49%)**

BEI 0.02 mg/L  
 Medium: blood  
 Time: prior to last shift of workweek  
 Parameter: Toluene

0.03 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Toluene

0.3 mg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: o-Cresol with hydrolysis (background)

**100-41-4 ethylbenzene (1-2.49%)**

BEI 0.7 g/g creatinine  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
 Medium: end-exhaled air  
 Time: not critical  
 Parameter: Ethyl benzene (semi-quantitative)

(Contd. on page 8)

US



**Product number KGA402**

**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 7)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· **Breathing equipment:**

Short term filter device:

Filter AX



Suitable respiratory protective device recommended.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

(Contd. on page 9)

US



# Safety Data Sheet acc. to OSHA HCS

Printing date 01/16/2020

Version number 1

Reviewed on 01/16/2020

**Product number KGA402****Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 8)

· <b>Color:</b>	According to product specification	
· <b>Odor:</b>	Characteristic	
· <b>Odor threshold:</b>	Not determined.	
· <b>pH-value:</b>	Not determined.	
· <b>Change in condition</b>		
· <b>Melting point/Melting range:</b>	Undetermined.	
· <b>Boiling point/Boiling range:</b>	82 °C (179.6 °F)	
· <b>Flash point:</b>	-4 °C (24.8 °F)	
· <b>Flammability (solid, gaseous):</b>	Not applicable.	
· <b>Ignition temperature:</b>	370 °C (698 °F)	
· <b>Decomposition temperature:</b>	Not determined.	
· <b>Auto igniting:</b>	Product is not selfigniting.	
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· <b>Explosion limits:</b>		
· <b>Lower:</b>	1 Vol %	
· <b>Upper:</b>	12 Vol %	
· <b>Vapor pressure at 20 °C (68 °F):</b>	43 hPa (32.3 mm Hg)	
· <b>Density (+/- 0,03) at 20 °C (68 °F):</b>	1 g/cm (8.345 lbs/gal)	
· <b>Relative density</b>	Not determined.	
· <b>Vapor density</b>	Not determined.	
· <b>Evaporation rate</b>	Not determined.	
· <b>Solubility in / Miscibility with</b>		
· <b>Water:</b>	Not miscible or difficult to mix.	
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.	
· <b>Viscosity:</b>		
· <b>Dynamic:</b>	Not determined.	
· <b>Kinematic at 20 °C (68 °F):</b>	55 s (ISO 6 mm)	
· <b>Oxidising properties:</b>	N.A.	
· <b>Solvent content:</b>		
· <b>VOC content:</b>	73.44 % 734.4 g/l / 6.13 lb/gal	
· <b>Solids content:</b>	26.6 %	
· <b>Other information (HAPS)</b>		
1330-20-7	xylene	5-9.99%
108-88-3	toluene	1-2.49%
100-41-4	ethylbenzene	1-2.49%
80-62-6	methyl methacrylate	≥0.1-<0.5%

(Contd. on page 10)

US

**Product number KGA402**  
**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 9)

· **Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
  - **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Reacts with strong acids and oxidizing agents.  
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
  - **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

<b>123-86-4 n-butyl acetate</b>		
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
<b>110-19-0 isobutyl acetate</b>		
Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)
<b>1330-20-7 xylene</b>		
Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4h.	27.571 mg/l (mouse)
<b>67-63-0 propan-2-ol</b>		
Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)
<b>108-88-3 toluene</b>		
Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)

(Contd. on page 11)

**Product number KGA402**  
**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 10)

<b>78-83-1 2-methylpropan-1-ol</b>		
Oral	LD50	2,460 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h.	19.2 mg/l (mouse)
<b>100-41-4 ethylbenzene</b>		
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)
<b>80-62-6 methyl methacrylate</b>		
Oral	LD50	7,872 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	78 mg/l (mouse)
<b>131-56-6 2,4-dihydroxybenzophenone</b>		
Oral	LD50	7,220 mg/kg (mouse)

- **Primary irritant effect:**
  - **on the skin:** No irritant effect.
  - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
  - Irritant
  - Causes serious eye irritation.
  - May cause drowsiness or dizziness.
  - Contains methyl methacrylate. May produce an allergic reaction.
- **Carcinogenic categories**
  - Ethylbenzene
  - From IARC MONOGRAPHS VOLUME 77/2000
  - Human carcinogenicity data
  - Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

**Evaluation**

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

<b>· IARC (International Agency for Research on Cancer - Cl. 1 and 2)</b>		
100-41-4	ethylbenzene	2B
<b>· NTP (National Toxicology Program)</b>		
None of the ingredients is listed.		
<b>· OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

US

(Contd. on page 12)

**Product number KGA402**  
**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 11)

## 12 Ecological information

### · Toxicity

#### · Aquatic toxicity:

##### **123-86-4 n-butyl acetate**

EC50	397 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)

##### **110-19-0 isobutyl acetate**

EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)

##### **1330-20-7 xylene**

EC50	2.2 mg/l (algae) (72h)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)

##### **67-63-0 propan-2-ol**

EC50	1,001 mg/l (algae) (72 h)
	10,000 mg/l (daphnia) (24 h)
LC50 (96h)	9,640 mg/l (Fish)

##### **108-88-3 toluene**

EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)

##### **78-83-1 2-methylpropan-1-ol**

EC50	1,799 mg/l (algae) (72 h)
	1,100 mg/l (daphnia) (48 h)
LC50 (96h)	1,430 mg/l (Fish)

##### **100-41-4 ethylbenzene**

EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)

##### **80-62-6 methyl methacrylate**

EC50	170 mg/l (algae) (72 h)
LC50 (96h)	191 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 13)

**Product number KGA402**  
**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 12)

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· **UN-Number**

· DOT, IMDG, IATA UN1263

· **UN proper shipping name**

· DOT Paint  
· IMDG, IATA PAINT

· **Transport hazard class(es)**

· DOT



· Class 3 Flammable liquids  
· Label 3  
· Class 3 Flammable liquids  
· Label 3

· IMDG, IATA



· Class 3 Flammable liquids  
· Label 3

(Contd. on page 14)

**Product number KGA402**  
**Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 13)

· <b>Packing group</b>	III
· DOT, IMDG, IATA	
· <b>Environmental hazards:</b>	
· Marine pollutant:	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· Danger code (Kemler):	-
· EMS Number:	F-E, S-E
· Stowage Category	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>IMDG</b>	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

## 15 Regulatory information

### · SARA

#### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

#### · Section 313 (Specific toxic chemical listings) :

1330-20-7	xylene	5-9.99%
67-63-0	propan-2-ol	1-2.49%
108-88-3	toluene	1-2.49%
100-41-4	ethylbenzene	1-2.49%
80-62-6	methyl methacrylate	≥0.1-<0.5%

#### · TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

#### · Hazardous Air Pollutants

1330-20-7	xylene
108-88-3	toluene
100-41-4	ethylbenzene
80-62-6	methyl methacrylate

(Contd. on page 15)

**Product number** KGA402  
**Trade name:** NEUTRAL ACRYLIC SELF S 50SH

(Contd. of page 14)

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene	*	1-2.49%
----------	--------------	---	---------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene		1-2.49%
----------	---------	--	---------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	5-9.99%
108-88-3	toluene	II	1-2.49%
100-41-4	ethylbenzene	D	1-2.49%
80-62-6	methyl methacrylate	E, NL	≥0.1-<0.5%

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
67-63-0	propan-2-ol	A4
108-88-3	toluene	A4
100-41-4	ethylbenzene	A3
80-62-6	methyl methacrylate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 01/16/2020 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 16)



# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/16/2020

Version number 1

Reviewed on 01/16/2020

**Product number KGA402****Trade name: NEUTRAL ACRYLIC SELF S 50SH**

(Contd. of page 15)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Acute Tox. 4: Acute toxicity . Category 4

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Dam. 1: Serious eye damage/eye irritation . Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A

Skin Sens. 1: Skin sensitisation . Category 1

Carc. 2: Carcinogenicity . Category 2

Repr. 2: Reproductive toxicity . Category 2

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2

Asp. Tox. 1: Aspiration hazard . Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

**• Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL  
and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer