

## 1 Identification

- **Product identifier**
  - *Product number* KKR106
  - *Trade name:* **WHITE PU CONVERTER HC 10 GL**
  - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
  - *Manufacturer/Supplier:*  
IVM Chemicals srl  
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
  - *Information department:*  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - *Emergency telephone number:*  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

- *Hazard pictograms*



GHS02 GHS07 GHS08

- *Signal word* Danger

- *Hazard-determining components of labeling:*

isobutyl acetate

xylene

ethyl acetate

n-butyl acetate

- *Hazard statements*

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 1)

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:**

**NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**



Health = \*2

Fire = 3

Reactivity = 0

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures**

**Description:** Mixture: consisting of the following components.






**Dangerous components:**

110-19-0	isobutyl acetate ⚠ Flam. Liq. 2, H225 ⚠ STOT SE 3, H336	12.5-15%
1330-20-7	xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	2.5-4.99%
141-78-6	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	2.5-4.99%
123-86-4	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	1-2.49%
108-65-6	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	1-2.49%
78-83-1	2-methylpropan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-2.49%

(Contd. on page 3)

**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

		(Contd. of page 2)
100-41-4	ethylbenzene  Flam. Liq. 2, H225  Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H332	0.5-1%
64-17-5	ethanol  Flam. Liq. 2, H225  Eye Irrit. 2A, H319	≥0.1-<0.5%

#### 4 First-aid measures

##### · Description of first aid measures

###### · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

###### · After inhalation:

Supply fresh air; consult doctor in case of complaints.

###### · After skin contact:

Generally the product does not irritate the skin.

###### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

###### · After swallowing:

Do not induce vomiting; immediately call for medical help.

###### · Information for doctor:

###### · Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

###### · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

##### · Extinguishing media

· Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

##### · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

##### · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

###### · Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

#### 6 Accidental release measures

##### · Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

##### · Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

##### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

# Safety Data Sheet

## 29 CFR Parts 1910 1915 1926

Printing date 06/19/2018

Version number 64

Reviewed on 06/18/2018

**Product number KKR106****Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 3)

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

**· Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**· Protective Action Criteria for Chemicals**

<b>· PAC-1:</b>		
110-19-0	isobutyl acetate	450 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
1330-20-7	xylene	130 ppm
141-78-6	ethyl acetate	1,200 ppm
123-86-4	n-butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
21645-51-2	aluminium hydroxide	8.7 mg/m
471-34-1	calcium carbonate	45 mg/m
78-83-1	2-methylpropan-1-ol	150 ppm
100-41-4	ethylbenzene	33 ppm
1314-23-4	zirconium oxide	14 mg/m
9002-88-4	Polyethylene low density	16 mg/m
64-17-5	ethanol	1,800 ppm

<b>· PAC-2:</b>		
110-19-0	isobutyl acetate	1300* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
1330-20-7	xylene	920* ppm
141-78-6	ethyl acetate	1,700 ppm
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
21645-51-2	aluminium hydroxide	73 mg/m
471-34-1	calcium carbonate	210 mg/m
78-83-1	2-methylpropan-1-ol	1,300 ppm
100-41-4	ethylbenzene	1100* ppm
1314-23-4	zirconium oxide	110 mg/m
9002-88-4	Polyethylene low density	170 mg/m
64-17-5	ethanol	3300* ppm

<b>· PAC-3:</b>		
110-19-0	isobutyl acetate	7500** ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
1330-20-7	xylene	2500* ppm
141-78-6	ethyl acetate	10000** ppm
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
21645-51-2	aluminium hydroxide	440 mg/m
471-34-1	calcium carbonate	1,300 mg/m
78-83-1	2-methylpropan-1-ol	8000* ppm

(Contd. on page 5)

**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 4)

100-41-4	ethylbenzene	1800* ppm
1314-23-4	zirconium oxide	680 mg/m
9002-88-4	Polyethylene low density	1,000 mg/m
64-17-5	ethanol	15000* ppm

## 7 Handling and storage

### · Handling:

#### · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

#### · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### · Conditions for safe storage, including any incompatibilities

#### · Storage:

##### · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

##### · Information about storage in one common storage facility: Not required.

##### · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

### · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

### · Additional information about design of technical systems: No further data; see item 7.

### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 712 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm

#### 141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 1440 mg/m , 400 ppm

(Contd. on page 6)

# Safety Data Sheet

## 29 CFR Parts 1910 1915 1926

Printing date 06/19/2018

Version number 64

Reviewed on 06/18/2018

**Product number KKR106****Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 5)

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 712 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

**78-83-1 2-methylpropan-1-ol**

PEL	Long-term value: 300 mg/m , 100 ppm
REL	Long-term value: 150 mg/m , 50 ppm
TLV	Long-term value: 152 mg/m , 50 ppm

**100-41-4 ethylbenzene**

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 87 mg/m , 20 ppm BEI

**· Ingredients with biological limit values:****1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

**· Additional information:** The lists that were valid during the creation were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 7)

US



**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 6)

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Liquid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

77 °C (170.6 °F)

· **Flash point:**

-4 °C (24.8 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

315 °C (599 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:**

1.1 Vol %

· **Upper:**

12 Vol %

· **Vapor pressure at 20 °C (68 °F):**

97 hPa (72.8 mm Hg)

(Contd. on page 8)

**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 7)

· <b>Density at 20 °C (68 °F):</b>		1.363 g/cm (11.374 lbs/gal)
· <b>Relative density</b>		Not determined.
· <b>Vapor density</b>		Not determined.
· <b>Evaporation rate</b>		Not determined.
· <b>Solubility in / Miscibility with</b>		
· <b>Water:</b>		Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b> Not determined.		
· <b>Viscosity:</b>		
· <b>Dynamic:</b>		Not determined.
· <b>Kinematic at 20 °C (68 °F):</b>		101 s (ISO 6 mm)
· <b>Oxidising properties:</b>		N.A.
· <b>Solvent content:</b>		
· <b>Water:</b>		0.0 %
· <b>VOC content:</b>		27.33 %
		372.5 g/l / 3.11 lb/gl
· <b>Solids content:</b>		72.7 %
· <b>Other information (HAPS)</b>		
1330-20-7	xylene	2.5-4.99%
100-41-4	ethylbenzene	0.5-1%
· <b>Other information</b>		No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
  - **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Reacts with oxidizing agents.  
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
in case of possible formation of combustion:  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
  - **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>110-19-0 isobutyl acetate</b>		
Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)

(Contd. on page 9)



**Product number KKR106**
**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 8)

**1330-20-7 xylene**

Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4h.	27.571 mg/l (mouse)

**141-78-6 ethyl acetate**

Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)

**123-86-4 n-butyl acetate**

Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral	LD50	8,532 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/l (mouse)

**78-83-1 2-methylpropan-1-ol**

Oral	LD50	2,460 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h.	19.2 mg/l (mouse)

**100-41-4 ethylbenzene**

Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)

**64741-65-7 Naphtha (petroleum), heavy alkylate**

Oral	LD50	6,001 mg/kg (mouse)
Dermal	LD50	3,001 mg/kg (rabbit)

**64-17-5 ethanol**

Oral	LD50	10,470 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	124.7 mg/l (mouse)

**· Primary irritant effect:**

- *on the skin:* No irritant effect.
- *on the eye:* Irritating effect.

**· Sensitization:** No sensitizing effects known.

**· Additional toxicological information:**
**Irritant**

Causes serious eye irritation.

May cause drowsiness or dizziness.

Contains Fatty acids, tallow, oleylamine compounds. May produce an allergic reaction.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

**· Carcinogenic categories**
**Titanium dioxide**

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in

(Contd. on page 10)

**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 9)

humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· **IARC (International Agency for Research on Cancer - Cl. 1 and 2)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

### · Toxicity

· **Aquatic toxicity:**

#### **110-19-0 isobutyl acetate**

EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)

#### **1330-20-7 xylene**

EC50	2.2 mg/l (algae) (72h)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)

#### **141-78-6 ethyl acetate**

EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)

#### **123-86-4 n-butyl acetate**

EC50	397 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)

#### **108-65-6 2-methoxy-1-methylethyl acetate**

EC50	1,001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)

(Contd. on page 11)

**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 10)

**78-83-1 2-methylpropan-1-ol**

EC50	1,799 mg/l (algae) (72 h)
	1,100 mg/l (daphnia) (48 h)
LC50 (96h)	1,430 mg/l (Fish)

**100-41-4 ethylbenzene**

EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)

**64-17-5 ethanol**

EC50	5,012 mg/l (daphnia) (48 h)
LC50 (96h)	15.3 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

110-19-0	isobutyl acetate	.
1330-20-7	xylene	.
141-78-6	ethyl acetate	.
123-86-4	n-butyl acetate	.
108-65-6	2-methoxy-1-methylethyl acetate	.
78-83-1	2-methylpropan-1-ol	.
100-41-4	ethylbenzene	.
64-17-5	ethanol	.

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

· **UN-Number**

· **DOT**

NA1263

(Contd. on page 12)

US

Printing date 06/19/2018



Version number 64

Reviewed on 06/18/2018

**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 11)

· <b>IMDG, IATA</b>	UN1263
· <b>UN proper shipping name</b>	
· <b>DOT</b>	Paint
· <b>IMDG, IATA</b>	PAINT
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Danger code (Kemler):</b>	-
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
Requirements of Federal Register

(Contd. on page 13)

**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 12)

· **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	2.5-4.99%
100-41-4	ethylbenzene	0.5-1%
67-63-0	propan-2-ol	<0.01%
78-93-3	butanone	<0.01%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	30-49.9%
100-41-4	ethylbenzene	*	0.5-1%

· **Chemicals known to cause reproductive toxicity for females:**

70657-70-4	2-methoxypropyl acetate	<0.01%
------------	-------------------------	--------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol	≥0.1-<0.5%
---------	---------	------------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	2.5-4.99%
100-41-4	ethylbenzene	D	0.5-1%
78-93-3	butanone	I	<0.01%

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
1314-23-4	zirconium oxide	A4
64-17-5	ethanol	A3
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	30-49.9%
------------	---	----------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

(Contd. on page 14)

**Product number KKR106**

**Trade name: WHITE PU CONVERTER HC 10 GL**

(Contd. of page 13)

- **Contact:** See emergency phone
- **Date of preparation / last revision** 06/19/2018 / 63
- **Abbreviations and acronyms:**
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - ACGIH: American Conference of Governmental Industrial Hygienists
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMIS: Hazardous Materials Identification System (USA)
  - VOC: Volatile Organic Compounds (USA, EU)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit
  - REL: Recommended Exposure Limit
  - BEI: Biological Exposure Limit
  - Flam. Liq. 2: Flammable liquids . Category 2
  - Flam. Liq. 3: Flammable liquids . Category 3
  - Acute Tox. 4: Acute toxicity . Category 4
  - Skin Irrit. 2: Skin corrosion/irritation . Category 2
  - Eye Dam. 1: Serious eye damage/eye irritation . Category 1
  - Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A
  - Carc. 2: Carcinogenicity . Category 2
  - STOT SE 3: Specific target organ toxicity (single exposure) . Category 3
  - STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2
  - Asp. Tox. 1: Aspiration hazard . Category 1
  - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3
- **Sources**
  - REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments
  - Agency ECHA web site
  - INRS Fiche Toxicologique
  - IARC International agency for research on cancer
- **\* Data compared to the previous version altered.**