

1 Identification

- **Product identifier**
 - *Product number* KKR513
 - *Trade name:* **ACR TOP-C WHITE 20SH**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

 Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

 STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

 STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

- *Hazard pictograms*



GHS02



GHS07



GHS08

(Contd. on page 2)

US

Product number KKR513

Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

n-butyl acetate

xylene

ethylbenzene

toluene

methyl methacrylate

E96096

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *2

Fire = 3

Reactivity = 0

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

123-86-4	<i>n</i> -butyl acetate	30-49.99%
	Flam. Liq. 3, H226 STOT SE 3, H336	

(Contd. on page 3)

Product number KKR513
Trade name: ACR TOP-C WHITE 20SH

		(Contd. of page 2)
110-19-0	isobutyl acetate ⚠ Flam. Liq. 2, H225 ⚠ STOT SE 3, H336	10-12.49%
1330-20-7	xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	5-9.99%
100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	1-2.49%
67-63-0	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	1-2.49%
108-88-3	toluene ⚠ Flam. Liq. 2, H225 ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Chronic 3, H412	1-2.49%
78-83-1	2-methylpropan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-2.49%
80-62-6	methyl methacrylate ⚠ Flam. Liq. 2, H225 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<0.5%
131-56-6	2,4-dihydroxybenzophenone ⚠ Repr. 2, H361 ⚠ Aquatic Chronic 2, H411 ⚠ Eye Irrit. 2A, H319 Aquatic Acute 2, H401	≥0.1-<0.25%
64-17-5	ethanol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319	<0.5%
	E96096 ⚠ Skin Sens. 1B, H317 Aquatic Chronic 4, H413	≥0.1-<0.5%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

(Contd. on page 4)

Product number KKR513

Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 3)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

For symptoms and effects caused by substances, refer to Section 11.

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Alcohol resistant foam, CO, powder, water spray/mist.

· **For safety reasons unsuitable extinguishing agents:**

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 5)

Product number KKR513
Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 4)

· Protective Action Criteria for Chemicals

· PAC-1:		
123-86-4	<i>n</i> -butyl acetate	5 ppm
110-19-0	isobutyl acetate	450 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m
67-63-0	propan-2-ol	400 ppm
108-88-3	toluene	67 ppm
78-83-1	2-methylpropan-1-ol	150 ppm
9002-88-4	Polyethylene low density	16 mg/m
80-62-6	methyl methacrylate	17 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
· PAC-2:		
123-86-4	<i>n</i> -butyl acetate	200 ppm
110-19-0	isobutyl acetate	1300* ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m
67-63-0	propan-2-ol	2000* ppm
108-88-3	toluene	560 ppm
78-83-1	2-methylpropan-1-ol	1,300 ppm
9002-88-4	Polyethylene low density	170 mg/m
80-62-6	methyl methacrylate	120 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
· PAC-3:		
123-86-4	<i>n</i> -butyl acetate	3000* ppm
110-19-0	isobutyl acetate	7500** ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
67-63-0	propan-2-ol	12000** ppm
108-88-3	toluene	3700* ppm
78-83-1	2-methylpropan-1-ol	8000* ppm
9002-88-4	Polyethylene low density	1,000 mg/m
80-62-6	methyl methacrylate	570 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm

US

(Contd. on page 6)

Product number KKR513

Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 5)

7 Handling and storage

· Handling:

· Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

- Store in a cool, well-ventilated area, away from heat and sources of ignition
- Provide solvent resistant, sealed floor.
- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
- In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate (30-49.99%)	
PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm
	Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 712 mg/m , 150 ppm
	Long-term value: 238 mg/m , 50 ppm
100-41-4 ethylbenzene (1-2.49%)	
PEL	Long-term value: 435 mg/m , 100 ppm

(Contd. on page 7)

Product number KKR513

Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 6)

REL Short-term value: 545 mg/m , 125 ppm
Long-term value: 435 mg/m , 100 ppm
TLV Long-term value: 87 mg/m , 20 ppm
BEI

67-63-0 propan-2-ol (1-2.49%)

PEL Long-term value: 980 mg/m , 400 ppm
REL Short-term value: 1225 mg/m , 500 ppm
Long-term value: 980 mg/m , 400 ppm
TLV Short-term value: 984 mg/m , 400 ppm
Long-term value: 492 mg/m , 200 ppm
BEI

78-83-1 2-methylpropan-1-ol (1-2.49%)

PEL Long-term value: 300 mg/m , 100 ppm
REL Long-term value: 150 mg/m , 50 ppm
TLV Long-term value: 152 mg/m , 50 ppm

80-62-6 methyl methacrylate (≥ 0.1 -<0.5%)

PEL Long-term value: 410 mg/m , 100 ppm
REL Long-term value: 410 mg/m , 100 ppm
TLV Short-term value: 410 mg/m , 100 ppm
Long-term value: 205 mg/m , 50 ppm
DSEN

Ingredients with biological limit values:

1330-20-7 xylene (5-9.99%)

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

100-41-4 ethylbenzene (1-2.49%)

BEI 0.7 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-
Medium: end-exhaled air
Time: not critical
Parameter: Ethyl benzene (semi-quantitative)

67-63-0 propan-2-ol (1-2.49%)

BEI 40 mg/L
Medium: urine
Time: end of shift at end of workweek
Parameter: Acetone (background, nonspecific)

(Contd. on page 8)

Product number KKR513

Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 7)

108-88-3 toluene (1-2.49%)

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

· *Additional information:* The lists that were valid during the creation were used as basis.

· **Exposure controls**

· *Personal protective equipment:*

· *General protective and hygienic measures:*

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
Pregnant women should strictly avoid inhalation or skin contact.

· *Breathing equipment:*

Short term filter device:
Filter AX



Suitable respiratory protective device recommended.

· *Protection of hands:*



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 9)

Product number KKR513

Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 8)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

78 °C (172.4 °F)

· Flash point:

4 °C (39.2 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

370 °C (698 °F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:

1 Vol %

· Upper:

12 Vol %

· Vapor pressure at 20 °C (68 °F):

43 hPa (32.3 mm Hg)

· Density (+/- 0,03) at 20 °C (68 °F):

1.077 g/cm (8.988 lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined.

(Contd. on page 10)

Product number KKR513
Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 9)

· Viscosity:		
· Dynamic:		Not determined.
· Kinematic at 20 °C (68 °F):		40 s (ISO 4 mm)
· Oxidising properties:		N.A.
· Solvent content:		
· Water:		0.0 %
· VOC content:		58.37 %
		628.7 g/l / 5.25 lb/gal
· Solids content:		41.6 %
· Other information (HAPS)		
1330-20-7	xylene	5-9.99%
100-41-4	ethylbenzene	1-2.49%
108-88-3	toluene	1-2.49%
80-62-6	methyl methacrylate	≥0.1-<0.5%
· Other information		No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
 - **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with strong acids and oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
123-86-4 n-butyl acetate		
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
110-19-0 isobutyl acetate		
Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)

(Contd. on page 11)

Product number KKR513
Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 10)

Inhalative	LC50/4 h	31 mg/l (mouse)
1330-20-7 xylene		
Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4h.	27.571 mg/l (mouse)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)
67-63-0 propan-2-ol		
Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)
108-88-3 toluene		
Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)
78-83-1 2-methylpropan-1-ol		
Oral	LD50	2,460 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h.	19.2 mg/l (mouse)
80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (mouse)
Dermal	LD50	5,001 mg/kg (rabbit)
Inhalative	LC50/4 h	78 mg/l (mouse)
131-56-6 2,4-dihydroxybenzophenone		
Oral	LD50	7,220 mg/kg (mouse)
64-17-5 ethanol		
Oral	LD50	10,470 mg/kg (mouse)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	124.7 mg/l (mouse)
E96096		
Oral	LD50	2,001 mg/kg (mouse)
Dermal	LD50	2,001 mg/kg (mouse)

- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 12)

Product number KKR513

Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 11)

· **Additional toxicological information:**

Irritant

Causes serious eye irritation.

May cause drowsiness or dizziness.

Contains methyl methacrylate, E96096. May produce an allergic reaction.

· **Carcinogenic categories**

Titanium dioxide

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	2B - DUST
100-41-4	ethylbenzene	2B
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

· **Toxicity**

· Aquatic toxicity:	
123-86-4 n-butyl acetate	
EC50	397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
110-19-0 isobutyl acetate	
EC50	370 mg/l (algae) (72 h) 25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)

(Contd. on page 13)

Product number KKR513
Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 12)

1330-20-7 xylene	
EC50	2.2 mg/l (algae) (72h)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)
100-41-4 ethylbenzene	
EC50	438 mg/l (algae) (72h)
	1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)
67-63-0 propan-2-ol	
EC50	1,001 mg/l (algae) (72 h)
	10,000 mg/l (daphnia) (24 h)
LC50 (96h)	9,640 mg/l (Fish)
108-88-3 toluene	
EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)
78-83-1 2-methylpropan-1-ol	
EC50	1,799 mg/l (algae) (72 h)
	1,100 mg/l (daphnia) (48 h)
LC50 (96h)	1,430 mg/l (Fish)
80-62-6 methyl methacrylate	
EC50	170 mg/l (algae) (72 h)
LC50 (96h)	191 mg/l (Fish)
64-17-5 ethanol	
EC50	5,012 mg/l (daphnia) (48 h)
LC50 (96h)	15.3 mg/l (Fish)
E96096	
EC50	101 mg/l (algae) (72 h)
	101 mg/l (daphnia) (48 h)
LC50 (96h)	101 mg/l (Fish)

· **Persistence and degradability**

Data refers to the substance Toluene CAS No. 108-88-3

Readily biodegradable (according to OECD criteria and/or EU RAR)

· **Behavior in environmental systems:**

· *Bioaccumulative potential* No further relevant information available.

· *Mobility in soil* No further relevant information available.

· **Additional ecological information:**

· *General notes:*

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 14)

Printing date 01/16/2020

Version number 36

Reviewed on 01/16/2020

Product number KKR513
Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 13)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT** NA1263

· **IMDG, IATA** UN1263

· **UN proper shipping name**

· **DOT** Paint

· **IMDG, IATA** PAINT

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids

· **Label** 3

· **Class** 3 Flammable liquids

· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids

· **Label** 3

· **Packing group**

· **DOT, IMDG, IATA** II

· **Environmental hazards:**

· **Marine pollutant:** No

(Contd. on page 15)

Product number KKR513
Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 14)

<ul style="list-style-type: none"> · Special precautions for user <ul style="list-style-type: none"> · <i>Danger code (Kemler):</i> · <i>EMS Number:</i> · <i>Stowage Category</i> 	<p>Warning: Flammable liquids</p> <p>33</p> <p>F-E, S-E</p> <p>B</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · IMDG <ul style="list-style-type: none"> · <i>Limited quantities (LQ)</i> · <i>Excepted quantities (EQ)</i> 	<p>5L</p> <p>Code: E2</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 500 ml</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 1263 PAINT, 3, II</p>

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
Requirements of Federal Register
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	5-9.99%
100-41-4	ethylbenzene	1-2.49%
67-63-0	propan-2-ol	1-2.49%
108-88-3	toluene	1-2.49%
80-62-6	methyl methacrylate	≥0.1-<0.5%
78-93-3	butanone	<0.01%

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
108-88-3	toluene
80-62-6	methyl methacrylate

- **Proposition 65**

- **Chemicals known to cause cancer:**
Titanium dioxide only in bound form

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6	only for Dust	15-19.99%
------------	---	---------------	-----------

(Contd. on page 16)

Product number KKR513
Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 15)

100-41-4	ethylbenzene	*	1-2.49%
----------	--------------	---	---------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene		1-2.49%
64-17-5	ethanol		<0.5%

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	5-9.99%
100-41-4	ethylbenzene	D	1-2.49%
108-88-3	toluene	II	1-2.49%
80-62-6	methyl methacrylate	E, NL	≥0.1-<0.5%
78-93-3	butanone	I	<0.01%

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6		A4
1330-20-7	xylene		A4
100-41-4	ethylbenzene		A3
67-63-0	propan-2-ol		A4
108-88-3	toluene		A4
80-62-6	methyl methacrylate		A4
64-17-5	ethanol		A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide C.I. 77891 Pigment white 6		15-19.99%
------------	---	--	-----------

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 01/16/2020 / 35

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 17)

Printing date 01/16/2020

Version number 36

Reviewed on 01/16/2020

Product number KKR513

Trade name: ACR TOP-C WHITE 20SH

(Contd. of page 16)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids . Category 2
Flam. Liq. 3: Flammable liquids . Category 3
Acute Tox. 4: Acute toxicity . Category 4
Skin Irrit. 2: Skin corrosion/irritation . Category 2
Eye Dam. 1: Serious eye damage/eye irritation . Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A
Skin Sens. 1: Skin sensitisation . Category 1
Skin Sens. 1B: Skin sensitisation . Category 1B
Carc. 2: Carcinogenicity . Category 2
Repr. 2: Reproductive toxicity . Category 2
STOT SE 3: Specific target organ toxicity (single exposure) . Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2
Asp. Tox. 1: Aspiration hazard . Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard . Category 4

• **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL
and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

• *** Data compared to the previous version altered.**