

1 Identification

- **Product identifier**
 - *Product number* LBA613
 - *Trade name:* **CLEAR PU SEALER**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

- *Hazard pictograms*



GHS02 GHS07

- *Signal word* Danger

- *Hazard-determining components of labeling:*

4-chloro-alpha,alpha,alpha-trifluorotoluene

- *Hazard statements*

H225 Highly flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

- *Precautionary statements*

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P321 Specific treatment (see on this label).

(Contd. on page 2)

Product number LBA613
Trade name: CLEAR PU SEALER

(Contd. of page 1)

P403+P235
P501

Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/
international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

540-88-5	tert-butyl acetate	20-24.9%
	⚠ Flam. Liq. 2, H225	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	20-24.9%
	⚠ Flam. Liq. 3, H226	
	⚠ Aquatic Chronic 2, H411	
	⚠ Skin Sens. 1, H317	
	Aquatic Acute 2, H401	
108-65-6	2-methoxy-1-methylethyl acetate	2.5-4.99%
	⚠ Flam. Liq. 3, H226	
123-86-4	n-butyl acetate	0.1-<10%
	⚠ Flam. Liq. 3, H226	
	⚠ STOT SE 3, H336	
67-64-1	acetone	1-2.49%
	⚠ Flam. Liq. 2, H225	
	⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

(Contd. on page 3)

Product number LBA613
Trade name: CLEAR PU SEALER

(Contd. of page 2)

- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed**
For symptoms and effects caused by substances, refer to Section 11.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:** Alcohol resistant foam, CO, powder, water spray/mist.
 - **For safety reasons unsuitable extinguishing agents:**
Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
 - **Protective equipment:**
Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to Section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
 - **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

Product number LBA613
Trade name: CLEAR PU SEALER

(Contd. of page 3)

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

540-88-5 tert-butyl acetate

PEL Long-term value: 950 mg/m , 200 ppm

REL Long-term value: 950 mg/m , 200 ppm

TLV Short-term value: 712 mg/m , 150 ppm
Long-term value: 238 mg/m , 50 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m , 150 ppm

REL Short-term value: 950 mg/m , 200 ppm
Long-term value: 710 mg/m , 150 ppm

TLV Short-term value: 712 mg/m , 150 ppm
Long-term value: 238 mg/m , 50 ppm

67-64-1 acetone

PEL Long-term value: 2400 mg/m , 1000 ppm

REL Long-term value: 590 mg/m , 250 ppm

TLV Short-term value: 1187 mg/m , 500 ppm
Long-term value: 594 mg/m , 250 ppm
BEI

· **Ingredients with biological limit values:**

67-64-1 acetone

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 5)

Product number LBA613
Trade name: CLEAR PU SEALER

(Contd. of page 4)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

56 °C (133 °F)

· **Flash point:**

-17 °C (1 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

315 °C (599 °F)

(Contd. on page 6)

US

Product number LBA613
Trade name: CLEAR PU SEALER

(Contd. of page 5)

· <i>Decomposition temperature:</i>	Not determined.	
· <i>Auto igniting:</i>	Product is not selfigniting.	
· <i>Danger of explosion:</i>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· <i>Explosion limits:</i>		
· <i>Lower:</i>	1.2 Vol %	
· <i>Upper:</i>	13.0 Vol %	
· <i>Vapor pressure at 20 °C (68 °F):</i>	233 hPa (175 mm Hg)	
· <i>Density at 20 °C (68 °F):</i>	1.089 g/cm (9.088 lbs/gal)	
· <i>Relative density</i>	Not determined.	
· <i>Vapor density</i>	Not determined.	
· <i>Evaporation rate</i>	Not determined.	
· <i>Solubility in / Miscibility with</i>		
· <i>Water:</i>	Not miscible or difficult to mix.	
· <i>Partition coefficient (n-octanol/water):</i>	Not determined.	
· <i>Viscosity:</i>		
· <i>Dynamic:</i>	Not determined.	
· <i>Kinematic at 20 °C (68 °F):</i>	25 s (ISO 6 mm)	
· <i>Oxidising properties:</i>	N.A.	
· <i>Solvent content:</i>		
· <i>VOC content:</i>	8.3 % 90.7 g/l / 0.76 lb/gl	
· <i>Solids content:</i>	46.3 %	
· Other information (HAPS)		
1330-20-7	xylene	0.1-<0.5%
100-41-4	ethylbenzene	<0.1%
108-88-3	toluene	<0.01%
· Other information	No further relevant information available.	

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**

in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

US

(Contd. on page 7)

Product number LBA613
Trade name: CLEAR PU SEALER

(Contd. of page 6)

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

540-88-5 tert-butyl acetate

Oral	LD50	4500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2001 mg/kg (Con)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

Oral	LD50	5001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	33 mg/l (rat/szczur/mouse/souris/Maus/ratón)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8532 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	35.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)

123-86-4 n-butyl acetate

Oral	LD50	10760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	14000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	21.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	20000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	76 mg/l (rat/szczur/mouse/souris/Maus/ratón)

· Primary irritant effect:

· on the skin: No irritant effect.

· on the eye: No irritating effect.

· Sensitization: Sensitization possible through skin contact.

· Additional toxicological information: Irritant

· Carcinogenic categories

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

14807-96-6	Talc (Mg3H2(SiO3)4)	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

(Contd. on page 8)

Product number LBA613
Trade name: CLEAR PU SEALER

(Contd. of page 7)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity** Harmful to aquatic life with long lasting effects.

· **Aquatic toxicity:**

540-88-5 tert-butyl acetate

EC50 350 mg/l (daphnia) (48 h)

LC50 (96h) 240 mg/l (Fish)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

EC50 500 mg/l (algae) (72 h)

16 mg/l (daphnia)

LC50 (96h) 3.6 mg/l (Fish)

108-65-6 2-methoxy-1-methylethyl acetate

EC50 1001 mg/l (algae) (72 h)

501 mg/l (daphnia) (48 h)

LC50 (96h) 134 mg/l (Fish)

123-86-4 n-butyl acetate

EC50 648 mg/l (algae) (72 h)

44 mg/l (daphnia) (48 h)

LC50 (96h) 18 mg/l (Fish)

67-64-1 acetone

EC50 8800 mg/l (daphnia)

LC50 (96h) 5540 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Printing date 08/08/2016

Version number 1

Reviewed on 06/30/2016

Product number LBA613
Trade name: CLEAR PU SEALER

(Contd. of page 8)

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· *Recommendation:* Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· *DOT* NA1263
· *IMDG, IATA* UN1263

· **UN proper shipping name**

· *DOT* Paint
· *IMDG, IATA* PAINT

· **Transport hazard class(es)**

· *DOT*



· *Class* 3 Flammable liquids
· *Label* 3
· *Class* 3 Flammable liquids
· *Label* 3

· *IMDG, IATA*



· *Class* 3 Flammable liquids
· *Label* 3

· **Packing group**

· *DOT, IMDG, IATA* II

· **Environmental hazards:**

· *Marine pollutant:* No

· **Special precautions for user**

Warning: Flammable liquids
· *Danger code (Kemler):* 33
· *EMS Number:* F-E, S-E
· *Segregation groups* Liquid halogenated hydrocarbons
· *Stowage Category* B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· *IMDG*

· *Limited quantities (LQ)* 5L
· *Excepted quantities (EQ)* Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging:

(Contd. on page 10)

Product number LBA613
Trade name: CLEAR PU SEALER

(Contd. of page 9)

500 ml
· UN "Model Regulation": UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

1330-20-7	xylene	0.1-<0.5%
100-41-4	ethylbenzene	<0.1%
75-65-0	2-methylpropan-2-ol	<0.1%
108-88-3	toluene	<0.01%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

100-41-4	ethylbenzene	*	<0.1%
----------	--------------	---	-------

· Chemicals known to cause reproductive toxicity for females:

70657-70-4	2-methoxypropyl acetate	<0.1%
1589-47-5	2-methoxypropanol	<0.01%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene	<0.01%
----------	---------	--------

· Carcinogenic categories

· EPA (Environmental Protection Agency)

67-64-1	acetone	I	1-2,49%
1330-20-7	xylene	I	0.1-<0.5%
100-41-4	ethylbenzene	D	<0.1%
108-88-3	toluene	II	<0.01%

· TLV (Threshold Limit Value established by ACGIH)

67-64-1	acetone	A4
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
75-65-0	2-methylpropan-2-ol	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 11)

Product number LBA613

Trade name: CLEAR PU SEALER

(Contd. of page 10)

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 08/08/2016 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A

Skin Sens. 1: Skin sensitisation . Category 1

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard . Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

· **Sources**

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer