

## 1 Identification

- **Product identifier**
  - *Product number* LDA200
  - *Trade name:* **Clear glossy PU topcoat**
  - *Relevant identified uses of the substance or mixture and uses advised against*  
Paint and relative material only for wood
  - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
  - *Manufacturer/Supplier:*  
IVM Chemicals srl  
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
  - *Information department:*  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
  - *Emergency telephone number:*  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

- *Hazard pictograms*



GHS02



GHS07



GHS08

- *Signal word* Danger

- *Hazard-determining components of labeling:*

xylene

ethylbenzene

**Product number LDA200**

**Trade name: Clear glossy PU topcoat**

(Contd. of page 1)

ethyl acetate

n-butyl acetate

**· Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

**· Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Classification system:**

**· NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 4

Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**



Health = \*1

Fire = 4

Reactivity = 0

**3 Composition/information on ingredients**

**· Chemical characterization: Mixtures**

**· Description:** Mixture: consisting of the following components.

**· Dangerous components:**







1330-20-7	xylene	30-49.9%
	<ul style="list-style-type: none"> <li>⚠ Flam. Liq. 3, H226</li> <li>⚠ STOT RE 2, H373; Asp. Tox. 1, H304</li> <li>⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335</li> </ul>	
100-41-4	ethylbenzene	5-9.99%
	<ul style="list-style-type: none"> <li>⚠ Flam. Liq. 2, H225</li> <li>⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304</li> <li>⚠ Acute Tox. 4, H332</li> </ul>	
141-78-6	ethyl acetate	5-9.99%
	<ul style="list-style-type: none"> <li>⚠ Flam. Liq. 2, H225</li> <li>⚠ Eye Irrit. 2, H319; STOT SE 3, H336</li> </ul>	

(Contd. on page 3)

**Product number LDA200**

**Trade name: Clear glossy PU topcoat**

(Contd. of page 2)

123-86-4	n-butyl acetate	0.1-<10%
	<ul style="list-style-type: none"> <li> Flam. Liq. 3, H226</li> <li> STOT SE 3, H336</li> </ul>	
64742-95-6	Solvent naphtha (petroleum), light arom.	0.1-<0.5%
	<ul style="list-style-type: none"> <li> Flam. Liq. 3, H226</li> <li> Asp. Tox. 1, H304</li> <li> Aquatic Chronic 2, H411</li> <li> STOT SE 3, H335-H336</li> </ul>	

## 4 First-aid measures

### · Description of first aid measures

#### · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

#### · After swallowing: Do not induce vomiting; immediately call for medical help.

#### · Information for doctor:

##### · Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

##### · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

### · Extinguishing media

· Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

### · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

### · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

#### · Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

US

(Contd. on page 4)

**Product number LDA200**

**Trade name: Clear glossy PU topcoat**

(Contd. of page 3)

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

**Product number LDA200**

**Trade name: Clear glossy PU topcoat**

(Contd. of page 4)

· **Control parameters**

· *Components with limit values that require monitoring at the workplace:*

**1330-20-7 xylene**

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 655 mg/m , 150 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Short-term value: 651 mg/m , 150 ppm Long-term value: 434 mg/m , 100 ppm BEI

**100-41-4 ethylbenzene**

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 87 mg/m , 20 ppm BEI

**141-78-6 ethyl acetate**

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 1440 mg/m , 400 ppm

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m , (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m , (150) NIC-50 ppm

· *Ingredients with biological limit values:*

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· *Additional information: The lists that were valid during the creation were used as basis.*

· **Exposure controls**

· *Personal protective equipment:*

· *General protective and hygienic measures:*

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.

(Contd. on page 6)

**Product number LDA200**

**Trade name: Clear glossy PU topcoat**

(Contd. of page 5)

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

77 °C (171 °F)

· **Flash point:**

-4 °C (25 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

370 °C (698 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 7)



Printing date 09/18/2015

Version number 34

Reviewed on 09/18/2015

**Product number LDA200**

**Trade name: Clear glossy PU topcoat**

(Contd. of page 6)

· <b>Explosion limits:</b>		
· <b>Lower:</b>		1.0 Vol %
· <b>Upper:</b>		11.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>		97 hPa (73 mm Hg)
· <b>Density at 20 °C (68 °F):</b>		0.995 g/cm (8.303 lbs/gal)
· <b>Relative density</b>		Not determined.
· <b>Vapour density</b>		Not determined.
· <b>Evaporation rate</b>		Not determined.
· <b>Solubility in / Miscibility with</b>		
· <b>Water:</b>		Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b> Not determined.		
· <b>Viscosity:</b>		
· <b>Dynamic:</b>		Not determined.
· <b>Kinematic at 20 °C (68 °F):</b>		38 s (ISO 4 mm)
· <b>Oxidising properties:</b>		N.A.
· <b>Solvent content:</b>		
· <b>VOC content:</b>		48.7 % 484.3 g/l / 4.04 lb/gl
· <b>Solids content:</b>		51.3 %
· <b>Other information (HAPS)</b>		
1330-20-7	xylene	30-49.9%
100-41-4	ethylbenzene	5-9,99%
· <b>Other information</b>		No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
  - **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions**  
Reacts with oxidizing agents.  
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
in case of possible formation of combustion:  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

Oral	LD50	3523 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
------	------	---

(Contd. on page 8)

**Product number LDA200**

**Trade name: Clear glossy PU topcoat**

(Contd. of page 7)

Dermal	LD50	1701 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
<b>100-41-4 ethylbenzene</b>		
Oral	LD50	3500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	15486 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	17.2 mg/l (rat/szczur/mouse/souris/Maus/ratón)
<b>141-78-6 ethyl acetate</b>		
Oral	LD50	4934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Dermal	LD50	20001 mg/kg (Con)
Inhalative	LC0	22.6 ppm (mouse)
	LC50/4 h	1600 mg/l (rat/szczur/mouse/souris/Maus/ratón)
<b>123-86-4 n-butyl acetate</b>		
Oral	LD50	10760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	14000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	21.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)
<b>64742-95-6 Solvent naphtha (petroleum), light arom.</b>		
Oral	LD50	6801 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	3401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)

· **Primary irritant effect:**

· **on the skin:**

Irritant to skin and mucous membranes.

Causes skin irritation.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

100-41-4 ethylbenzene

2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

· **Toxicity**

· **Aquatic toxicity:**

**100-41-4 ethylbenzene**

EC50 75 mg/l (daphnia) (48 h)

(Contd. on page 9)



**Product number LDA200**

**Trade name: Clear glossy PU topcoat**

(Contd. of page 8)

**141-78-6 ethyl acetate**

EC50 165 mg/l (daphnia) (48 h)

LC50 (96h) 230 mg/l (Fish)

**123-86-4 n-butyl acetate**

EC50 648 mg/l (algae) (72 h)

44 mg/l (daphnia) (48 h)

LC50 (96h) 18 mg/l (Fish)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
  - **Bioaccumulative potential** No further relevant information available.
  - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
  - **General notes:**
    - Water hazard class 2 (Self-assessment): hazardous for water
    - Do not allow product to reach ground water, water course or sewage system.
    - Danger to drinking water if even small quantities leak into the ground.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
  - **Recommendation:**
    - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
    - Hand over to hazardous waste disposers.
    - Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
  - **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
    - DOT NA1263
    - IMDG, IATA UN1263
  - **UN proper shipping name**
    - DOT Paint
    - IMDG, IATA PAINT
  - **Transport hazard class(es)**
    - DOT
- 

FLAMMABLE LIQUID  
3
- **Class** 3 Flammable liquids
  - **Label** 3
  - **Class** 3 Flammable liquids

(Contd. on page 10)

Printing date 09/18/2015


Version number 34

Reviewed on 09/18/2015

**Product number LDA200**

**Trade name: Clear glossy PU topcoat**

(Contd. of page 9)

· <b>Label</b>	3
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Danger code (Kemler):</b>	33
· <b>EMS Number:</b>	F-E, S-E
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN1263, Paint, special provision 640D, 3, II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	30-49.9%
100-41-4	ethylbenzene	5-9,99%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene	*	5-9,99%
----------	--------------	---	---------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 11)

**Product number LDA200**
**Trade name: Clear glossy PU topcoat**

(Contd. of page 10)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	30-49.9%
100-41-4	ethylbenzene	D	5-9.99%

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 09/18/2015 / 33

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· **Sources**

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

· **\* Data compared to the previous version altered.**