

Printing date 12/03/2015

Version number 8

Reviewed on 11/12/2015

#### 1 Identification

- · Product identifier
  - · Product number LFC201J
  - · Trade name: UR CLEAR PRECAT SELF-S 8SH
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



**GHS05** Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

#### · Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









GHS02 GHS05 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: butan-1-ol

(Contd. on page 2)



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

Product number LFC201J

Trade name: UR CLEAR PRECAT SELF-S 8SH

(Contd. of page 1)

toluene

ethyl acetate

2-methylpropan-1-ol

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = \*1 Fire = 3

Reactivity = 0

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Danger		
110-19-0	isobutyl acetate	20-24.9%
	♦ Flam. Liq. 2, H225	
141-78-6	ethyl acetate	12,5-15%
	<ul> <li>Flam. Liq. 2, H225</li> <li>Eye Irrit. 2, H319; STOT SE 3, H336</li> </ul>	
123-86-4	n-butyl acetate	10-<15%
	<ul><li>Flam. Liq. 3, H226</li><li>STOT SE 3, H336</li></ul>	
67-63-0	propan-2-ol	5-9,99%
	<ul> <li>Flam. Liq. 2, H225</li> <li>Eye Irrit. 2, H319; STOT SE 3, H336</li> </ul>	
		(Contd. on page 3

- US



Printing date 12/03/2015

Version number 8

Reviewed on 11/12/2015

Product number LFC201J

Trade name: UR CLEAR PRECAT SELF-S 8SH

78-93-3	butanone	(Contd. of page 2 2,5-4,99%
	<ul> <li>Flam. Liq. 2, H225</li> <li>Eye Irrit. 2, H319; STOT SE 3, H336</li> </ul>	
71-36-3	butan-1-ol	2,5-4,99%
	<ul> <li>Flam. Liq. 3, H226</li> <li>Eye Dam. 1, H318</li> <li>Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336</li> </ul>	
108-88-3	toluene	2,5-4,99%
	<ul> <li>Flam. Liq. 2, H225</li> <li>Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304</li> <li>Skin Irrit. 2, H315; STOT SE 3, H336</li> <li>Aquatic Chronic 3, H412</li> </ul>	
77-90-7	tributyl O-acetylcitrate Aquatic Acute 3, H402; Aquatic Chronic 3, H412	2,5-4,99%
1330-20-7	xylene <ul> <li>Flam. Liq. 3, H226</li> <li>STOT RE 2, H373; Asp. Tox. 1, H304</li> <li>↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335</li> </ul>	1-2,49%
78-83-1	2-methylpropan-1-ol	1-2,49%
	<ul> <li>Flam. Liq. 3, H226</li> <li>Eye Dam. 1, H318</li> <li>Skin Irrit. 2, H315; STOT SE 3, H335-H336</li> </ul>	
100-41-4	ethylbenzene	0,5-1%
	<ul> <li>Flam. Liq. 2, H225</li> <li>Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304</li> <li>Acute Tox. 4, H332</li> </ul>	
50-00-0	formaldehyde	<0.1%
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Muta. 2, H341; Carc. 1B, H350 Skin Corr. 1B, H314 Skin Sens. 1, H317	

### 4 First-aid measures

#### · Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

(Contd. on page 4)



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

Product number LFC201J

Trade name: UR CLEAR PRECAT SELF-S 8SH

(Contd. of page 3)

· Information for doctor:

· Most important symptoms and effects, both acute and delayed
For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

#### · Extinguishing media

- · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
- · For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

#### · Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 5)



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

Product number LFC201J

Trade name: UR CLEAR PRECAT SELF-S 8SH

(Contd. of page 4)

Keep respiratory protective device available.

#### · Conditions for safe storage, including any incompatibilities

- · Storage:
  - Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Co	omponents with limit values that require monitoring at the workplace:
110-1	19-0 isobutyl acetate
PEL	Long-term value: 700 mg/m³, 150 ppm
REL	Long-term value: 700 mg/m³, 150 ppm
TLV	Short-term value: NIC-712 mg/m³, NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm
141-7	78-6 ethyl acetate
PEL	Long-term value: 1400 mg/m³, 400 ppm
REL	Long-term value: 1400 mg/m³, 400 ppm
TLV	Long-term value: 1440 mg/m³, 400 ppm
123-8	36-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm
67-6 <b>:</b>	3-0 propan-2-ol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI

78-93-3 butanone

PEL Long-term value: 590 mg/m³, 200 ppm

(Contd. on page 6)



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

Product number LFC201J

Trade name: UR CLEAR PRECAT SELF-S 8SH

(Contd. of page 5) REL Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m<sup>3</sup>, 200 ppm BEI 71-36-3 butan-1-ol PEL Long-term value: 300 mg/m³, 100 ppm REL Ceiling limit value: 150 mg/m<sup>3</sup>, 50 ppm TLV Long-term value: 61 mg/m³, 20 ppm 78-83-1 2-methylpropan-1-ol PEL Long-term value: 300 mg/m³, 100 ppm REL Long-term value: 150 mg/m³, 50 ppm TLV Long-term value: 152 mg/m<sup>3</sup>, 50 ppm · Ingredients with biological limit values: 67-63-0 propan-2-ol BEI 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) 78-93-3 butanone BEI 2 mg/L Medium: urine Time: end of shift Parameter: MEK 108-88-3 toluene BEI 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

· Additional information: The lists that were valid during the creation were used as basis.

### · Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 7)



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

Product number LFC201J

Trade name: UR CLEAR PRECAT SELF-S 8SH

(Contd. of page 6)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



#### Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

#### 9 Physical and chemical properties

Information on	basic ph	vsical and	chemical	properties
minorinauon on	Dasic pii	y Sicai aila	Gilcillicai	pi opci lica

· General Information

· Appearance:

· Form: Fluid

· Color: According to product specification

Odor: Characteristic
 Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
 Boiling point/Boiling range: 77 °C (171 °F)

· Flash point: -4 °C (25 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 340 °C (644 °F)

· Decomposition temperature: Not determined.

(Contd. on page 8)



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

**Product number LFC201J** 

Trade name: UR CLEAR PRECAT SELF-S 8SH

	(Contd. of page
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosi air/vapor mixtures are possible.
· Explosion limits:	
·Lower:	1.1 Vol %
· Upper:	12.0 Vol %
· Vapor pressure at 20 °C (68 °F):	105 hPa (79 mm Hg)
· Density at 20 °C (68 °F):	0.932 g/cm³ (7.778 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/w	vater): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	110 s (ISO 4 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· VOC content:	72.2 %
	672.9 g/l / 5.62 lb/gl
· Solids content:	27.8 %
· Other information (HAPS)	
108-88-3 toluene	2,5-4,999
1330-20-7 xylene	1-2,49%
100-41-4 ethylbenzene	0,5-1%
1330-20-7 xylene	0.1-<0.5
50-00-0 formaldehyde	<0.1%
Other information	No further relevant information available.

### 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
  - · Chemical stability The product is stable in normal conditions of storage and use recommended
    - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with strong acids and oxidizing agents.

Vapours may form explosive mixtures with air

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

in case of possible formation of combustion:

Carbon monoxide and carbon dioxide



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

**Product number LFC201J** 

11 Toxicological information

Trade name: UR CLEAR PRECAT SELF-S 8SH

(Contd. of page 8)

	· Information on toxicological effects · Acute toxicity:			
· <i>LD</i> /	· LD/LC50 values that are relevant for classification:			
110-19-0	isobutyl a	cetate		
Oral	LD50	13400 mg/kg (rat/szczur/mouse/souris/Maus/ratón)		
Dermal	LD50	17401 mg/kg (Con)		
Inhalative	LC50/4 h	31 mg/l (rat/szczur/mouse/souris/Maus/ratón)		
141-78-6 ethyl acet		ate		
Oral	LD50	4934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)		
Dermal	LD50	20001 mg/kg (Con)		

Dermal	LD50	20001 mg/kg (Con)
Inhalative	LC50/4 h	1600 mg/l (rat/szczur/mouse/souris/Maus/ratón)
		22.6 ppm (mouse)
123-86-4 n-butyl acetate		

Oral	LD50	10760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	14000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	21.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)

67-63-0 propan-2-ol		
Oral		4710 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12800 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	72.6 mg/l (rat/szczur/mouse/souris/Maus/ratón)

78-93-3 bi	utanone	
Oral		2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50	21 mg/l (rat/szczur/mouse/souris/Maus/ratón)

71-36-3 b	utan-1-ol	
Oral	LD50	790 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	3400 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	8000 mg/l (rat/szczur/mouse/souris/Maus/ratón)

108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	25.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)
77-90-7 tributyl O-acetylcitrate		
01	1.050	04500 (1

ı	Urai	LDSU	31300 mg/kg (rai/szczui/mouse/souns/maus/raton)		
Ī	1330-20-7	1330-20-7 xylene Oral LD50 3523 mg/kg (rat/szczur/mouse/souris/Maus/ratón) Dermal LD50 1701 mg/kg (rabbit/królik/Kaninchen/conejo/lapin) 78-83-1 2-methylpropan-1-ol			
Ī	Oral LD50 3523 mg/kg (rat/szczur/mouse/souris/Maus/ratón)				
Dermal LD50 1701 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)		1701 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)			
	78-83-1 2·	-methylpro	ethylpropan-1-ol		
ſ	Oral	LD50	2460 mg/kg (rat/szczur/mouse/souris/Maus/ratón)		
	Dermal	LD50	3400 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)		
	Inhalative	LC50	18.2 mg/l (rat/szczur/mouse/souris/Maus/ratón) (6 h)		

(Contd. on page 10)



Printing date 12/03/2015

Version number 8

Reviewed on 11/12/2015

Product number LFC201J

Trade name: UR CLEAR PRECAT SELF-S 8SH

		(Contd. of page 9)		
100-41-4 €	ethylbenze	ene		
Oral LD50 3500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)				
Dermal	LD50	15486 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)		
Inhalative	LC50/4 h	17.2 mg/l (rat/szczur/mouse/souris/Maus/ratón)		
50-00-0 fo	rmaldehy	de		
Oral	LD50	100 mg/kg (rat/szczur/mouse/souris/Maus/ratón)		
Dermal	LD50	271 mg/kg (Con)		

- · Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - · on the eve:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Causes skin irritation.

Causes serious eye damage.

Suspected of damaging the unborn child.

May cause drowsiness or dizziness.

Irritant

· Carcinogenic categories

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

#### Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

•.	IARC (International Agency for Research on Cancer - Cl. 1 and 2)	
100-41-4	ethylbenzene	2B
50-00-0	formaldehyde	1
•	NTP (National Toxicology Program)	
50-00-0 1	ormaldehyde	<0.1%
	OSHA-Ca (Occupational Safety & Health Administration)	
50-00-0 1	ormaldehyde	<0.1%

# 12 Ecological information

#### · Toxicity

	TOXICITY	
	· Aquatic t	oxicity:
	110-19-0 is	obutyl acetate
I	EC50	370 mg/l (algae) (72 h)
		25 mg/l (daphnia)
	LC50 (96h)	17 mg/l (Fish)

(Contd. on page 11)



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

Product number LFC201J

Trade name: UR CLEAR PRECAT SELF-S 8SH

		(Contd. of pa
141-78-6 et	•	
EC50	165 mg/l (daphnia) (48 h)	
, ,	230 mg/l (Fish)	
	butyl acetate	
EC50	648 mg/l (algae) (72 h)	
	44 mg/l (daphnia) (48 h)	
LC50 (96h)	18 mg/l (Fish)	
67-63-0 pro	pan-2-ol	
EC50	1001 mg/l (algae) (72 h)	
	10000 mg/l (daphnia) (24 h)	
LC50 (96h)	9640 mg/l (Fish)	
78-93-3 but	anone	
EC50	2029 mg/l (algae) (96 h)	
	308 mg/l (daphnia) (48 h)	
LC50 (96h)	2993 mg/l (Fish)	
108-88-3 to	luene	
EC50	134 mg/l (algae) (3 h)	
	3.78 mg/l (daphnia) (48 h)	
	58 mg/l (Fish)	
77-90-7 trib	utyl O-acetylcitrate	
LC50 (96h)	60 mg/l (Fish)	
78-83-1 2-m	nethylpropan-1-ol	
EC50	1799 mg/l (algae) (72 h)	
	1100 mg/l (daphnia) (48 h)	
LC50 (96h)	1430 mg/l (Fish)	
100-41-4 et	hylbenzene	
EC50	75 mg/l (daphnia) (48 h)	
50-00-0 for	maldehyde	
EC50	11.3 mg/l (daphnia) (48 h)	
	22.6 mg/l (Fish)	

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
  - · Bioaccumulative potential No further relevant information available.
  - · Mobility in soil No further relevant information available.
- · Additional ecological information:
  - · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

· Other adverse effects No further relevant information available.

US



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

Product number LFC201J

Trade name: UR CLEAR PRECAT SELF-S 8SH

(Contd. of page 11)

### 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.

1/ Tranchart Intarn	
14 Transport inform	

	•			I		1_	_	
	ın	ı_	N	•	m	n	0	r

*· DOT* NA 1263 *· IMDG, IATA* UN1263

#### · UN proper shipping name

· DOT, IATA Paint
· IMDG PAINT

#### · Transport hazard class(es)

 $\cdot DOT$ 



· Class 3 Flammable liquids

· Label

· Class 3 Flammable liquids

· Label

#### · IMDG, IATA



· Class 3 Flammable liquids

· Label 3

#### · Packing group

· DOT, IMDG, IATA

#### · Environmental hazards:

· Marine pollutant: No

#### · Special precautions for user Warning: Flammable liquids

Danger code (Kemler):
EMS Number:
Stowage Category

33
F-E,S-E
B

#### · Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 13)



5L

Code: E2

Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

Product number LFC201J

· IMDG

Trade name: UR CLEAR PRECAT SELF-S 8SH

· Transport/Additional information:

· Limited quantities (LQ)

71-36-3 butan-1-ol

108-88-3 toluene

· Excepted quantities (EQ)

(Contd. of page 12)

		Maximum net quantity per inne ml Maximum net quantity per ou 500 ml	•	
· UN "Mode	el Regulation":	UN 1263 PAINT, SPECIAL PROVISI	NC	640D, 3,
E Dogulot	ow, information			
	ory information ealth and environmenta	I regulations/legislation specific for the	e SI	ubstance
mixture				
·	c acid, butyl ester			
· SARA				
	ion 355 (extremely hazardous	substances):		
50-00-0 fo	ormaldehyde		_	<0.1
	ion 313 (Specific toxic chemi	cal listings):		
	propan-2-ol			5-9,99%
	butanone			2,5-4,99
	butan-1-ol			2,5-4,99
108-88-3				2,5-4,99
1330-20-7	_			1-2,49%
	ethylbenzene			0,5-1%
1330-20-7				0.1-<0.5
50-00-0	formaldehyde			<0.1%
,	Toxic Substances Control Act	t):		
	ents are listed.			
· Proposi				
	micals known to cause cancer	r:		
	ethylbenzene			* 0,5-1
	formaldehyde			* <0.1
	micals known to cause reprod	luctive toxicity for females:		
108-88-3	toluene			2,5-4,99
	micals known to cause reprod	luctive toxicity for males:		
None of th	e ingredients is listed.			
· Che	micals known to cause develo	pmental toxicity:		
108-88-3	toluene			2,5-4,99
. Carcina	genic categories			
	. (Environmental Protection A	Agency)		
	butanone	-0/	I	2,5-4,99
. 5 55 6			•	_,,,

D 2,5-4,99%

II 2,5-4,99%(Contd. on page 14)



Printing date 12/03/2015 Version number 8

Reviewed on 11/12/2015

Product number LFC201J

**UR CLEAR PRECAT SELF-S 8SH** Trade name:

		(Cc	ntd. of page
1330-20-7	•	I	1-2,49%
100-41-4	ethylbenzene	D	0,5-1%
1330-20-7	xylene	1	0.1-<0.59
50-00-0	formaldehyde	B1	<0.1%
· TLV	(Threshold Limit Value established by ACGIH)		
67-63-0	propan-2-ol		A.
108-88-3	toluene		A.
1330-20-7 xylene			
100-41-4	ethylbenzene		A.
1330-20-7	xylene		A.
50-00-0	formaldehyde		A
· NIO	SH-Ca (National Institute for Occupational Safety and Health)	•	
50-00-0 fc	ormaldehyde		<0.19

#### · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - Date of preparation / last revision 12/03/2015 / 7
  - · Abbreviations and acronvms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Lig. 3: Flammable liquids, Hazard Category 3

Acute Tox. 3: Acute toxicity, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Muta. 2: Germ cell mutagenicity, Hazard Category 2 Carc. 1B: Carcinogenicity, Hazard Category 1B

Carc. 2: Carcinogenicity, Hazard Category 2



Printing date 12/03/2015 Version number 8 Reviewed on 11/12/2015

Product number LFC201J

Trade name: **UR CLEAR PRECAT SELF-S 8SH** 

(Contd. of page 14)

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Acute 3: Hazardous to the aquatic environment - AcuteHazard, Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

\* Data compared to the previous version altered.