

1 Identification

· Product identifier

- *Product number* LGA233
- *Trade name:* **PU Clear Topcoat 20 gl**
- *Relevant identified uses of the substance or mixture and uses advised against*
Paint and relative material only for wood
- *Application of the substance / the mixture* For professional use

· Details of the supplier of the safety data sheet

- *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
- *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
- *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Fam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02



GHS07



GHS08

· Signal word Danger

· Hazard-determining components of labeling: xylene

Product number LGA233

Trade name: PU Clear Topcoat 20 gl

(Contd. of page 1)

ethylbenzene

toluene

4-methylpentan-2-one

Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = *1

Fire = 3

Reactivity = 0

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture: consisting of the following components.

Dangerous components:

1330-20-7	xylene	15-19.9%
	Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
141-78-6	ethyl acetate	10-12.49%
	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
110-19-0	isobutyl acetate	5-9.99%
	Flam. Liq. 2, H225	

(Contd. on page 3)

Product number LGA233

Trade name: PU Clear Topcoat 20 gl

		(Contd. of page 2)
123-86-4	n-butyl acetate <div> <div>Flam. Liq. 3, H226</div> <div>STOT SE 3, H336</div> </div>	0.1-<10%
100-41-4	ethylbenzene <div> <div>Flam. Liq. 2, H225</div> <div>Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304</div> <div>Acute Tox. 4, H332</div> </div>	2.5-4.99%
78-93-3	butanone <div> <div>Flam. Liq. 2, H225</div> <div>Eye Irrit. 2, H319; STOT SE 3, H336</div> </div>	2.5-4.99%
108-88-3	toluene <div> <div>Flam. Liq. 2, H225</div> <div>Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304</div> <div>Skin Irrit. 2, H315; STOT SE 3, H336</div> <div>Aquatic Chronic 3, H412</div> </div>	2.5-4.99%
108-10-1	4-methylpentan-2-one <div> <div>Flam. Liq. 2, H225</div> <div>Carc. 2, H351</div> <div>Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335</div> </div>	2.5-4.99%
67-63-0	propan-2-ol <div> <div>Flam. Liq. 2, H225</div> <div>Eye Irrit. 2, H319; STOT SE 3, H336</div> </div>	1-2.49%
64-17-5	ethanol <div> <div>Flam. Liq. 2, H225</div> </div>	0.1-<0.5%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

US

(Contd. on page 4)

Product number LGA233

Trade name: PU Clear Topcoat 20 gl

(Contd. of page 3)

5 Fire-fighting measures

· **Extinguishing media**

· *Suitable extinguishing agents:* Alcohol resistant foam, CO, powder, water spray/mist.

· *For safety reasons unsuitable extinguishing agents:*

Do not use a jet water stream as it may scatter and spread fire.

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· *Protective equipment:*

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· *Precautions for safe handling*

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· *Information about protection against explosions and fires:*

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· *Storage:*

· *Requirements to be met by storerooms and receptacles:*

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

(Contd. on page 5)

Product number LGA233

Trade name: PU Clear Topcoat 20 gl

(Contd. of page 4)

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

1330-20-7 xylene

PEL Long-term value: 435 mg/m , 100 ppm

REL Short-term value: 655 mg/m , 150 ppm

Long-term value: 435 mg/m , 100 ppm

TLV Short-term value: 651 mg/m , 150 ppm

Long-term value: 434 mg/m , 100 ppm

BEI

141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m , 400 ppm

REL Long-term value: 1400 mg/m , 400 ppm

TLV Long-term value: 1440 mg/m , 400 ppm

110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m , 150 ppm

REL Long-term value: 700 mg/m , 150 ppm

TLV Short-term value: NIC-712 mg/m , NIC-150 ppm

Long-term value: (713) NIC-238 mg/m , (150) NIC-50 ppm

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m , 150 ppm

REL Short-term value: 950 mg/m , 200 ppm

Long-term value: 710 mg/m , 150 ppm

TLV Short-term value: (950) NIC-712 mg/m , (200) NIC-150 ppm

Long-term value: (713) NIC-238 mg/m , (150) NIC-50 ppm

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m , 100 ppm

REL Short-term value: 545 mg/m , 125 ppm

Long-term value: 435 mg/m , 100 ppm

TLV Long-term value: 87 mg/m , 20 ppm

BEI

78-93-3 butanone

PEL Long-term value: 590 mg/m , 200 ppm

REL Short-term value: 885 mg/m , 300 ppm

Long-term value: 590 mg/m , 200 ppm

(Contd. on page 6)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 28

Reviewed on 09/18/2015

Product number LGA233**Trade name: PU Clear Topcoat 20 gl**

(Contd. of page 5)

TLV Short-term value: 885 mg/m , 300 ppm
 Long-term value: 590 mg/m , 200 ppm
 BEI

108-88-3 toluene

PEL Long-term value: 200 ppm
 Ceiling limit value: 300; 500* ppm
 *10-min peak per 8-hr shift

REL Short-term value: 560 mg/m , 150 ppm
 Long-term value: 375 mg/m , 100 ppm

TLV Long-term value: 75 mg/m , 20 ppm
 BEI

108-10-1 4-methylpentan-2-one

PEL Long-term value: 410 mg/m , 100 ppm

REL Short-term value: 300 mg/m , 75 ppm
 Long-term value: 205 mg/m , 50 ppm

TLV Short-term value: 307 mg/m , 75 ppm
 Long-term value: 82 mg/m , 20 ppm
 BEI

67-63-0 propan-2-ol

PEL Long-term value: 980 mg/m , 400 ppm

REL Short-term value: 1225 mg/m , 500 ppm
 Long-term value: 980 mg/m , 400 ppm

TLV Short-term value: 984 mg/m , 400 ppm
 Long-term value: 492 mg/m , 200 ppm
 BEI

· Ingredients with biological limit values:**1330-20-7 xylene**

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-
 Medium: end-exhaled air
 Time: not critical
 Parameter: Ethyl benzene (semi-quantitative)

78-93-3 butanone

BEI 2 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MEK

(Contd. on page 7)

Product number LGA233

Trade name: PU Clear Topcoat 20 gl

(Contd. of page 6)

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

108-10-1 4-methylpentan-2-one

BEI 1 mg/L
Medium: urine
Time: end of shift
Parameter: MIBK

67-63-0 propan-2-ol

BEI 40 mg/L
Medium: urine
Time: end of shift at end of workweek
Parameter: Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)

Product number LGA233

Trade name: PU Clear Topcoat 20 gl

(Contd. of page 7)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

77 °C (171 °F)

· **Flash point:**

-4 °C (25 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

370 °C (698 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:**

1.0 Vol %

· **Upper:**

12.0 Vol %

· **Vapor pressure at 20 °C (68 °F):**

105 hPa (79 mm Hg)

· **Density at 20 °C (68 °F):**

0.96 g/cm (8.011 lbs/gal)

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**

· **Water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):**

Not determined.

· **Viscosity:**

· **Dynamic:**

Not determined.

· **Kinematic at 20 °C (68 °F):**

40 s (ISO 4 mm)

· **Oxidising properties:**

N.A.

(Contd. on page 9)

Product number LGA233

Trade name: PU Clear Topcoat 20 gl

(Contd. of page 8)

· Solvent content:		
· VOC content:	61.5 %	
	590.7 g/l / 4.93 lb/gl	
· Solids content:		
38.3 %		
· Other information (HAPS)		
1330-20-7	xylene	15-19.9%
100-41-4	ethylbenzene	2,5-4,99%
108-88-3	toluene	2,5-4,99%
108-10-1	4-methylpentan-2-one	2,5-4,99%
1330-20-7	xylene	<0.1%
· Other information		No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
 - **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with strong acids and oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**

in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
1330-20-7 xylene		
Oral	LD50	3523 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	1701 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
141-78-6 ethyl acetate		
Oral	LD50	4934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Dermal	LD50	20001 mg/kg (Con)
Inhalative	LC0	22.6 ppm (mouse)
	LC50/4 h	1600 mg/l (rat/szczur/mouse/souris/Maus/ratón)
110-19-0 isobutyl acetate		
Oral	LD50	13400 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	17401 mg/kg (Con)
Inhalative	LC50/4 h	31 mg/l (rat/szczur/mouse/souris/Maus/ratón)

(Contd. on page 10)

Product number LGA233

Trade name: PU Clear Topcoat 20 gl

(Contd. of page 9)

123-86-4 n-butyl acetate

Oral	LD50	10760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	14000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	21.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)

100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	15486 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	17.2 mg/l (rat/szczur/mouse/souris/Maus/ratón)

78-93-3 butanone

Oral	LD50	2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50	21 mg/l (rat/szczur/mouse/souris/Maus/ratón)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	25.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)

108-10-1 4-methylpentan-2-one

Oral	LD50	2080 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	16.6 mg/l (rat/szczur/mouse/souris/Maus/ratón)

67-63-0 propan-2-ol

Oral	LD50	4710 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12800 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	72.6 mg/l (rat/szczur/mouse/souris/Maus/ratón)

64-17-5 ethanol

Oral	LD50	10470 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	20000 mg/kg (Con)
Inhalative	LC50/4 h	124.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)

· **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging the unborn child.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful

Irritant

· **Carcinogenic categories**

Quartz.

In physical state and in the quantities present in the formula, substance is not dangerous.

· **IARC (International Agency for Research on Cancer)**

100-41-4 ethylbenzene

2B

(Contd. on page 11)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 28

Reviewed on 09/18/2015

Product number LGA233**Trade name: PU Clear Topcoat 20 gl**

(Contd. of page 10)

108-10-1	4-methylpentan-2-one	2B
67-63-0	propan-2-ol	3
14808-60-7	Quartz (SiO ₂)	1

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	<0.1%
------------	----------------------------	-------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:****141-78-6 ethyl acetate**

EC50 165 mg/l (daphnia) (48 h)

LC50 (96h) 230 mg/l (Fish)

110-19-0 isobutyl acetate

EC50 370 mg/l (algae) (72 h)

25 mg/l (daphnia)

LC50 (96h) 17 mg/l (Fish)

123-86-4 n-butyl acetate

EC50 648 mg/l (algae) (72 h)

44 mg/l (daphnia) (48 h)

LC50 (96h) 18 mg/l (Fish)

100-41-4 ethylbenzene

EC50 75 mg/l (daphnia) (48 h)

78-93-3 butanone

EC50 2029 mg/l (algae) (96 h)

308 mg/l (daphnia) (48 h)

LC50 (96h) 2993 mg/l (Fish)

108-88-3 toluene

EC50 134 mg/l (algae) (3 h)

3.78 mg/l (daphnia) (48 h)

58 mg/l (Fish)

108-10-1 4-methylpentan-2-one

EC50 101 mg/l (daphnia) (48 h)

LC50 (96h) 101 mg/l (Fish)

67-63-0 propan-2-ol

EC50 1001 mg/l (algae) (72 h)

10000 mg/l (daphnia) (24 h)

LC50 (96h) 9640 mg/l (Fish)

64-17-5 ethanol

EC50 5012 mg/l (daphnia) (48 h)

LC50 (96h) 15.3 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

(Contd. on page 12)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 28

Reviewed on 09/18/2015

Product number LGA233**Trade name: PU Clear Topcoat 20 gl**

(Contd. of page 11)

- **Behavior in environmental systems:**
 - *Bioaccumulative potential* No further relevant information available.
 - *Mobility in soil* No further relevant information available.
- **Additional ecological information:**
 - *General notes:*
 - Water hazard class 3 (Self-assessment): extremely hazardous for water
 - Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 - Danger to drinking water if even extremely small quantities leak into the ground.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - *Recommendation:*
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Hand over to hazardous waste disposers.
 - Dispose of contents and container in accordance with local state and federal regulations.
- **Uncleaned packagings:**
 - *Recommendation:* Disposal must be made according to official regulations.

14 Transport information

- | | |
|-------------------------------------|---------------------|
| · UN-Number | |
| · DOT | NA1263 |
| · IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · IMDG, IATA | PAINT |
| · Transport hazard class(es) | |
| · DOT | |
| | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
| | |
| · Class | 3 Flammable liquids |
| · Label | 3 |

(Contd. on page 13)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 28

Reviewed on 09/18/2015

Product number LGA233**Trade name: PU Clear Topcoat 20 gl**

(Contd. of page 12)

· Packing group	II
· DOT, IMDG, IATA	
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1263, Paint, special provision 640D, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· **SARA**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

1330-20-7	xylene	15-19.9%
100-41-4	ethylbenzene	2,5-4,99%
78-93-3	butanone	2,5-4,99%
108-88-3	toluene	2,5-4,99%
108-10-1	4-methylpentan-2-one	2,5-4,99%
67-63-0	propan-2-ol	1-2,49%
1330-20-7	xylene	<0.1%
111-76-2	2-butoxyethanol	<0.01%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene	*	2,5-4,99%
108-10-1	4-methylpentan-2-one	*	2,5-4,99%
14808-60-7	Quartz (SiO ₂)	*	<0.1%

(Contd. on page 14)

Product number LGA233

Trade name: PU Clear Topcoat 20 gl

(Contd. of page 13)

· Chemicals known to cause reproductive toxicity for females:		
108-88-3	toluene	2,5-4,99%

· Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		

· Chemicals known to cause developmental toxicity:		
108-88-3	toluene	2,5-4,99%
108-10-1	4-methylpentan-2-one	2,5-4,99%
64-17-5	ethanol	0.1-<0.5%

· Carcinogenic categories			
· EPA (Environmental Protection Agency)			
1330-20-7	xylene	I	15-19.9%
100-41-4	ethylbenzene	D	2,5-4,99%
78-93-3	butanone	I	2,5-4,99%
108-88-3	toluene	II	2,5-4,99%
108-10-1	4-methylpentan-2-one	I	2,5-4,99%
1330-20-7	xylene	I	<0.1%
111-76-2	2-butoxyethanol	NL	<0.01%

· TLV (Threshold Limit Value established by ACGIH)		
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4
67-63-0	propan-2-ol	A4
112945-52-5	silicon dioxide	A4
64-17-5	ethanol	A3
1330-20-7	xylene	A4
14808-60-7	Quartz (SiO ₂)	A2
111-76-2	2-butoxyethanol	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
14808-60-7	Quartz (SiO ₂)	<0.1%

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone

· Date of preparation / last revision 09/18/2015 / 27

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 15)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 28

Reviewed on 09/18/2015

Product number LGA233**Trade name: PU Clear Topcoat 20 gl**

(Contd. of page 14)

ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 Flam. Liq. 2: Flammable liquids, Hazard Category 2
 Flam. Liq. 3: Flammable liquids, Hazard Category 3
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
 Carc. 2: Carcinogenicity, Hazard Category 2
 Repr. 2: Reproductive toxicity, Hazard Category 2
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

• **Sources**

Directive 1999/45/EC and following amendments
 Directive 67/548/EEC and following amendments and adjustments
 Agency ECHA web site
 INRS Fiche Toxicologique
 IARC International agency for research on cancer

• *** Data compared to the previous version altered.**

US