

1 Identification

- **Product identifier**
 - Product number LMT004
 - Trade name: **pasta metallizzata fine**
 - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
 - Manufacturer/Supplier:
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - Information department:
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - Emergency telephone number:
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**
toluene

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 1)

ethylbenzene
xylene
ethyl acetate
methyl methacrylate
2-hydroxyethyl methacrylate
Fatty acids, tallow, oleylamine compounds

· Hazard statements

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerous components:

141-78-6	ethyl acetate	20-24.9%
	Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	

(Contd. on page 3)

Product number LMT004
Trade name: pasta metallizzata fine

		(Contd. of page 2)
108-88-3	toluene <div> <div>Flam. Liq. 2, H225</div> <div>Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304</div> <div>Skin Irrit. 2, H315; STOT SE 3, H336</div> <div>Aquatic Chronic 3, H412</div> </div>	15-19.9%
110-19-0	isobutyl acetate <div> <div>Flam. Liq. 2, H225</div> <div>STOT SE 3, H336</div> </div>	5-9.99%
1330-20-7	xylene <div> <div>Flam. Liq. 3, H226</div> <div>STOT RE 2, H373; Asp. Tox. 1, H304</div> <div>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335</div> </div>	5-9.99%
123-86-4	n-butyl acetate <div> <div>Flam. Liq. 3, H226</div> <div>STOT SE 3, H336</div> </div>	5-9.99%
108-65-6	2-methoxy-1-methylethyl acetate <div> <div>Flam. Liq. 3, H226</div> </div>	2.5-4.99%
64742-95-6	Solvent naphtha (petroleum), light arom. <div> <div>Flam. Liq. 3, H226</div> <div>Asp. Tox. 1, H304</div> <div>Aquatic Chronic 2, H411</div> <div>STOT SE 3, H335-H336</div> </div>	1-2.49%
64742-48-9	Naphtha (petroleum), hydrotreated heavy <div> <div>Asp. Tox. 1, H304</div> <div>Flam. Liq. 4, H227</div> </div>	1-2.49%
67-63-0	propan-2-ol <div> <div>Flam. Liq. 2, H225</div> <div>Eye Irrit. 2A, H319; STOT SE 3, H336</div> </div>	1-2.49%
100-41-4	ethylbenzene <div> <div>Flam. Liq. 2, H225</div> <div>Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304</div> <div>Acute Tox. 4, H332</div> </div>	1-2.49%
80-62-6	methyl methacrylate <div> <div>Flam. Liq. 2, H225</div> <div>Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335</div> </div>	0.5-1%
868-77-9	2-hydroxyethyl methacrylate <div> <div>Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317</div> </div>	≥0.1-<0.5%
64-17-5	ethanol <div> <div>Flam. Liq. 2, H225</div> <div>Eye Irrit. 2A, H319</div> </div>	≥0.1-<0.5%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 4)

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 3)

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**
*Immediately wash with water and soap and rinse thoroughly.
Take off immediately all contaminated clothing, include underwear and shoes (if necessary).
Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.*
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.
- **After swallowing:** *Do not induce vomiting; immediately call for medical help.*
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed**
For symptoms and effects caused by substances, refer to Section 11.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:** *Alcohol resistant foam, CO, powder, water spray/mist.*
 - **For safety reasons unsuitable extinguishing agents:**
Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
 - **Protective equipment:**
Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
*Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources*
- **Environmental precautions:**
*Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to Section 13.
Ensure adequate ventilation.*
- **Reference to other sections**
*See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.*
- **Protective Action Criteria for Chemicals**

· **PAC-I:**

141-78-6 ethyl acetate

1,200 ppm

(Contd. on page 5)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 02/19/2018

Version number 30

Reviewed on 02/19/2018

Product number LMT004**Trade name: pasta metallizzata fine**

(Contd. of page 4)

108-88-3	toluene	67 ppm
110-19-0	isobutyl acetate	450 ppm
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m
67-63-0	propan-2-ol	400 ppm
100-41-4	ethylbenzene	33 ppm
80-62-6	methyl methacrylate	17 ppm
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m
64-17-5	ethanol	1,800 ppm

· PAC-2:

141-78-6	ethyl acetate	1,700 ppm
108-88-3	toluene	560 ppm
110-19-0	isobutyl acetate	1300* ppm
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m
67-63-0	propan-2-ol	2000* ppm
100-41-4	ethylbenzene	1100* ppm
80-62-6	methyl methacrylate	120 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m
64-17-5	ethanol	3300* ppm

· PAC-3:

141-78-6	ethyl acetate	10000** ppm
108-88-3	toluene	3700* ppm
110-19-0	isobutyl acetate	7500** ppm
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m
67-63-0	propan-2-ol	12000** ppm
100-41-4	ethylbenzene	1800* ppm
80-62-6	methyl methacrylate	570 ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m
64-17-5	ethanol	15000* ppm

7 Handling and storage

· Handling:**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

(Contd. on page 6)

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 5)

- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
Store in a cool, well-ventilated area, away from heat and sources of ignition
Provide solvent resistant, sealed floor.
Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.
In cases where there is no reported expiration date, it means that the product must be used within 8 months.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 1440 mg/m , 400 ppm

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 172 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Long-term value: 950 mg/m , 200 ppm
TLV	Short-term value: 712 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m , 400 ppm
REL	Short-term value: 1225 mg/m , 500 ppm Long-term value: 980 mg/m , 400 ppm

(Contd. on page 7)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 02/19/2018

Version number 30

Reviewed on 02/19/2018

Product number LMT004**Trade name:** pasta metallizzata fine

(Contd. of page 6)

TLV Short-term value: 984 mg/m , 400 ppm
 Long-term value: 492 mg/m , 200 ppm
 BEI

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m , 100 ppm
 REL Short-term value: 545 mg/m , 125 ppm
 Long-term value: 435 mg/m , 100 ppm
 TLV Long-term value: 87 mg/m , 20 ppm
 BEI

80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m , 100 ppm
 REL Long-term value: 410 mg/m , 100 ppm
 TLV Short-term value: 410 mg/m , 100 ppm
 Long-term value: 205 mg/m , 50 ppm
 DSEN

· Ingredients with biological limit values:**108-88-3 toluene**

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

1330-20-7 xylene

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

67-63-0 propan-2-ol

BEI 40 mg/L
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Acetone (background, nonspecific)

(Contd. on page 8)

US

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 7)

100-41-4 ethylbenzene

BEI	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	
	Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

US

(Contd. on page 9)

Product number LMT004
Trade name: pasta metallizzata fine

(Contd. of page 8)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

77 °C (170.6 °F)

· Flash point:

-4 °C (24.8 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

240 °C (464 °F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:

0.6 Vol %

· Upper:

12 Vol %

· Vapor pressure at 20 °C (68 °F):

97 hPa (72.8 mm Hg)

· Density at 20 °C (68 °F):

0.998 g/cm (8.328 lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C (68 °F):

40 s (ISO 4 mm)

· Oxidising properties:

N.A.

· Solvent content:

· Water:

0.0 %

· VOC content:

75.31 %

751.6 g/l / 6.27 lb/gal

· Solids content:

24.7 %

· Other information (HAPS)

108-88-3	toluene	15-19.9%
1330-20-7	xylene	5-9.99%
100-41-4	ethylbenzene	1-2.49%
80-62-6	methyl methacrylate	0.5-1%

(Contd. on page 10)

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 9)

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
 - **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with strong acids and oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Dermal	LD50	20,001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	1,600 mg/l (rat/szczur/mouse/souris/Maus/ratón)
	LC0	22.6 ppm (mouse)

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12,124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	25.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)

110-19-0 isobutyl acetate

Oral	LD50	13,400 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	17,401 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	31 mg/l (rat/szczur/mouse/souris/Maus/ratón)

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50.	12,126 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4h.	27.571 mg/l (rat/szczur/mouse/souris/Maus/ratón)

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	14,000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	21.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
------	------	--

(Contd. on page 11)

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 10)

Dermal	LD50	5,001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	35.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	6,801 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	3,401 mg/kg (rab)
Inhalative	LC50/4 h	20.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5,000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	>3,000 mg/kg (rab)
67-63-0 propan-2-ol		
Oral	LD50	4,710 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12,800 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	72.6 mg/l (rat/szczur/mouse/souris/Maus/ratón)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	15,486 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	17.2 mg/l (rat/szczur/mouse/souris/Maus/ratón)
80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5,001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	78 mg/l (rat/szczur/mouse/souris/Maus/ratón)
868-77-9 2-hydroxyethyl methacrylate		
Oral	LD50	5,050 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
64-17-5 ethanol		
Oral	LD50	10,470 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	20,000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	124.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)

· **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

Irritant

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Contains methyl methacrylate, 2-hydroxyethyl methacrylate, Fatty acids, tallow, oleylamine compounds. May produce an allergic reaction.

· **Carcinogenic categories**

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up

(Contd. on page 12)

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 11)

of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1

· NTP (National Toxicology Program)		
None of the ingredients is listed.		

· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

· **Toxicity** Harmful to aquatic life with long lasting effects.

· <i>Aquatic toxicity:</i>	
141-78-6 ethyl acetate	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)
108-88-3 toluene	
EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)
110-19-0 isobutyl acetate	
EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)
123-86-4 n-butyl acetate	
EC50	648 mg/l (algae) (72 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
108-65-6 2-methoxy-1-methylethyl acetate	
EC50	1,001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)
64742-95-6 Solvent naphtha (petroleum), light arom.	
EC50	1 mg/l (algae) (72 h)
	1 mg/l (daphnia) (48 h)
LC50 (96h)	1 mg/l (Fish)
67-63-0 propan-2-ol	
EC50	1,001 mg/l (algae) (72 h)
	10,000 mg/l (daphnia) (24 h)
LC50 (96h)	9,640 mg/l (Fish)

(Contd. on page 13)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 02/19/2018

Version number 30

Reviewed on 02/19/2018

Product number LMT004**Trade name:** pasta metallizzata fine

(Contd. of page 12)

100-41-4 ethylbenzene

EC50 75 mg/l (daphnia) (48 h)

80-62-6 methyl methacrylate

EC50 170 mg/l (algae) (72 h)

LC50 (96h) 191 mg/l (Fish)

868-77-9 2-hydroxyethyl methacrylate

LC50 (96h) 240 mg/l (Fish)

64-17-5 ethanol

EC50 5,012 mg/l (daphnia) (48 h)

LC50 (96h) 15.3 mg/l (Fish)

· **Persistence and degradability**

Data refers to the substance Toluene CAS No. 108-88-3

Readily biodegradable (according to OECD criteria and/or EU RAR)

· **Substances Easily biodegradable**

141-78-6	ethyl acetate	.
108-88-3	toluene	.
110-19-0	isobutyl acetate	.
1330-20-7	xylene	.
123-86-4	n-butyl acetate	.
108-65-6	2-methoxy-1-methylethyl acetate	.
67-63-0	propan-2-ol	.
100-41-4	ethylbenzene	.
64-17-5	ethanol	.

· **Behavior in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Harmful to fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

(Contd. on page 14)

Printing date 02/19/2018

Version number 30

Reviewed on 02/19/2018

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 13)

· **Uncleaned packagings:**

· *Recommendation:* Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· *DOT* NA1263
· *IMDG, IATA* UN1263

· **UN proper shipping name**

· *DOT* Paint
· *IMDG, IATA* PAINT

· **Transport hazard class(es)**

· *DOT*



· *Class* 3 Flammable liquids
· *Label* 3
· *Class* 3 Flammable liquids
· *Label* 3

· *IMDG, IATA*



· *Class* 3 Flammable liquids
· *Label* 3

· **Packing group**

· *DOT, IMDG, IATA* II

· **Environmental hazards:**

· *Marine pollutant:* No

· **Special precautions for user**

Warning: Flammable liquids
· *Danger code (Kemler):* 33
· *EMS Number:* F-E, S-E
· *Stowage Category* B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· *IMDG*

· *Limited quantities (LQ)* 5L
· *Excepted quantities (EQ)* Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

(Contd. on page 15)

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 14)

· **UN "Model Regulation":**

UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings) :**

108-88-3	toluene	15-19.9%
1330-20-7	xylene	5-9.99%
7429-90-5	aluminium powder (stabilised)	5-9.99%
67-63-0	propan-2-ol	1-2.49%
100-41-4	ethylbenzene	1-2.49%
80-62-6	methyl methacrylate	0.5-1%
78-93-3	butanone	<0.01%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene	*	1-2.49%
----------	--------------	---	---------

· **Chemicals known to cause reproductive toxicity for females:**

70657-70-4	2-methoxypropyl acetate	<0.01%
------------	-------------------------	--------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene	15-19.9%
64-17-5	ethanol	≥0.1-<0.5%

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II	15-19.9%
1330-20-7	xylene	I	5-9.99%
100-41-4	ethylbenzene	D	1-2.49%
80-62-6	methyl methacrylate	E, NL	0.5-1%
78-93-3	butanone	I	<0.01%

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
1330-20-7	xylene	A4
7429-90-5	aluminium powder (stabilised)	A4
67-63-0	propan-2-ol	A4
100-41-4	ethylbenzene	A3

(Contd. on page 16)

Product number LMT004

Trade name: pasta metallizzata fine

(Contd. of page 15)

80-62-6	methyl methacrylate	A4
64-17-5	ethanol	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 02/19/2018 / 29

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Flam. Liq. 4: Flammable liquids . Category 4

Acute Tox. 4: Acute toxicity . Category 4

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A

Skin Sens. 1: Skin sensitisation . Category 1

Carc. 2: Carcinogenicity . Category 2

Carc. 2: Carcinogenicity . Category 2

Repr. 2: Reproductive toxicity . Category 2

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2

Asp. Tox. 1: Aspiration hazard . Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

· **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer