

1 Identification

- **Product identifier**
 - Product number LOB603
 - Trade name: **ACCELERATOR FOR POLYESTER**
 - Application of the substance / the mixture For professional use
- **Details of the supplier of the safety data sheet**
 - Manufacturer/Supplier:
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - Information department:
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - Emergency telephone number:
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.
 Aquatic Acute 2 H401 Toxic to aquatic life.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

Product number LOB603

Trade name: ACCELERATOR FOR POLYESTER

(Contd. of page 1)

· **Hazard-determining components of labeling:**

toluene
cobalt bis(2-ethylhexanoate)
ethyl acetate
xylene

· **Hazard statements**

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 3
Reactivity = 0

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.











· **Dangerous components:**

108-88-3	toluene	30-49.9%
	Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Chronic 3, H412	

(Contd. on page 3)

Product number LOB603

Trade name: ACCELERATOR FOR POLYESTER

		(Contd. of page 2)
141-78-6	ethyl acetate  Flam. Liq. 2, H225  Eye Irrit. 2A, H319; STOT SE 3, H336	30-49.9%
136-52-7	cobalt bis(2-ethylhexanoate)  Carc. 2, H351; Repr. 2, H361  Aquatic Acute 1, H400  Eye Irrit. 2A, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	10-12.49%
57-55-6	propane-1,2-diol	10-12.49%
1330-20-7	xylene  Flam. Liq. 3, H226  STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	2.5-4.99%
556-67-2	octamethylcyclotetrasiloxane  Flam. Liq. 3, H226  Repr. 2, H361 Aquatic Chronic 4, H413	≥0.1-<0.5%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 4)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/26/2017

Version number 365

Reviewed on 09/04/2017

Product number LOB603**Trade name: ACCELERATOR FOR POLYESTER**

(Contd. of page 3)

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals**· PAC-1:**

108-88-3	toluene	67 ppm
141-78-6	ethyl acetate	1,200 ppm
57-55-6	propane-1,2-diol	30 mg/m3
1330-20-7	xylene	130 ppm
556-67-2	octamethylcyclotetrasiloxane	30 ppm

· PAC-2:

108-88-3	toluene	560 ppm
141-78-6	ethyl acetate	1,700 ppm
57-55-6	propane-1,2-diol	1,300 mg/m3
1330-20-7	xylene	920* ppm
556-67-2	octamethylcyclotetrasiloxane	68 ppm

· PAC-3:

108-88-3	toluene	3700* ppm
141-78-6	ethyl acetate	10000** ppm
57-55-6	propane-1,2-diol	7,900 mg/m3
1330-20-7	xylene	2500* ppm
556-67-2	octamethylcyclotetrasiloxane	130 ppm

US

(Contd. on page 5)

Product number LOB603

Trade name: ACCELERATOR FOR POLYESTER

(Contd. of page 4)

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m³, 400 ppm

REL Long-term value: 1400 mg/m³, 400 ppm

TLV Long-term value: 1440 mg/m³, 400 ppm

57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m³

556-67-2 octamethylcyclotetrasiloxane

WEEL Long-term value: 10* ppm

*OARS WEEL

(Contd. on page 6)

US

Product number LOB603

Trade name: ACCELERATOR FOR POLYESTER

(Contd. of page 5)

· Ingredients with biological limit values:

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
------------	--

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

Product number LOB603

Trade name: ACCELERATOR FOR POLYESTER

(Contd. of page 6)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

77°C (°F)

· Flash point:

-4°C (°F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

371°C (°F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:

1.1 Vol %

· Upper:

12.6 Vol %

· Vapor pressure at 20°C (68 °F):

97 hPa (mm Hg)

· Density at 20°C (68 °F):

0.914 g/cm (lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20°C (68 °F):

40 s (ISO 4 mm)

· Oxidising properties:

N.A.

· Solvent content:

· VOC content:

88.61 %

809.9 g/l / 6.76 lb/gl

· Solids content:

11.4 %

(Contd. on page 8)

Product number LOB603

Trade name: ACCELERATOR FOR POLYESTER

(Contd. of page 7)

· **Other information (HAPS)**

108-88-3	toluene	30-49.9%
1330-20-7	xylene	2.5-4.99%
· Other information		No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
 - **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with strong acids and oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12,124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	25.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Dermal	LD50	20,001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	1,600 mg/l (rat/szczur/mouse/souris/Maus/ratón)
	LC0	22.6 ppm (mouse)

136-52-7 cobalt bis(2-ethylhexanoate)

Oral	LD50	2,119 mg/kg (mouse)
		4,300 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5,001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50	5,000 ppm (rat/szczur/mouse/souris/Maus/ratón) (4 h)

57-55-6 propane-1,2-diol

Oral	LD50	20,000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2,001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)

1330-20-7 xylene

Oral	LD50.	3,523 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50.	12,126 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

(Contd. on page 9)

Product number LOB603

Trade name: ACCELERATOR FOR POLYESTER

(Contd. of page 8)

Inhalative	LC50/4h.	27.571 mg/l (rat/szczur/mouse/souris/Maus/ratón)
556-67-2 octamethylcyclotetrasiloxane		
Oral	LD50	4,800 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2,500 mg/kg (Rabbit)
Inhalative	LC50/4 h	2,975 mg/l (rat/szczur/mouse/souris/Maus/ratón)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
 - Irritant
 - Causes skin irritation.
 - Causes serious eye irritation.
 - May cause an allergic skin reaction.
 - Suspected of damaging fertility or the unborn child.
 - May cause drowsiness or dizziness.
 - May cause damage to organs through prolonged or repeated exposure.
 - May be fatal if swallowed and enters airways.

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
136-52-7	cobalt bis(2-ethylhexanoate)	2B
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- **Toxicity** Harmful to aquatic life with long lasting effects.

· Aquatic toxicity:	
108-88-3 toluene	
EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)
141-78-6 ethyl acetate	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)
57-55-6 propane-1,2-diol	
EC50	19,000 mg/l (algae) (48 h)
	18,340 mg/l (daphnia) (48 h)
LC50 (96h)	40,613 mg/l (Fish)

· **Persistence and degradability**

Data refers to the substance Toluene CAS No. 108-88-3
Readily biodegradable (according to OECD criteria and/or EU RAR)

· Substances Easily biodegradable	
108-88-3	toluene

(Contd. on page 10)

Product number LOB603

Trade name: ACCELERATOR FOR POLYESTER

(Contd. of page 9)

141-78-6	ethyl acetate	.
57-55-6	propane-1,2-diol	.
1330-20-7	xylene	.

· **Behavior in environmental systems:**

- *Bioaccumulative potential* No further relevant information available.
- *Mobility in soil* No further relevant information available.

· **Ecotoxic effects:**

- *Remark:* Harmful to fish

· **Additional ecological information:**

· *General notes:*

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· *Recommendation:*

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Hand over to hazardous waste disposers.
Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

- *Recommendation:* Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

- *DOT* NA1263
- *IMDG, IATA* UN1263

· **UN proper shipping name**

- *DOT* Paint
- *IMDG, IATA* PAINT

· **Transport hazard class(es)**

· *DOT*




- *Class* 3 Flammable liquids
- *Label* 3
- *Class* 3 Flammable liquids

(Contd. on page 11)

Product number LOB603

Trade name: ACCELERATOR FOR POLYESTER

(Contd. of page 10)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

108-88-3	toluene	30-49.9%
136-52-7	cobalt bis(2-ethylhexanoate)	10-12.49%
1330-20-7	xylene	2.5-4.99%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 09/26/2017

Version number 365

Reviewed on 09/04/2017

Product number LOB603**Trade name: ACCELERATOR FOR POLYESTER**

(Contd. of page 11)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene		30-49.9%
----------	---------	--	----------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II	30-49.9%
1330-20-7	xylene	I	2.5-4.99%

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene		A4
1330-20-7	xylene		A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 09/26/2017 / 364

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Acute Tox. 4: Acute toxicity . Category 4

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A

Skin Sens. 1: Skin sensitisation . Category 1

Carc. 2: Carcinogenicity . Category 2

Carc. 2: Carcinogenicity . Category 2

Repr. 2: Reproductive toxicity . Category 2

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

(Contd. on page 13)

Safety Data Sheet
29 CFR Parts 1910 1915 1926

Printing date 09/26/2017

Version number 365

Reviewed on 09/04/2017

Product number LOB603**Trade name: ACCELERATOR FOR POLYESTER**

(Contd. of page 12)

*STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2**Asp. Tox. 1: Aspiration hazard . Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard . Category 1**Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard . Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3**Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard . Category 4***• Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

*Agency ECHA web site**INRS Fiche Toxicologique**IARC International agency for research on cancer***• * Data compared to the previous version altered.**

US