

## 1 Identification

### · Product identifier

- Product number LQA24011
- Trade name: **INSULATOR**
- Relevant identified uses of the substance or mixture and uses advised against  
Paint and relative material only for wood
- Application of the substance / the mixture For professional use

### · Details of the supplier of the safety data sheet

- Manufacturer/Supplier:  
IVM Chemicals srl  
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
- Information department:  
Environmental Health and safety office  
hseoffice@ivmchemicals.com
- Emergency telephone number:  
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

## 2 Hazard(s) identification

### · Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

### · Label elements

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### · Hazard pictograms



GHS02



GHS07



GHS08

**Product number LQA24011**  
**Trade name: INSULATOR**

(Contd. of page 1)

· **Signal word** Danger

· **Hazard-determining components of labeling:**

toluene

4,4'-methylenediphenyl diisocyanate

ethyl acetate

Aromatic polyisocyanate

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*1

Fire = 3

Reactivity = 0

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.














· **Dangerous components:**

141-78-6	ethyl acetate	30-49.9%
	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	

(Contd. on page 3)

**Product number LQA24011**  
**Trade name: INSULATOR**

(Contd. of page 2)

108-88-3	toluene  Flam. Liq. 2, H225  Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Chronic 3, H412	20-24.9%
110-19-0	isobutyl acetate  Flam. Liq. 2, H225	12.5-15%
101-68-8	4,4'-methylenediphenyl diisocyanate  Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-9.99%
53317-61-6	Aromatic polyisocyanate  Acute Tox. 4, H332; Eye Irrit. 2A, H319; Skin Sens. 1, H317	2.5-4.99%
108-65-6	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226	2.5-4.99%
78-93-3	butanone  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	2.5-4.99%
26471-62-5	m-tolylidene diisocyanate  Acute Tox. 2, H330  Resp. Sens. 1, H334; Carc. 2, H351  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 Aquatic Chronic 3, H412	<0.1%

## 4 First-aid measures

### · Description of first aid measures

#### · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · After swallowing: Do not induce vomiting; immediately call for medical help.

#### · Information for doctor:

##### · Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

##### · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

US

(Contd. on page 4)

**Product number LQA24011**  
**Trade name: INSULATOR**

(Contd. of page 3)

## 5 Fire-fighting measures

- **Extinguishing media**

- *Suitable extinguishing agents:* Alcohol resistant foam, CO, powder, water spray/mist.

- *For safety reasons unsuitable extinguishing agents:*

- Do not use a jet water stream as it may scatter and spread fire.

- **Special hazards arising from the substance or mixture**

- Formation of toxic gases is possible during heating or in case of fire.

- **Advice for firefighters**

- Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

- *Protective equipment:*

- Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

- Wear protective equipment. Keep unprotected persons away.

- Ensure adequate ventilation

- Keep away from ignition sources

- **Environmental precautions:**

- Do not allow product to reach sewage system or any water course.

- Inform respective authorities in case of seepage into water course or sewage system.

- Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

- Dispose contaminated material as waste according to Section 13.

- Ensure adequate ventilation.

- Do not flush with water or aqueous cleansing agents

- **Reference to other sections**

- See Section 7 for information on safe handling.

- See Section 8 for information on personal protection equipment.

- See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**

- *Precautions for safe handling*

- Ensure good ventilation/exhaustion at the workplace.

- Prevent formation of aerosols.

- Protect against electrostatic charges.

- Use explosion-proof apparatus / fittings and spark-proof tools.

- *Information about protection against explosions and fires:*

- Keep ignition sources away - Do not smoke.

- Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- *Storage:*

- *Requirements to be met by storerooms and receptacles:*

- Store in a cool, well-ventilated area, away from heat and sources of ignition

- Provide solvent resistant, sealed floor.

- Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

(Contd. on page 5)

**Product number LQA24011**  
**Trade name: INSULATOR**

(Contd. of page 4)

In cases where there is no reported expiration date , it means that the product must be used within 8 months.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** Those typical of the product and the instructions in the data sheet if required.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

### 141-78-6 ethyl acetate

PEL	Long-term value: 1400 mg/m , 400 ppm
REL	Long-term value: 1400 mg/m , 400 ppm
TLV	Long-term value: 1440 mg/m , 400 ppm

### 108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m , 150 ppm Long-term value: 375 mg/m , 100 ppm
TLV	Long-term value: 75 mg/m , 20 ppm BEI

### 110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: NIC-712 mg/m , NIC-150 ppm Long-term value: (713) NIC-238 mg/m , (150) NIC-50 ppm

### 101-68-8 4,4'-methylenediphenyl diisocyanate

PEL	Ceiling limit value: 0.2 mg/m , 0.02 ppm
REL	Long-term value: 0.05 mg/m , 0.005 ppm Ceiling limit value: 0.2* mg/m , 0.02* ppm *10-min
TLV	Long-term value: 0.051 mg/m , 0.005 ppm

### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

### 78-93-3 butanone

PEL	Long-term value: 590 mg/m , 200 ppm
REL	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm
TLV	Short-term value: 885 mg/m , 300 ppm Long-term value: 590 mg/m , 200 ppm BEI

(Contd. on page 6)

**Product number LQA24011**  
**Trade name: INSULATOR**

(Contd. of page 5)

**· Ingredients with biological limit values:**

**108-88-3 toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

**78-93-3 butanone**

BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK
-----	---

**· Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls**

**· Personal protective equipment:**

**· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

**· Breathing equipment:**

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**· Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)



**Product number LQA24011**  
**Trade name: INSULATOR**

(Contd. of page 6)

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

##### · Appearance:

##### · Form:

Fluid

##### · Color:

According to product specification

##### · Odor:

Characteristic

##### · Odour threshold:

Not determined.

##### · pH-value:

Not determined.

#### · Change in condition

##### · Melting point/Melting range:

Undetermined.

##### · Boiling point/Boiling range:

77 °C (171 °F)

##### · Flash point:

-4 °C (25 °F)

##### · Flammability (solid, gaseous):

Not applicable.

##### · Ignition temperature:

315 °C (599 °F)

##### · Decomposition temperature:

Not determined.

##### · Auto igniting:

Product is not selfigniting.

##### · Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

#### · Explosion limits:

##### · Lower:

0.4 Vol %

##### · Upper:

11.5 Vol %

##### · Vapor pressure at 20 °C (68 °F):

105 hPa (79 mm Hg)

##### · Density at 20 °C (68 °F):

0.938 g/cm (7.828 lbs/gal)

##### · Relative density

Not determined.

##### · Vapour density

Not determined.

##### · Evaporation rate

Not determined.

#### · Solubility in / Miscibility with

##### · Water:

Not miscible or difficult to mix.

##### · Partition coefficient (n-octanol/water):

Not determined.

#### · Viscosity:

##### · Dynamic:

Not determined.

##### · Kinematic at 20 °C (68 °F):

29 s (ISO 3 mm)

#### · Oxidising properties:

N.A.

#### · Solvent content:

##### · VOC content:

78.0 %

731.3 g/l / 6.10 lb/gl

##### · Solids content:

22.0 %

(Contd. on page 8)

**Product number LQA24011**  
**Trade name: INSULATOR**

(Contd. of page 7)

· **Other information (HAPS)**

108-88-3	toluene	20-24.9%
101-68-8	4,4'-methylenediphenyl diisocyanate	5-9,99%
26471-62-5	m-tolylidene diisocyanate	<0.1%
· <b>Other information</b>		No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
  - **Chemical stability** The product is stable in normal conditions of storage and use recommended
  - **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Reacts with strong acids and oxidizing agents.  
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
in case of possible formation of combustion:  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
  - **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>141-78-6 ethyl acetate</b>		
Oral	LD50	4934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Dermal	LD50	20001 mg/kg (Con)
Inhalative	LC0	22.6 ppm (mouse)
	LC50/4 h	1600 mg/l (rat/szczur/mouse/souris/Maus/ratón)
<b>108-88-3 toluene</b>		
Oral	LD50	5000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	25.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)
<b>110-19-0 isobutyl acetate</b>		
Oral	LD50	13400 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	17401 mg/kg (Con)
Inhalative	LC50/4 h	31 mg/l (rat/szczur/mouse/souris/Maus/ratón)
<b>101-68-8 4,4'-methylenediphenyl diisocyanate</b>		
Oral	LD50	2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	9401 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
<b>53317-61-6 Aromatic polyisocyanate</b>		
Oral	LD50	5001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)

(Contd. on page 9)



**Product number** LQA24011  
**Trade name:** INSULATOR

(Contd. of page 8)

### 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8532 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	35.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)

### 78-93-3 butanone

Oral	LD50	2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50	21 mg/l (rat/szczur/mouse/souris/Maus/ratón)

### 26471-62-5 m-tolylidene diisocyanate

Oral	LD50	5110 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	9401 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	0.107 mg/l (rat/szczur/mouse/souris/Maus/ratón)

· **Primary irritant effect:**

- *on the skin:* Irritant to skin and mucous membranes.
- *on the eye:* Irritating effect.

· **Sensitization:**

- Sensitization possible through inhalation.
- Sensitization possible through skin contact.

· **Additional toxicological information:**

- Causes skin irritation.
- Causes serious eye irritation.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause an allergic skin reaction.
- Suspected of causing cancer.
- Suspected of damaging the unborn child.
- May cause drowsiness or dizziness.
- May cause damage to organs through prolonged or repeated exposure.
- May be fatal if swallowed and enters airways.
- Contains isocyanates. May produce an allergic reaction.
- Harmful
- Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

101-68-8	4,4'-methylenediphenyl diisocyanate	3
26471-62-5	m-tolylidene diisocyanate	2B
98-88-4	benzoyl chloride	2A

· **NTP (National Toxicology Program)**

26471-62-5	m-tolylidene diisocyanate	<0.1%
------------	---------------------------	-------

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **More information**

(Contd. on page 10)

# Safety Data Sheet

## 29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 46

Reviewed on 09/18/2015

**Product number** LQA24011  
**Trade name:** INSULATOR

(Contd. of page 9)

Monomers / polymers isocyanate

Particular characteristics / effects; prolonged exposure may irritate the eyes, nose, throat and respiratory tract.

Isocyanate exposure may result in the delayed appearance of respiratory disorders, cough or asthma. Sensitive individuals may show exposure symptoms to isocyanates below workplace TLV values. Prolonged skin contact may result cause irritation and dehydration.

## 12 Ecological information

### · Toxicity

#### · Aquatic toxicity:

#### **141-78-6 ethyl acetate**

EC50 165 mg/l (daphnia) (48 h)

LC50 (96h) 230 mg/l (Fish)

#### **108-88-3 toluene**

EC50 134 mg/l (algae) (3 h)

3.78 mg/l (daphnia) (48 h)

58 mg/l (Fish)

#### **110-19-0 isobutyl acetate**

EC50 370 mg/l (algae) (72 h)

25 mg/l (daphnia)

LC50 (96h) 17 mg/l (Fish)

#### **101-68-8 4,4'-methylenediphenyl diisocyanate**

EC50 1001 mg/l (daphnia) (24 h)

LC50 (96h) 1001 mg/l (Fish) (96 h)

#### **108-65-6 2-methoxy-1-methylethyl acetate**

EC50 1001 mg/l (algae) (72 h)

501 mg/l (daphnia) (48 h)

LC50 (96h) 134 mg/l (Fish)

#### **78-93-3 butanone**

EC50 2029 mg/l (algae) (96 h)

308 mg/l (daphnia) (48 h)

LC50 (96h) 2993 mg/l (Fish)

#### **26471-62-5 m-tolylidene diisocyanate**

EC50 12.5 mg/l (daphnia) (48h)

LC50 (96h) 133 mg/l (Leuciscus idus melanotus)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 11)

# Safety Data Sheet 29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 46

Reviewed on 09/18/2015

**Product number** LQA24011  
**Trade name:** INSULATOR

(Contd. of page 10)

· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· **UN-Number**

· **DOT**

NA1263

· **IMDG, IATA**

UN1263

· **UN proper shipping name**

· **DOT**

Paint

· **IMDG, IATA**

PAINT

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

· **Label**

3

· **Class**

3 Flammable liquids

· **Label**

3

· **IMDG, IATA**



· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**

· **DOT, IMDG, IATA**

II

· **Environmental hazards:**

· **Marine pollutant:**

No

· **Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):**

33

· **EMS Number:**

F-E, S-E

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

(Contd. on page 12)

**Product number LQA24011**  
**Trade name: INSULATOR**

(Contd. of page 11)

**· Transport/Additional information:**

**· IMDG**

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**· UN "Model Regulation":**

UN1263, Paint, special provision 640D, 3, II

**15 Regulatory information**

**· Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

**· SARA**

**· Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**· Section 313 (Specific toxic chemical listings) :**

108-88-3	toluene	20-24.9%
101-68-8	4,4'-methylenediphenyl diisocyanate	5-9,99%
78-93-3	butanone	2,5-4,99%
26471-62-5	m-tolyldiene diisocyanate	<0.1%
98-88-4	benzoyl chloride	<0.01%

**· TSCA (Toxic Substances Control Act):**

All ingredients are listed.

**· Proposition 65**

**· Chemicals known to cause cancer:**

26471-62-5	m-tolyldiene diisocyanate	*	<0.1%
------------	---------------------------	---	-------

**· Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene	20-24.9%
70657-70-4	2-methoxypropyl acetate	<0.1%
1589-47-5	2-methoxypropanol	<0.01%

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

108-88-3	toluene	20-24.9%
----------	---------	----------

**· Carcinogenic categories**

**· EPA (Environmental Protection Agency)**

108-88-3	toluene	II	20-24.9%
101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD	5-9,99%
78-93-3	butanone	I	2,5-4,99%

**· TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
----------	---------	----

(Contd. on page 13)

# Safety Data Sheet

## 29 CFR Parts 1910 1915 1926

Printing date 09/18/2015

Version number 46

Reviewed on 09/18/2015

**Product number** LQA24011  
**Trade name:** INSULATOR

(Contd. of page 12)

26471-62-5	m-tolylidene diisocyanate	(A4)
98-88-4	benzoyl chloride	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
26471-62-5	m-tolylidene diisocyanate	<0.1%

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** IVM Chemicals Srl

· **Contact:** See emergency phone

· **Date of preparation / last revision** 09/18/2015 / 45

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 2: Acute toxicity, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· **Sources**

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

· **\* Data compared to the previous version altered.**