

Printing date 09/26/2017

Version number 34

Reviewed on 09/21/2017

1 Identification

- · Product identifier
 - · Product number LTC18494
 - · Trade name: ADDITIVE
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

H225 Highly flammable liquid and vapor. Flam. Lig. 2



GHS07

Eve Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Acute 3 H402 Harmful to aquatic life.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: ethyl acetate
- · Hazard statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment. P241

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

(Contd. on page 2)



Printing date 09/26/2017 Version number 34 Reviewed on 09/21/2017

Product number LTC18494 Trade name: ADDITIVE

(Contd. of page 1)

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 0

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - · Description: Mixture: consisting of the following components.

· Dangerous components:				
141-78-6	ethyl acetate	 Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336 	75-100%	
107-46-0	hexamethyldisiloxane	Flam. Liq. 2, H225Aquatic Acute 1, H400	0.5-1%	

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - Most important symptoms and effects, both acute and delayed
 For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
 - · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.

(Contd. on page 3)



Printing date 09/26/2017

Version number 34

Reviewed on 09/21/2017

Product number LTC18494 Trade name: ADDITIVE

(Contd. of page 2)

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

Trotodivo florion efficination					
· PAC-1.					
141-78-6	ethyl acetate	1,200 ppm			
107-46-0	hexamethyldisiloxane	13 ppm			
· PAC-2:					
141-78-6	ethyl acetate	1,700 ppm			
107-46-0	hexamethyldisiloxane	140 ppm			
· PAC-3.	· PAC-3:				
141-78-6	ethyl acetate	10000** ppm			
107-46-0	hexamethyldisiloxane	150 ppm			

7 Handling and storage

- · Handling:
 - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)



Printing date 09/26/2017

Version number 34

Reviewed on 09/21/2017

Product number LTC18494 Trade name: ADDITIVE

(Contd. of page 3)

· Conditions for safe storage, including any incompatibilities

- · Storage:
 - · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m³, 400 ppm REL Long-term value: 1400 mg/m³, 400 ppm TLV Long-term value: 1440 mg/m³, 400 ppm

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)




Printing date 09/26/2017 Version number 34 Reviewed on 09/21/2017

Product number LTC18494 Trade name: **ADDITIVE**

(Contd. of page 4)

· Eye protection:



Information on basic physical and	chemical properties
· General Information · Appearance:	
· Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	77°C (°F)
· Flash point:	-4°C (°F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	460°C (°F)
\cdot Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explos
	air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	2.1 Vol %
· Upper:	11.5 Vol %
· Vapor pressure at 20°C (68 °F):	97 hPa (mm Hg)
· Density at 20°C (68 °F):	0.9 g/cm³ (lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
Kinematic at 20°C (68 °F):	40 s (ISO 4 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· VOC content:	90.90 %
	818.1 g/l / 6.83 lb/gl
· Solids content:	9.1 %



Printing date 09/26/2017

Version number 34

Reviewed on 09/21/2017

Product number LTC18494 Trade name: ADDITIVE

(Contd. of page 5)

· Other information (HAPS)

None of the ingredients is listed.

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
 - · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Vapours may form explosive mixtures with air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

in case of possible formation of combustion:

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Dermal	LD50	20,001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	1,600 mg/l (rat/szczur/mouse/souris/Maus/ratón)
	LC0	22.6 ppm (mouse)

- · Primary irritant effect:
 - · on the skin: No irritant effect.
 - · on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Irritant

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.



Printing date 09/26/2017 Version number 34 Reviewed on 09/21/2017

Product number LTC18494 Trade name: ADDITIVE

(Contd. of page 6)

12 Ecological information

- · Toxicity
 - · Aquatic toxicity:

141-78-6 ethyl acetate

EC50 165 mg/l (daphnia) (48 h)

LC50 (96h) 230 mg/l (Fish)

- · Persistence and degradability No further relevant information available.
 - · Substances Easily biodegradable

141-78-6 ethyl acetate .

- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- Additional ecological information:
 - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT NA 1263 *· IMDG, IATA* UN1263

· UN proper shipping name

· DOT Paint · IMDG, IATA PAINT

- · Transport hazard class(es)
 - $\cdot DOT$



· Class 3 Flammable liquids

· Label

· Class 3 Flammable liquids

3

(Contd. on page 8)



3

3

Printing date 09/26/2017 Version number 34 Reviewed on 09/21/2017

Product number LTC18494 Trade name: ADDITIVE

(Contd. of page 7)

· Label

· IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group

· DOT, IMDG, IATA

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): 33

• EMS Number: F-E,S-E • Stowage Category B

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30

ml

Maximum net quantity per outer packaging:

500 ml

• UN "Model Regulation": UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 9)



Printing date 09/26/2017

Version number 34

Reviewed on 09/21/2017

Product number LTC18494 ADDITIVE Trade name:

(Contd. of page 8)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 09/26/2017 / 33
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Lig. 2: Flammable liquids - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer