

Printing date 09/18/2015

Version number 116

Reviewed on 09/18/2015

1 Identification

- · Product identifier
 - · Product number LZC1026
 - · Trade name: P.U. THINNER
 - · Relevant identified uses of the substance or mixture and uses advised against

Thinner for paint products

- · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS

GHS07 GHS0

- · Signal word Danger
- · Hazard-determining components of labeling: toluene

(Contd. on page 2)



Printing date 09/18/2015 Version number 116 Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

(Contd. of page 1)

ethyl acetate

n-butyl acetate

acetone

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 IF ON SKIN (or hair): Řemove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 4

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*1 Health = *1

Fire = 4

Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description:

Mixture: consisting of the following components.

Solvent mixture

108-88-3	toluene
	 Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Chronic 3, H412
	& Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304
	♦ Skin Irrit. 2, H315; STOT SE 3, H336
	Åquatic Chronic 3, H412

141-78-6 ethyl acetate

Flam. Liq. 2, H225

Eye Irrit. 2, H319; STOT SE 3, H336

30-49.9%

30-49.9%

(Contd. on page 3)



Printing date 09/18/2015

Version number 116

Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

	(1	Contd. of page 2)
123-86-4	n-butyl acetate	10-<15%
	Flam. Liq. 3, H226STOT SE 3, H336	
67-64-1	acetone	5-9.99%
	 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 	
108-65-6	2-methoxy-1-methylethyl acetate	2.5-4.99%
	♦ Flam. Liq. 3, H226	

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - Most important symptoms and effects, both acute and delayed

 For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
 - · For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)



Printing date 09/18/2015

Version number 116

Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

(Contd. of page 3)

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
 - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)



Printing date 09/18/2015

Version number 116

Reviewed on 09/18/2015

Product number LZC1026 P.U. THINNER Trade name:

(Contd. of page 4)

Control parameters

	ol parameters
· Coi	nponents with limit values that require monitoring at the workplace:
108-88	3-3 toluene
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV	Long-term value: 75 mg/m³, 20 ppm BEI
141-78	3-6 ethyl acetate
PEL	Long-term value: 1400 mg/m³, 400 ppm
REL	Long-term value: 1400 mg/m³, 400 ppm
TLV	Long-term value: 1440 mg/m³, 400 ppm
123-80	6-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm
67-64-	1 acetone
PEL	Long-term value: 2400 mg/m³, 1000 ppm
REL	Long-term value: 590 mg/m³, 250 ppm
TLV	Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI
108-6	5-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm

· Ingredients with biological limit values:

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

67-64-1 acetone

(Contd. on page 6)



Printing date 09/18/2015

Version number 116

Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

(Contd. of page 5)

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
 - · General Information
 - · Appearance:

· Form: Fluid

· Color: According to product specification

Odor: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

· Melting point/Melting range: Undetermined.

(Contd. on page 7)



Printing date 09/18/2015 Version number 116 Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

	(C	ontd. of page
· Boiling point/Boiling range:	56 °C (133 °F)	
· Flash point:	-17 °C (1 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	315 °C (599 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
· Lower:	1.2 Vol %	
· Upper:	13.0 Vol %	
· Vapor pressure at 20 °C (68 °F):	233 hPa (175 mm Hg)	
· Density at 20 °C (68 °F):	0.879 g/cm³ (7.335 lbs/gal)	
Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
· Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm)	
· Oxidising properties:	N.A.	
· Solvent content:		
· VOC content:	95.0 %	
	834.8 g/l / 6.97 lb/gl	
Other information (HAPS)		
108-88-3 toluene		30-49.9
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
 - · Chemical stability The product is stable in normal conditions of storage and use recommended
 - · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions

Reacts with strong acids and oxidizing agents.

Vapours may form explosive mixtures with air

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

in case of possible formation of combustion:

(Contd. on page 8)



Printing date 09/18/2015

Version number 116

Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

Carbon monoxide and carbon dioxide

(Contd. of page 7)

11 Toxicological information

· Information on toxicological effects

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

· Acute toxicity:

Acute	-		
$\cdot LD/$	LC50 value	es that are relevant for classification:	
108-88-3 t	toluene		
Oral	LD50	5000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	12124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
Inhalative	LC50/4 h	25.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)	
141-78-6	ethyl aceta	ate	
Oral	LD50	4934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
Dermal	LD50	20001 mg/kg (Con)	
Inhalative	LC0	22.6 ppm (mouse)	
	LC50/4 h	1600 mg/l (rat/szczur/mouse/souris/Maus/ratón)	
123-86-4	n-butyl ac	etate	
Oral	LD50	10760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	14000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
Inhalative	LC50/4 h	21.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)	
67-64-1 a	cetone		
Oral	LD50	5800 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	20000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
Inhalative	LC50/4 h	76 mg/l (rat/szczur/mouse/souris/Maus/ratón)	
108-65-6	2-methoxy	v-1-methylethyl acetate	
Oral	LD50	8532 mg/kg (rat/szczur/mouse/souris/Maus/ratón)	
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)	
Inhalative	LC50/4 h	35.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)	

- · Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - · on the eye:

Irritating effect.

Causes serious eye irritation.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Irritant

May cause drowsiness or dizziness.

(Contd. on page 9)



Printing date 09/18/2015

Version number 116

Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

(Contd. of page 8)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

TOXICITY					
· Aquatic t	oxicity:				
108-88-3 to	luene				
EC50	134 mg/l (algae) (3 h)				
	3.78 mg/l (daphnia) (48 h)				
	58 mg/l (Fish)				
141-78-6 et	hyl acetate				
EC50	165 mg/l (daphnia) (48 h)				
LC50 (96h)) 230 mg/l (Fish)				
123-86-4 n-	butyl acetate				
EC50	648 mg/l (algae) (72 h)				
	44 mg/l (daphnia) (48 h)				
LC50 (96h)	18 mg/l (Fish)				
67-64-1 ace	etone				
EC50	8800 mg/l (daphnia)				
LC50 (96h)	5540 mg/l (Fish)				
108-65-6 2-	methoxy-1-methylethyl acetate				
EC50	1001 mg/l (algae) (72 h)				
	501 mg/l (daphnia) (48 h)				
LC50 (96h)	134 mg/l (Fish)				

- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Additional ecological information:
 - · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Other adverse effects No further relevant information available.

- 119



Printing date 09/18/2015 Version number 116 Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

(Contd. of page 9)

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

Transport information		
UN-Number		
$\cdot DOT$	NA 1263	
· IMDG, IATA	UN1263	
UN proper shipping name		
$\cdot DOT$	Paint	
· IMDG, IATA	PAINT	
Transport hazard class(es)		
\cdot DOT		
FLAMMABLE LIQUID		
3		
· Class	3 Flammable liquids	
· Label	3	
· Class	3 Flammable liquids	
\cdot Label	3	
· IMDG, IATA		
3		
· Class	2 Flammable liquida	
· Label	3 Flammable liquids 3	
Packing group	II	
· DOT, IMDG, IATA		
Environmental hazards:		
· Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
· Danger code (Kemler):	33	
· EMS Number:	F-E, <u>S-E</u>	

(Contd. on page 11)



Printing date 09/18/2015

Version number 116

Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

(Contd. of page 10)

• Transport/Additional information:

• IMDG

• Limited quantities (LQ)
• Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

• UN "Model Regulation":

UN1263, Paint, special provision 640D, 3, II

	alth and environmen	tal regulations/legislation speci	fic for the substance
mixture	to of Fordonal Dominton		
<u> </u>	ts of Federal Register		
· SARA	255 / , 1.1 1		
	n 355 (extremely hazardo	us substances):	
	ingredients is listed.		
	n 313 (Specific toxic cher	nical listings) :	
108-88-3 to	luene		30-49.9%
· TSCA (Ta	oxic Substances Control A	(ct):	
All ingredien	nts are listed.		
· Propositio	on 65		
· Chemi	icals known to cause cand	cer:	
None of the	ingredients is listed.		
· Chemi	icals known to cause repr	oductive toxicity for females:	
108-88-3	toluene		30-49.9%
70657-70-4	2-methoxypropyl aceta	te	<0.1%
1589-47-5	2-methoxypropanol		<0.01%
· Chemi	icals known to cause repr	oductive toxicity for males:	'
	ingredients is listed.		
	icals known to cause deve	planmental taxicity:	
108-88-3 to		copmentationary.	30-49.99

als known to cause develop	nental toxicity:				
108-88-3 toluene			30-49	.9%	
ic categories					
nvironmental Protection Ag	rency)				
ene		11	30-49	30-49.9%	
tone		1	I 5-9,99%		
reshold Limit Value establ	ished by ACGIH)				
ene				A4	
tone				A4	
Ca (National Institute for (Occupational Safety and Health)				
gredients is listed.					
greaterits is listed.		(Cor	ntd. on pa		



Printing date 09/18/2015

Version number 116

Reviewed on 09/18/2015

Product number LZC1026
Trade name: P.U. THINNER

(Contd. of page 11)

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - Date of preparation / last revision 09/18/2015 / 115
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

·Sources

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

* Data compared to the previous version altered.