

Printing date 08/01/2017

Version number 71

Reviewed on 08/01/2017

#### 1 Identification

- · Product identifier
  - · Product number LZC209
  - · Trade name: THINNER
    - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
  - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Lig. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eve Irrit. 2A H319 Causes serious eve irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

### · Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

toluene ethyl acetate n-butyl acetate butanone

(Contd. on page 2)



Printing date 08/01/2017

Version number 71

Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

(Contd. of page 1)

#### · Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3

 $\nearrow$  Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = \*1 Fire = 3 Reactivity = 0

### 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description:

Mixture: consisting of the following components.

Solvent mixture

| 141-78-6 | ethyl acetate  | 30-49.9%  |
|----------|--|-----------|
|          | <ul> <li>Flam. Liq. 2, H225</li> <li>Eye Irrit. 2A, H319; STOT SE 3, H336</li> </ul>   |           |
| 123-86-4 | n-butyl acetate  | 20-24.9%  |
|          | <ul><li>Flam. Liq. 3, H226</li><li>STOT SE 3, H336</li></ul>   |           |
| 108-88-3 | toluene  | 20-24.9%  |
|          | <ul> <li>Flam. Liq. 2, H225</li> <li>Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304</li> <li>Skin Irrit. 2, H315; STOT SE 3, H336</li> <li>Aquatic Chronic 3, H412</li> </ul> |           |
| 108-65-6 | 2-methoxy-1-methylethyl acetate  | 10-12.49% |
|          | ♦ Flam. Liq. 3, H226   |           |



Printing date 08/01/2017 Version

Version number 71 Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

|  | (Contd. of page 2) |
|--|--------------------|
| 78-93-3 butanone   | 5-9.99%            |
| <ul> <li>Flam. Liq. 2, H225</li> <li>Eye Irrit. 2A, H319; STOT SE 3, H336</li> </ul> |                    |

### 4 First-aid measures

#### · Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary). Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist , consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - · Most important symptoms and effects, both acute and delayed
    For symptoms and effects caused by substances, refer to Section 11.
  - Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
  - · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
  - $\cdot \textit{For safety reasons unsuitable extinguishing agents:} \\$

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 08/01/2017 Version number 71

Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

(Contd. of page 3)

#### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### Protective Action Criteria for Chemicals

| · PAC-1  | · PAC-1:                        |             |  |  |
|----------|---------------------------------|-------------|--|--|
| 141-78-6 | 6 ethyl acetate                 |             |  |  |
| 123-86-4 | n-butyl acetate                 |             |  |  |
| 108-88-3 | toluene                         |             |  |  |
| 108-65-6 | 2-methoxy-1-methylethyl acetate |             |  |  |
| 78-93-3  | 3 butanone                      |             |  |  |
| · PAC-2  | · PAC-2:                        |             |  |  |
| 141-78-6 | 141-78-6 ethyl acetate          |             |  |  |
| 123-86-4 | 4 n-butyl acetate               |             |  |  |
| 108-88-3 | -3 toluene                      |             |  |  |
| 108-65-6 | 2-methoxy-1-methylethyl acetate |             |  |  |
| 78-93-3  | 3 butanone                      |             |  |  |
| · PAC-3: |                                 |             |  |  |
| 141-78-6 | ethyl acetate                   | 10000** ppm |  |  |
| 123-86-4 | n-butyl acetate                 | 3000* ppm   |  |  |
| 108-88-3 | toluene                         | 3700* ppm   |  |  |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 5000* ppm   |  |  |
| 78-93-3  | utanone 4000* p <sub>k</sub>    |             |  |  |
|          |                                 |             |  |  |

### 7 Handling and storage

#### Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

#### Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

(Contd. on page 5)



Printing date 08/01/2017 Version number 71 Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

(Contd. of page 4)

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
  - · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

| 141-78                   | ethyl acetate  |  |  |  |
|--------------------------|--|--|--|--|
| PEL                      | Long-term value: 1400 mg/m³, 400 ppm   |  |  |  |
| REL                      | Long-term value: 1400 mg/m³, 400 ppm   |  |  |  |
| TLV                      | Long-term value: 1440 mg/m³, 400 ppm   |  |  |  |
| 123-86-4 n-butyl acetate |  |  |  |  |
| PEL                      | Long-term value: 710 mg/m³, 150 ppm  |  |  |  |
| REL                      | Short-term value: 950 mg/m³, 200 ppm<br>Long-term value: 710 mg/m³, 150 ppm        |  |  |  |
| TLV                      | Short-term value: 712 mg/m³, 150 ppm<br>Long-term value: 238 mg/m³, 50 ppm         |  |  |  |
| 108-65                   | 108-65-6 2-methoxy-1-methylethyl acetate   |  |  |  |
| WEEL                     | Long-term value: 50 ppm  |  |  |  |
| 78-93-                   | 3 butanone   |  |  |  |
| PEL                      | Long-term value: 590 mg/m³, 200 ppm  |  |  |  |
| REL                      | Short-term value: 885 mg/m³, 300 ppm<br>Long-term value: 590 mg/m³, 200 ppm        |  |  |  |
| TLV                      | Short-term value: 885 mg/m³, 300 ppm<br>Long-term value: 590 mg/m³, 200 ppm<br>BEI |  |  |  |

### · Ingredients with biological limit values:

#### 108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 6)



Printing date 08/01/2017

Version number 71

Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

(Contd. of page 5)

#### 78-93-3 butanone

BEI 2 mg/L

Medium: urine Time: end of shift Parameter: MEK

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
  - · General Information
    - · Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

(Contd. on page 7)



Printing date 08/01/2017 Version number 71 Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

|  | (Contd. of  | f page |
|--|---|--------|
| · pH-value:                            | Not determined.                                     |        |
| · Change in condition                  |   |        |
| · Melting point/Melting range:         | Undetermined.                                       |        |
| · Boiling point/Boiling range:         | 77 °C (171 °F)                                      |        |
| · Flash point:                         | -4 °C (25 °F)                                       |        |
| · Flammability (solid, gaseous):       | Not applicable.                                     |        |
| · Ignition temperature:                | 315 °C (599 °F)                                     |        |
| · Decomposition temperature:           | Not determined.                                     |        |
| · Auto igniting:                       | Product is not selfigniting.                        |        |
| · Danger of explosion:                 | Product is not explosive. However, formation of exp | losi   |
|  | air/vapor mixtures are possible.                    |        |
| · Explosion limits:                    |   |        |
| · Lower:                               | 1.2 Vol %   |        |
| · Upper:                               | 11.5 Vol %  |        |
| · Vapor pressure at 20 °C (68 °F):     | 105 hPa (79 mm Hg)                                  |        |
| · Density at 20 °C (68 °F):            | 0.871 g/cm³ (7.268 lbs/gal)                         |        |
| · Relative density                     | Not determined.                                     |        |
| · Vapor density                        | Not determined.                                     |        |
| · Evaporation rate                     | Not determined.                                     |        |
| · Solubility in / Miscibility with     |   |        |
| · Water:                               | Not miscible or difficult to mix.                   |        |
| · Partition coefficient (n-octanol/wat | er): Not determined.                                |        |
| · Viscosity:                           |   |        |
| · Dynamic:                             | Not determined.                                     |        |
| · Kinematic at 20 °C (68 °F):          | 29 s (ISO 3 mm)                                     |        |
| · Oxidising properties:                | N.A.  |        |
| · Solvent content:                     |   |        |
| · VOC content:                         | 100.0 %   |        |
|  | 871.0 g/l / 7.27 lb/gl                              |        |
| Other information (HAPS)               |   |        |
| 08-88-3 toluene                        | 20-2  | 4.99   |
| Other information                      | No further relevant information available.          |        |

# 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
  - · Chemical stability The product is stable in normal conditions of storage and use recommended
    - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with strong acids and oxidizing agents.

Vapours may form explosive mixtures with air

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 8)



Printing date 08/01/2017 Version number 71

Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

(Contd. of page 7)

### · Hazardous decomposition products:

in case of possible formation of combustion: Carbon monoxide and carbon dioxide

### 11 Toxicological information

- · Information on toxicological effects
  - · Acute toxicity:

| · Actie toxicity:   |            |  |
|---|------------|--|
| · LD/LC50 values that are relevant for classification:    |            |  |
| 141-78-6 ethyl acetate                                    |            |  |
| Oral LD50   |            | 4934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)  |
| Dermal  | LD50       | 20001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin) |
| Inhalative  | LC50/4 h   | 1600 mg/l (rat/szczur/mouse/souris/Maus/ratón)     |
|   | LC0        | 22.6 ppm (mouse)                                   |
| 123-86-4  | n-butyl ac | etate  |
| Oral  | LD50       | 10760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)   |
| Dermal  | LD50       | 14000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin) |
| Inhalative  | LC50/4 h   | 21.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)     |
| 108-88-3 toluene  |            |  |
| Oral  | LD50       | 5000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)    |
| Dermal  | LD50       | 12124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin) |
| Inhalative  | LC50/4 h   | 25.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)     |
| 108-65-6 2-methoxy-1-methylethyl acetate                  |            |  |
| Oral  | LD50       | 8532 mg/kg (rat/szczur/mouse/souris/Maus/ratón)    |
| Dermal  | LD50       | 5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)  |
| Inhalative  | LC50/4 h   | 35.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)     |
| 78-93-3 butanone  |            |  |
| Oral LD50 2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón) |            | 2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)    |
| Dermal  | LD50       | 5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)  |
| Inhalative  | LC50/4 h   | 21 mg/l (rat/szczur/mouse/souris/Maus/ratón)       |
|   |            |  |

- · Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Irritant

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

(Contd. on page 9)



Printing date 08/01/2017

Version number 71

Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

(Contd. of page 8)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

#### · Toxicity

### · Persistence and degradability No further relevant information available.

| · Substa | nces Easily biodegradable       |  |
|----------|---------------------------------|--|
| 141-78-6 | ethyl acetate                   |  |
| 123-86-4 | n-butyl acetate                 |  |
| 108-88-3 | toluene                         |  |
| 108-65-6 | 2-methoxy-1-methylethyl acetate |  |
| 78-93-3  | butanone                        |  |

#### · Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

#### · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Other adverse effects No further relevant information available.



Printing date 08/01/2017 Version number 71 Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

(Contd. of page 9)

# 13 Disposal considerations

- · Waste treatment methods
  - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
  - · Recommendation: Disposal must be made according to official regulations.

| Transport information                      |                            |  |
|--|----------------------------|--|
| UN-Number                                  |                            |  |
| $\cdot DOT$                                | NA1263                     |  |
| · IMDG, IATA                               | UN1263                     |  |
| UN proper shipping name                    |                            |  |
| $\cdot DOT$                                | Paint                      |  |
| · IMDG, IATA                               | PAINT                      |  |
| Transport hazard class(es)                 |                            |  |
| $\cdot$ DOT                                |                            |  |
| FLAMMARIE LOUID                            |                            |  |
| · Class                                    | 3 Flammable liquids        |  |
| · Label                                    | 3                          |  |
| · Class                                    | 3 Flammable liquids        |  |
| $\cdot$ Label                              | 3                          |  |
| · IMDG, IATA                               |                            |  |
| 3  |                            |  |
| · Class                                    | 3 Flammable liquids        |  |
| · Label                                    | 3                          |  |
| Packing group<br>· DOT, IMDG, IATA         | II .                       |  |
| Environmental hazards: · Marine pollutant: | No                         |  |
| Special precautions for user               | Warning: Flammable liquids |  |
| · Danger code (Kemler):                    | 33                         |  |
| · EMS Number:                              | F-E,S-E                    |  |

Not applicable.



Printing date 08/01/2017

Version number 71

Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

(Contd. of page 10)

· Transport/Additional information:

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

5L

Code: E2

Maximum net quantity per inner packaging: 30

m

Maximum net quantity per outer packaging:

500 ml

· UN "Model Regulation": UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

 108-88-3 toluene
 20-24.9%

 78-93-3 butanone
 5-9,99%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

70657-70-4 2-methoxypropyl acetate

<0.1%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

20-24.9%

· Carcinogenic categories

| · EPA    | · EPA (Environmental Protection Agency) |    |          |  |
|----------|---|----|----------|--|
| 108-88-3 | toluene                                 | 11 | 20-24.9% |  |
| 78-93-3  | butanone                                | 1  | 5-9,99%  |  |

· TLV (Threshold Limit Value established by ACGIH)

108-88-3 toluene

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 12)



Printing date 08/01/2017

Version number 71

Reviewed on 08/01/2017

Product number LZC209
Trade name: THINNER

(Contd. of page 11)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - Date of preparation / last revision 08/01/2017 / 70
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

\* Data compared to the previous version altered.