

Printing date 12/07/2017

Version number 1

Reviewed on 12/07/2017

1 Identification

- · Product identifier
 - · Product number LZC6AA1
 - Trade name: Diluente per tinte
 - \cdot Application of the substance / the mixture For professional use

· Details of the supplier of the safety data sheet

- Manufacturer/Supplier: IVM Chemicals srl
 Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
- Information department: Environmental Health and safety office hseoffice @ivmchemicals.com
- · Emergency telephone number:
- ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS07

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: ethyl acetate
- propan-2-ol

acetone

- · Hazard statements
- H225 Highly flammable liquid and vapor.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- · Precautionary statements
- P210Keep away from heat/sparks/open flames/hot surfaces. No smoking.P241Use explosion-proof electrical/ventilating/lighting/equipment.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)



Version number 1

Reviewed on 12/07/2017

Product number LZC6AA1	

Printing date 12/07/2017

Trade name:	Diluente per tinte
B (05	(Contd. of page 1)
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
· Classificatio	•
	ings (scale 0 - 4)
230	Health = 2 Fire = 3 Reactivity = 0
· HMIS-rat	ings (scale 0 - 4)

	Reactivity = 0	
		_

3

² Health = 2 Fire = 3

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description:

HEALTH

Mixture: consisting of the following components.

Solvent mixture

· Danger	rous components:		
141-78-6	ethyl acetate	 Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336 	50-74.9%
67-63-0	propan-2-ol	 Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336 	20-24.9%
67-64-1	acetone	 ♦ Flam. Liq. 2, H225 ♦ Eye Irrit. 2A, H319; STOT SE 3, H336 	10-12.49%

4 First-aid measures

· Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- personal protective equipment for first aid responders is recommended. (please see section 8)
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 - For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

US



Printing date 12/07/2017

Safety Data Sheet 29 CFR Parts 1910 1915 1926

Version number 1

Reviewed on 12/07/2017

Product number LZC6AA1 Trade name: Diluente per tinte

(Contd. of page 2)

5 Fire-fighting measures

· Extinguishing media

- · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
- · For safety reasons unsuitable extinguishing agents:
- Do not use a jet water stream as it may scatter and spread fire.
- · Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation. • Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1.	:	
141-78-6	ethyl acetate	1,200 ppm
67-63-0	propan-2-ol	400 ppm
67-64-1	acetone	200 ppm
· PAC-2	:	
141-78-6	ethyl acetate	1,700 ppm
67-63-0	propan-2-ol	2000* ppm
67-64-1	acetone	3200* ppm
· PAC-3	:	
141-78-6	ethyl acetate	10000** ppm
67-63-0	propan-2-ol	12000** ppm
67-64-1	acetone	5700* ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. of page 3)



Printing date 12/07/2017

Safety Data Sheet 29 CFR Parts 1910 1915 1926

Version number 1

Reviewed on 12/07/2017

Product number LZC6AA1 Trade name: Diluente per tinte

Prevent formation of aerosols.

Protect against electrostatic charges. Use explosion-proof apparatus / fittings and spark-proof tools. · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. · Conditions for safe storage, including any incompatibilities · Storage: • Requirements to be met by storerooms and receptacles: Store in a cool, well-ventilated area, away from heat and sources of ignition Provide solvent resistant, sealed floor. Observe the label precautions, the expiration date for the use, if not indicated, is from deliverv date of goods. In cases where there is no reported expiration date, it means that the product must be used within 8 months. · Information about storage in one common storage facility: Not required. · Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles. · Specific end use(s) Those typical of the product and the instructions in the data sheet if required. 8 Exposure controls/personal protection · Additional information about design of technical systems: No further data; see item 7. · Control parameters · Components with limit values that require monitoring at the workplace: 141-78-6 ethvl acetate PEL Long-term value: 1400 mg/m³, 400 ppm REL Long-term value: 1400 mg/m³, 400 ppm

- TLV Long-term value: 1440 mg/m³, 400 ppm
- 67-63-0 propan-2-ol
- PEL Long-term value: 980 mg/m³, 400 ppm
- REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
- TLV Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI

67-64-1 acetone

- PEL Long-term value: 2400 mg/m³, 1000 ppm
- REL Long-term value: 590 mg/m³, 250 ppm
- TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI

· Ingredients with biological limit values:

67-63-0 propan-2-ol

BEI 40 mg/L

Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

(Contd. on page 5)

US



Printing date 12/07/2017

Safety Data Sheet 29 CFR Parts 1910 1915 1926

Version number 1

Reviewed on 12/07/2017

Product number LZC6AA1 Trade name: Diluente per tinte

(Contd. of page 4)

67-64-1 acetone
BEI 50 ma/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

• General Information • Appearance:

· Form:

· pH-value:

- · Color:
- · Odor:
- Odor threshold:

Not determined.

Fluid

Characteristic

Not determined.

According to product specification

(Contd. on page 6)

US



Version number 1

Reviewed on 12/07/2017

Product number LZC6AA1 Trade name: Diluente per tinte

Printing date 12/07/2017

• Change in condition • Melting point/Melting range:	Undetermined.
• Boiling point/Boiling range:	56 °C (132.8 °F)
· Flash point:	-17 °C (1.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	425 °C (797 °F)
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	2 Vol %
· Upper:	13 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
• Density at 20 •C (68 •F):	0.8 g/cm³ (6.676 lbs/gal)
· Relative density	Not determined.
• Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wa	tter): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
• Kinematic at 20 •C (68 •F):	29 s (ISO 3 mm)
• Oxidising properties:	N.A.
· Solvent content:	
• VOC content:	90.00 %
	720.0 g/l / 6.01 lb/gl
· Solids content:	0.0 %
Other information (HAPS)	
None of the ingredients is listed.	
Other information	No further relevant information available.

10 Stability and reactivity

 \cdot **Reactivity** typical of the product as indicated in the data sheet

- Chemical stability The product is stable in normal conditions of storage and use recommended
 Thermal decomposition / conditions to be avoided:
 - No decomposition if used and stored according to specifications.
- · Possibility of hazardous reactions Vapours may form explosive mixtures with air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

in case of possible formation of combustion:

(Contd. on page 7)

⁻US

(Contd. of page 6)



Printing date 12/07/2017

Safety Data Sheet 29 CFR Parts 1910 1915 1926

Version number 1

Product number LZC6AA1 Trade name: Diluente per tinte

Carbon monoxide and carbon dioxide

11 Toxicological information

Information on toxicological effects

• Acute toxicity:

	· LD/LC50 values that are relevant for classification:		
1	141-78-6 ethyl acetate		
(Dral	LD50	4,934 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Ľ	Dermal	LD50	20,001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
l	nhalative	LC50/4 h	1,600 mg/l (rat/szczur/mouse/souris/Maus/ratón)
		LC0	22.6 ppm (mouse)
6	67-63-0 propan-2-ol		
(Dral	LD50	4,710 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Ľ	Dermal	LD50	12,800 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
l	nhalative	LC50/4 h	72.6 mg/l (rat/szczur/mouse/souris/Maus/ratón)
6	67-64-1 acetone		
(Dral	LD50	5,800 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Ľ	Dermal	LD50	20,000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
h	nhalative	LC50/4 h	76 mg/l (rat/szczur/mouse/souris/Maus/ratón)
	· Primary irritant effect ·		

Primary irritant effect:

 on the skin: No irritant effect.
 on the eye: Irritating effect.

 Sensitization: No sensitizing effects known.

• Additional toxicological information: Irritant

Causes serious eye irritation. May cause drowsiness or dizziness.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)

None of the ingredients is listed.

·NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity:

141-78-6 ethyl acetate

EC50 165 mg/l (daphnia) (48 h)

LC50 (96h) 230 mg/l (Fish)

67-63-0 propan-2-ol

EC50 1,001 mg/l (algae) (72 h)

(Contd. on page 8)



Version number 1

Reviewed on 12/07/2017

Product number LZC6AA1 Trade name: Diluente per tinte

Printing date 12/07/2017

	(Contd. of page 7
	10,000 mg/l (daphnia) (24 h)
LC50 (96h)	9,640 mg/l (Fish)
67-64-1 ace	tone
EC50	8,800 mg/l (daphnia)
LC50 (96h)	5,540 mg/l (Fish)
· Persistence	e and degradability No further relevant information available.
· Substanc	es Easily biodegradable
141-78-6 e	thyl acetate .
67-63-0 p	ropan-2-ol .
67-64-1 a	cetone .
	n environmental systems:
	nulative potential No further relevant information available.
	in soil No further relevant information available.
	ecological information:
· General 1	
	azard class 1 (Self-assessment): slightly hazardous for water
100000	llow undiluted product or large quantities of it to reach ground water, water course of
sewage	

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

UN-Number		
· DOT	NA 1263	
· IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
· IMDG, IATA	PAINT	
Transport hazard class(es)		
·DOT		
FLAMMABLE LIQUID		
3		
· Class	3 Flammable liquids	
· Label	3	



Printing date 12/07/2017

Version number 1

Reviewed on 12/07/2017

Product number	LZC6AA1
Trade name:	Diluente per tinte

	(Contd. of page
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	11
· Environmental hazards:	
• Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	В
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	II of Not applicable.
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	5L
$\cdot Excepted$ quantities (\widetilde{EQ})	Code: E2
	Maximum net quantity per inner packaging: 3
	ml
	Maximum net quantity per outer packaging 500 ml
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640C, 3, II

15 Regulatory information

· SARA	
· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings) :	
67-63-0 propan-2-ol	20-24.9%
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
	(Contd. on page 10)



Printing date 12/07/2017

Version number 1

Product number LZC6AA1 Trade name: Diluente per tinte

> • Chemicals known to cause developmental toxicity: None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

67-64-1 acetone

• TLV (Threshold Limit Value established by ACGIH) 67-63-0 propan-2-ol

67-64-1 acetone

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: IVM Chemicals Srl

· Contact: See emergency phone

· Date of preparation / last revision 12/07/2017 / -· Abbreviations and acronvms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer

us -

I 10-12.49%

10 10 10

A4

A4

(Contd. of page 9)