

Printing date 09/18/2015

Version number 117

Reviewed on 08/28/2015

1 Identification

- · Product identifier
 - · Product number LZC70
 - · Trade name: P.U. THINNER
 - · Relevant identified uses of the substance or mixture and uses advised against

Thinner for paint products

- · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Lig. 3 H226 Flammable liquid and vapor.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
 - · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02

2 GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

n-butyl acetate

· Hazard statements

H226 Flammable liquid and vapor.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

(Contd. on page 2)



Printing date 09/18/2015

Version number 117

Reviewed on 08/28/2015

Product number LZC70

Trade name: P.U. THINNER

(Contd. of page 1)

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 4 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 4 Reactivity = 0

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
 - · Description:

Mixture: consisting of the following components.

Solvent mixture

· Dange	rous components:		
123-86-4	n-butyl acetate	Flam. Liq. 3, H226STOT SE 3, H336	50 - 100%
108-65-6	2-methoxy-1-methylethyl acetate	♠ Flam. Liq. 3, H226	30-49.9%

4 First-aid measures

- · Description of first aid measures
 - · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.
 - · For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

- Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- · Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

(Contd. on page 3)



Printing date 09/18/2015

Version number 117

Reviewed on 08/28/2015

Product number LZC70

Trade name: P.U. THINNER

(Contd. of page 2)

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
 - · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - · Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)



Printing date 09/18/2015 Version number 117 Reviewed on 08/28/2015

Product number LZC70

Trade name: P.U. THINNER

(Contd. of page 3)

· Control parameters

· Com	nponents with limit values that require monitoring at the workplace:
123-86	-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm
108-65	-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures: Wash hands before breaks and at the end of work.
 - · Breathing equipment: Not required.
 - · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form: Fluid

· Color: According to product specification

Odor: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:
 Boiling point/Boiling range:
 Undetermined.
 124 °C (255 °F)

· Flash point: 25 °C (77 °F)

(Contd. on page 5)



Printing date 09/18/2015 Version number 117 Reviewed on 08/28/2015

Product number LZC70

Trade name: P.U. THINNER

	(Contd. of page
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosiv air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
· Upper:	10.8 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	0.908 g/cm³ (7.577 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wo	ater): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm)
· Oxidising properties:	N.A.
· Solvent content:	
· VOC content:	100.0 % 907.6 g/l / 7.57 lb/gl
· Other information (HAPS)	
None of the ingredients is listed.	
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
 - · Chemical stability The product is stable in normal conditions of storage and use recommended
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Vapours may form explosive mixtures with air
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

110



Printing date 09/18/2015

Version number 117

Reviewed on 08/28/2015

Product number LZC70

Trade name: P.U. THINNER

(Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

123-86-4 ı	n-butyl ac	etate
Oral	LD50	10760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	14000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	21.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8532 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	35.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)

· LD/LC50 values that are relevant for classification:

- · Primary irritant effect:
 - on the skin: No irritant effect.
 - · on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

May cause drowsiness or dizziness.

May cause drowsiness or dizziness.

- · Carcinogenic categories
 - · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic t	•
	butyl acetate
EC50	648 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
	44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
108-65-6 2-	methoxy-1-methylethyl acetate
EC50	1001 mg/l (algae) (72 h)
	501 mg/l (daphnia) (48 h)
LC50 (96h)	134 mg/l (Fish)

- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.

(Contd. on page 7)



Printing date 09/18/2015 Version number 117 Reviewed on 08/28/2015

Product number LZC70

Trade name: P.U. THINNER

(Contd. of page 6)

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

UN-Number		
· DOT	NA1263	
· IMDG, IATA	UN1263	
UN proper shipping name		
$\cdot DOT$	Paint	
· IMDG, IATA	PAINT	
Transport hazard class(es)		
\cdot DOT		
FLAMMRIE LIQUID		
· Class	3 Flammable liquids	
\cdot Label	3	
· Class	3 Flammable liquids	
· Label	3	
· IMDG, IATA		
· Class	3 Flammable liquids	
· Label	3	
Packing group		
· DOT, IMDĠ, IATA	III	
Environmental hazards:		
· Marine pollutant:	No	



Printing date 09/18/2015

Version number 117

Reviewed on 08/28/2015

Product number LZC70

Trade name: P.U. THINNER

(Contd. of page 7)

Danger code (Kemler): 30EMS Number: F-E,S-E

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

Remarks: Classification: 3 ADR P.G. III UN 1866

RESIN SOLUTION when packages > 450

liters

IMDG 3 P.G. III UN 1866

RESIN SOLUTION when packages > 30 liters

· IMDG

· Limited quantities (LQ) 5L

• Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30

ml

Maximum net quantity per outer packaging:

1000 ml

· UN "Model Regulation": UN1263, Paint, special provision 640E, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

70657-70-4 2-methoxypropyl acetate

<0.1%

1589-47-5 2-methoxypropanol

<0.01%

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 9)



Printing date 09/18/2015

Version number 117

Reviewed on 08/28/2015

Product number LZC70

Trade name: P.U. THINNER

(Contd. of page 8)

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - Date of preparation / last revision 09/18/2015 / 116
 - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Lig. 3: Flammable liquids, Hazard Category 3

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· Sources

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

* * Data compared to the previous version altered.

US