

Printing date 09/18/2015

Version number 12

Reviewed on 09/18/2015

#### 1 Identification

- · Product identifier
  - · Product number XGC33
  - · Trade name: Clear WB topcoat for mainten.
  - · Relevant identified uses of the substance or mixture and uses advised against

A coating composition for water-based coating and / or decoration of wooden artefacts

· Application of the substance / the mixture For professional use

#### · Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Flam. Liq. 4 H227 Combustible liquid. Flam. Liq. 4

#### · Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) a mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC No 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC No 220-239-6] (3:1)

1,2-benzisothiazol-3(2H)-one

Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omegahydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

· Hazard statements

H227 Combustible liquid. Flam. Liq. 4

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from flames and hot surfaces. – No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P321 Specific treatment (see on this label).

(Contd. on page 2)



Printing date 09/18/2015

Version number 12

Reviewed on 09/18/2015

**Product number XGC33** 

Trade name: Clear WB topcoat for mainten.

(Contd. of page 1)

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0
 Fire = 2
 Reactivity = 0

# 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerous	components:				
34590-94-8	(2-methoxymethylethoxy)propanol				
	Flam. Liq. 4, H227				
	Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	0.1-<0.5%			
	Aquatic Chronic 2, H411 Skin Sens. 1, H317				
127087-87-0	Nonylphenol, ethoxylated  ❖ Eye Dam. 1, H318  ❖ Aquatic Chronic 2, H411  ❖ Acute Tox. 4, H302  Aquatic Acute 2, H401	0.1-<0.5%			
121-44-8	triethylamine  Flam. Liq. 2, H225  Skin Corr. 1A, H314  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	0.1-<0.5%			
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) a mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC No 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC No 220-239-6] (3:1)				
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Skin Corr. 1B, H314 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317				

- US



Printing date 09/18/2015

Version number 12

Reviewed on 09/18/2015

**Product number XGC33** 

Trade name: Clear WB topcoat for mainten.

(Contd. of page 2)

### 4 First-aid measures

#### · Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
  - · Most important symptoms and effects, both acute and delayed
    For symptoms and effects caused by substances, refer to Section 11.
  - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

#### · Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

### 6 Accidental release measures

#### · Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to Section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- 119



Printing date 09/18/2015

Version number 12

Reviewed on 09/18/2015

**Product number XGC33** 

Trade name: Clear WB topcoat for mainten.

(Contd. of page 3)

## 7 Handling and storage

- · Handling:
  - · Precautions for safe handling No special precautions are necessary if used correctly.
  - · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
  - · Storage:
    - · Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 °C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
  - · Components with limit values that require monitoring at the workplace:

### 34590-94-8 (2-methoxymethylethoxy)propanol

PEL Long-term value: 600 mg/m³, 100 ppm

Skin

REL Short-term value: 900 mg/m³, 150 ppm Long-term value: 600 mg/m³, 100 ppm

Skin

TLV Short-term value: 909 mg/m³, 150 ppm Long-term value: 606 mg/m³, 100 ppm

Skin

· Additional information: The lists that were valid during the creation were used as basis.

### · Exposure controls

- · Personal protective equipment:
  - · General protective and hygienic measures: Wash hands before breaks and at the end of work.
  - · Breathing equipment: Not required.
  - · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Printing date 09/18/2015 Version number 12 Reviewed on 09/18/2015

**Product number XGC33** 

Trade name: Clear WB topcoat for mainten.

(Contd. of page 4)

· Eye protection: Goggles recommended during refilling.

nformation on basic physical and chemic	al properties
· General Information	
· Appearance:  · Form:	Fluid
· Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	89 °C (192 °F)
· Flash point:	75 °C (167 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	270 °C (518 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
· Lower:	1.1 Vol %
· Upper:	14.0 Vol %
· Vapor pressure at 20 °C (68 °F):	0.4 hPa
• Density at 20 °C (68 °F):	1.03 g/cm³ (8.595 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	Al a state of the
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	Not determined
· Dynamic:	Not determined.
· Kinematic at 20 °C (68 °F): · Oxidising properties:	21 s (ISO 4 mm) N.A.
	N.A.
· Solvent content:	57 7 9/
· Water:	57.7 % 8.1 %
· VOC content:	8.1 % 83.2 g/l / 0.69 lb/gl
· Solids content:	34.2 %
other information (HAPS)	

(Contd. on page 6)



Printing date 09/18/2015

Version number 12

Reviewed on 09/18/2015

**Product number XGC33** 

Trade name: Clear WB topcoat for mainten.

	triethylamine 2-[2-(2-butoxyethoxy)ethoxy]ethanol		Ontd. of page 5) 0.1-<0.5% <0.1%
· Other inf	ormation	No further relevant information availab	le.

### 10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
  - · Chemical stability The product is stable in normal conditions of storage and use recommended
    - · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
  - · Acute toxicity:

1101110 10				
· <i>LD</i> /.	LC50 value	es that are relevant for classification:		
34590-94-	8 (2-meth	oxymethylethoxy)propanol		
Oral	LD50	5135 mg/kg (rat/szczur/mouse/souris/Maus/ratón)		
Dermal	LD50	19020 mg/kg (rab)		
hydroxyp hydroxyp	oly(oxyet henyl)pro	(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega- hylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- pionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) oxyethylene)		
Oral	LD50	5001 mg/kg (rat/szczur/mouse/souris/Maus/ratón) (OECD - 401)		
Dermal	LD50	2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón) (OECD - 402)		
Inhalative	Inhalative LC50/4 h 5.9 mg/l (mouse) (OCSE - 403)			
121-44-8 triethylamine				
Oral	LD50	730 mg/kg (rat/szczur/mouse/souris/Maus/ratón)		
Dermal	LD50	580 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)		
Inhalative LC50/4 h 10.9 mg/l (rat/szczur/mouse/souris/Maus/ratón)				
	aam innitan			

- · Primary irritant effect:
  - · on the skin: No irritant effect.
  - · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information: No additional toxicological information know
  - · Carcinogenic categories
    - · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)



Printing date 09/18/2015 Version number 12

Reviewed on 09/18/2015

**Product number XGC33** 

Trade name: Clear WB topcoat for mainten.

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

### · Toxicity

• A	19	ш	at	ıc	ta	xı	сиу	:		

### 34590-94-8 (2-methoxymethylethoxy)propanol

EC50 970 mg/l (algae) (72 h)

1919 mg/l (daphnia) (48 h)

LC50 (96h) 1001 mg/l (Fish)

Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

EC50 101 mg/l (algae) (72h)

4 mg/l (daphnia) (OECD linee guida 202 parte 1)

LC50 (96h) 2.8 mg/l (Leuciscus idus melanotus) (OECD linee guida 203)

### 121-44-8 triethylamine

EC50 8 mg/l (algae) (72 h) 17 mg/l (daphnia) (48 h)

LC50 (96h) 36 mg/l (Fish)

55965-84-9 a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) a mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC No 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC No 220-239-6] (3:1)

EC50 0.1 mg/l (daphnia) (48 h)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
  - · Bioaccumulative potential No further relevant information available.
  - · Mobility in soil No further relevant information available.
- Additional ecological information:
  - · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No further relevant information available.

## 13 Disposal considerations

### · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

(Contd. on page 8)



Printing date 09/18/2015

Version number 12

Reviewed on 09/18/2015

**Product number XGC33** 

Trade name: Clear WB topcoat for mainten.

(Contd. of page 7)

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number		
· DOT, ADN, IMDG, IATA	Not applicable	
UN proper shipping name		
· DOT, ADN, IMDG, IATA	Not applicable	
Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA	Nataralia	
· Class	Not applicable	
Packing group		
· DOT, IMDG, IATA	Not applicable	
Environmental hazards:		
· Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	ː II of	
MARPOL73/78 and the IBC Code	Not applicable.	

# 15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

Requirements of Federal Register

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

121-44-8 triethylamine

143-22-6 2-[2-(2-butoxyethoxy)ethoxy]ethanol <0.1%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)

0.1-<0.5%



Printing date 09/18/2015

Version number 12

Reviewed on 09/18/2015

**Product number XGC33** 

Trade name: Clear WB topcoat for mainten.

(Contd. of page 8)

· Carcinogenic categories

	8			
· EPA (Environmental Protection Agency)				
None of the ii	ngredients is listed.			
$\cdot TLV(T)$	hreshold Limit Value established by ACGIH)			
112945-52-5	silicon dioxide	A4		
121-44-8	triethylamine	A4		
· NIOSH	-Ca (National Institute for Occupational Safety and Health)			
None of the ingredients is listed.				

#### · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
  - · Date of preparation / last revision 09/18/2015 / 11
  - · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 3: Acute toxicity, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - AcuteHazard, Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· Sources

Directive 1999/45/EC and following amendments

Directive 67/548/EEC and following amendments and adjustments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

\* \* Data compared to the previous version altered.