

Printing date 04/27/2017

Version number 1

Reviewed on 04/27/2017

1 Identification

- · Product identifier
 - · Product number XHT612
 - · Trade name: WB IMPR. WAX TEAK
 - · Application of the substance / the mixture For professional use
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· Information department:

Environmental Health and safety office

hseoffice@ivmchemicals.com

· Emergency telephone number:

ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

· Classification of the substance or mixture



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Flam. Liq. 4 H227 Combustible liquid. Flam. Liq. 4

Aquatic Acute 2 H401 Toxic to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

3-lodo-2-propynylbutylcarbamate

2,4,7,9-tetramethyldec-5-yne-4,7-diol

1,2-benzisothiazol-3(2H)-one

a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)

· Hazard statements

H227 Combustible liquid. Flam. Liq. 4

H317 May cause an allergic skin reaction.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from flames and hot surfaces. – No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see on this label).

(Contd. on page 2)



Printing date 04/27/2017

Version number 1

Reviewed on 04/27/2017

Product number XHT612

Trade name: WB IMPR. WAX TEAK

(Contd. of page 1)

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0 Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0
 Fire = 2
 Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture: consisting of the following components.

· Dangerous	components:	
111-76-2	2-butoxyethanol • Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Flam. Liq. 4, H227	2.5-4.99%
57-55-6	propane-1,2-diol	2.5-4.99%
55406-53-6	3-lodo-2-propynylbutylcarbamate Acute Tox. 3, H331 STOT RE 1, H372 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1) Acute Tox. 4, H302; Skin Sens. 1, H317	0.5-<1%
107-21-1	ethanediol STOT RE 2, H373 Acute Tox. 4, H302	
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol Eye Dam. 1, H318 Skin Sens. 1, H317 Flam. Liq. 4, H227; Aquatic Acute 3, H402; Aquatic Chronic 3, H412	
127087-87-0	Nonylphenol, ethoxylated Eye Dam. 1, H318 Aquatic Chronic 2, H411 Acute Tox. 4, H302 Aquatic Acute 2, H401	0.25-<0.5%
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Skin Corr. 1B, H314 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	<0.0015%



Printing date 04/27/2017 Version number 1 Reviewed on 04/27/2017

Product number XHT612

Trade name: WB IMPR. WAX TEAK

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed
 For symptoms and effects caused by substances, refer to Section 11.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Advice for firefighters

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

· Protective equipment:

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Printing date 04/27/2017 Version number 1

Reviewed on 04/27/2017

Product number XHT612

Trade name: WB IMPR. WAX TEAK

· Protective A	ction Criteria for Chemicals	(Contd. of page 3)
· PAC-1:		
57-55-6	propane-1,2-diol	30 mg/m3
55406-53-6	3-lodo-2-propynylbutylcarbamate	3.3 mg/m3
577-11-7	docusate sodium	5.7 mg/m3
107-21-1	ethanediol	30 ppm
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	30 mg/m3
127087-87-0	Nonylphenol, ethoxylated	30 mg/m3
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
· PAC-2:		
57-55-6	propane-1,2-diol	1,300 mg/m3
55406-53-6	3-lodo-2-propynylbutylcarbamate	36 mg/m3
577-11-7	docusate sodium	63 mg/m3
107-21-1	ethanediol	150 ppm
126-86-3	2,4,7,9-tetramethyldec-5-yne-4,7-diol	330 mg/m3
127087-87-0	Nonylphenol, ethoxylated	330 mg/m3
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
· PAC-3:		
57-55-6	propane-1,2-diol	7,900 mg/m3
55406-53-6	3-lodo-2-propynylbutylcarbamate	220 mg/m3
577-11-7	docusate sodium	380 mg/m3
107-21-1	ethanediol	900 ppm

7 Handling and storage

- · Handling:
 - · Precautions for safe handling No special precautions are necessary if used correctly.
 - · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

126-86-3 2,4,7,9-tetramethyldec-5-yne-4,7-diol

34590-94-8 (2-methoxymethylethoxy)propanol

127087-87-0 Nonylphenol, ethoxylated

- · Conditions for safe storage, including any incompatibilities
 - · Storage:
 - Requirements to be met by storerooms and receptacles:

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

Take on temperature greater than 5 °C

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

2,000 mg/m3

2,000 mg/m3

9900** ppm



Printing date 04/27/2017 Version number 1 Reviewed on 04/27/2017

Product number XHT612

Trade name: WB IMPR. WAX TEAK

(Contd. of page 4)

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 97 mg/m³, 20 ppm BEI

WEEL Long-term value: 10 mg/m³

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
 - · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.



Printing date 04/27/2017 Version number 1 Reviewed on 04/27/2017

Product number XHT612

Trade name: WB IMPR. WAX TEAK

(Contd. of page 5)

Information on basic physical and chemic General Information	cal properties	
· Appearance:		
· Form:	Fluid	
· Color:	According to product spe	cification
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	65 °C (149 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Not determined.	
· Explosion limits:	4 4 14 4 24	
· Lower:	1.1 Vol % 12.6 Vol %	
· Upper:		
· Vapor pressure at 20 °C (68 °F):	1.2 hPa (1 mm Hg)	
Density at 20 °C (68 °F):	1.02 g/cm³ (8.512 lbs/gal)	
· Relative density	Not determined.	
· Vapor density · Evaporation rate	Not determined. Not determined.	
<u> </u>	Not determined.	
Solubility in / Miscibility with Water:	Not miscible or difficult to mi	X.
· Partition coefficient (n-octanol/water):	Not determined.	
· Viscosity:		
· Dynamic:	Not determined.	
· Kinematic at 20 °C (68 °F):	29 s (ISO 3 mm)	
· Oxidising properties:	N.A.	
· Solvent content:	05.0.07	
· Water:	65.9 %	
· VOC content:	9.6 % 98.0 g/l / 0.82 lb/gl	
· Solids content:	24.5 %	
	24.J /0	
Other information (HAPS) 107-21-1 ethanediol		0.1-<0.5
112-34-5 2-(2-butoxyethoxy)ethanol		<0.1%
98-82-8 cumene		<0.1%
1330-20-7 xylene		<0.01%



Printing date 04/27/2017 Version number 1 Reviewed on 04/27/2017

Product number XHT612

Trade name: WB IMPR. WAX TEAK

143-22-6 2-[2-(2-h	utoxyethoxy)ethoxy]ethanol	(Contd. of page < 0.01%
111-90-0 2-(2-etho		<0.01%
Other information	No further releva	nt information available.

10 Stability and reactivity

- · Reactivity typical of the product as indicated in the data sheet
 - · Chemical stability The product is stable in normal conditions of storage and use recommended
 - $\cdot \textit{Thermal decomposition / conditions to be avoided:} \\$

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

nicute to	<i></i>	
· LD/	LC50 value	es that are relevant for classification:
111-76-2	2-butoxye	thanol
Oral	LD50	1480 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	1100 mg/kg (rab)
57-55-6 p	ropane-1,2	2-diol
Oral	LD50	20000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
55406-53-	6 3-lodo-2	2-propynylbutylcarbamate
Oral	LD50	500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
107-21-1	ethanedio	il .
Oral	LD50	301 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	3501 mg/kg (mouse)
		9530 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/6 h	2.5 ppm (rat/szczur/mouse/souris/Maus/ratón)
126-86-3	2,4,7,9-teti	ramethyldec-5-yne-4,7-diol
Oral	LD50	4600 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
127087-87	7-0 Nonyl	ohenol, ethoxylated
Oral	LD50	1999 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Dania	• • •	A official

- · Primary irritant effect:
 - · on the skin: No irritant effect.
 - · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Irritant

Contains 3-lodo-2-propynylbutylcarbamate, 2,4,7,9-tetramethyldec-5-yne-4,7-diol, 1,2-benzisothiazol-3(2H)-one, a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-(Contd. on page 8)



Printing date 04/27/2017 Version number 1 Reviewed on 04/27/2017

Product number XHT612

Trade name: WB IMPR. WAX TEAK

(Contd. of page 7)

7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1). May produce an allergic reaction.

· Carcinogenic categories

Carbon Black

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to carbon black but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as paint."

• 1	· IARC (International Agency for Research on Cancer - Cl. 1 and 2)			
98-82-8	cumene	2B		
1333-86-4	Carbon black	2B Dust		
• 1	NTP (National Toxicology Program)			
98-82-8 c	umene	<0.1%		
• (OSHA-Ca (Occupational Safety & Health Administration)			
None of th	e ingredients is listed.			

12 Ecological information

· Toxicity Harmful to aquatic life with long lasting effects.

· TOXICILY Ha	armiui to aquatic lile with long lasting ellects.
· Aquatic t	oxicity:
111-76-2 2-	butoxyethanol
EC50	101 mg/l (daphnia) (24 h)
LC50 (96h)	101 mg/l (Fish)
57-55-6 pro	pane-1,2-diol
EC50	19000 mg/l (algae) (48 h)
	18340 mg/l (daphnia) (48 h)
LC50 (96h)	40613 mg/l (Fish)
55406-53-6	3-lodo-2-propynylbutylcarbamate
EC50	0.022 mg/l (algae) (72 h)
	0.16 mg/l (daphnia) (48 h)
LC50 (96h)	0.067 mg/l (Fish)
127087-87-	0 Nonylphenol, ethoxylated
EC50	100 mg/l (algae) (72 h)
	100 mg/l (daphnia) (48 h)
LC50 (96h)	10 mg/l (Fish)
55965-84-9	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1)
EC50	0.1 mg/l (daphnia) (48 h)
	and decreased bits. No finite an adecrease information arrelated

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
 - · Remark: Harmful to fish

(Contd. on page 9)



Printing date 04/27/2017 Version number 1 Reviewed on 04/27/2017

Product number XHT612

Trade name: WB IMPR. WAX TEAK

(Contd. of page 8)

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- · Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

UN-Number		
· DOT, ADN, IMDG, IATA	Not applicable	
UN proper shipping name		
· DOT, ADN, IMDG, IATA	Not applicable	
Transport hazard class(es)		
· DOT, ADR, ADN, IMDG, IATA		
· Class	Not applicable	
Packing group		
· DOT, IMDG, IATA	Not applicable	
Environmental hazards:		
· Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	· II of	
MARPOL73/78 and the IBC Code	Not applicable.	
UN "Model Regulation":	Not applicable	

15 Regulatory information

· SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

 111-76-2
 2-butoxyethanol
 2,5-4,99%

 55406-53-6
 3-lodo-2-propynylbutylcarbamate
 0.5-<1%</td>

(Contd. on page 10)



Printing date 04/27/2017

Version number 1

Reviewed on 04/27/2017

Product number XHT612

Trade name: WB IMPR. WAX TEAK

		(C	ontd. of p	age 9	
107-21-1	-1 ethanediol 0.1-<0.				
95-63-6	95-63-6 1,2,4-trimethylbenzene <0.1%				
112-34-5 2-(2-butoxyethoxy)ethanol <0.1%					
98-82-8	cumene		<0.1%	,	
1330-20-7	xylene		<0.019	%	
143-22-6	2-[2-(2-butoxyethoxy)ethoxy]ethanol		<0.019	%	
111-90-0	2-(2-ethoxyethoxy)ethanol		<0.019	%	
· TSCA (T	oxic Substances Control Act):				
All ingredie	nts are listed.				
· Propositi					
· Chem	nicals known to cause cancer:				
98-82-8	cumene		* <0.	.1%	
1333-86-4	Carbon black		* <0.0	01%	
· Chem	icals known to cause reproductive toxicity for females:				
	e ingredients is listed.				
	nicals known to cause reproductive toxicity for males:				
	e ingredients is listed.				
107-21-1 e	ticals known to cause developmental toxicity:		0.1.40	. <i>E</i> 0.	
107-21-1 6	uranedor		0.1-<0	.5%	
· Carcinog	renic categories				
	(Environmental Protection Agency)				
111-76-2	2-butoxyethanol	NL	2,5-4,	99%	
95-63-6	1,2,4-trimethylbenzene	<i>II</i>	<0.1	1%	
98-82-8	cumene	D, CBD	<0.1	1%	
526-73-8	1,2,3-trimethylbenzene	II .	<0.0	1%	
1330-20-7	xylene	1	<0.0	1%	
$\cdot TLV$	(Threshold Limit Value established by ACGIH)				
	2-butoxyethanol			A	
	ethanediol			A	
1330-20-7	xylene			A	
	Carbon black			A	
· NIOS	H-Ca (National Institute for Occupational Safety and Health)				
	Carbon black		<0.0	01%	
. 555 66 7			10.0	/ (

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: IVM Chemicals Srl
- · Contact: See emergency phone
 - · Date of preparation / last revision 04/27/2017 / -

(Contd. on page 11)



Printing date 04/27/2017

Version number 1

Reviewed on 04/27/2017

Product number XHT612

WB IMPR. WAX TEAK Trade name:

(Contd. of page 10)

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids - Category 4 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity - Category 3

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Agency ECHA web site INRS Fiche Toxicologique IARC International agency for research on cancer