

Acrylic Polyurethanes

- Excellent chemical resistance
- Non-yellowing
- Easy application and mixing ratios
- Follows the contour of the wood grain
- Gives great pore definition
- Enhances grain for open pore finishes
- Excellent flexibility and elasticity
- Smooth feel to the touch
- Superior Clarity
- Formaldehyde Free
- Max Dry Film Build: 10 mils

INTERIOR ACRYLICS

LJA99 – Acrylic Sealer

Contains a UV inhibitor

Catalyst LNB99 // 20% // 3 HR Pot Life

LUA118 – Natural Look Self-Sealing Top Coat

5 Sheen

Catalyst LNB99 // 25% // 4 HR Pot Life

LUA430 Series – Acrylic Self-Sealing Top Coat

24 Hour Pot Life. Available in 2, 5, 10, 20, 40, and 65 sheens.

Catalyst LNB99 // 10% // 24 HR Pot Life

LLA6020 – Acrylic Clear Gloss

100 Sheen

Catalyst LNB99 // 80% // 3 HR Pot Life

EXTERIOR ACRYLICS

YBA600 – Exterior Isolante Sealer

Must be used with oily woods.

Catalyst LNB99 // 40% // 4 HR Pot Life

YGA601 Series– Exterior Acrylic Self-Sealing Top Coat

Available in 15 and 30 sheens.

Catalyst LNB99 // 40% // 3 HR Pot Life

LGA180 – Exterior Xilocrom Neutral Converter

For tinting bold colors. Self-Sealing. 30 sheen.

Catalyst LNB99 // 40% // 4 HR Pot Life

LKR181– Exterior Xilocrom Acrylic White Topcoat

Self-Sealing. 30 sheen.

Catalyst LNB99 // 40% // 4 HR Pot Life

| | |
|-------------------|--|
| Hardener | LNB99 - For all acrylic polyurethanes |
| Reducers | Fast - LZC1026 Medium - LZC70 Slow - LZC2A12 Retarder - LTC40 |
| Initial Reduction | 10% |
| Max Reduction | 40% |
| Cleanup | Acetone |