

Acrylic Polyurethanes

- Excellent chemical resistance
- Non-yellowing
- Easy application and mixing ratios
- Follows the contour of the wood grain
- Gives great pore definition
- Enhances grain for open pore finishes
- Excellent flexibility and elasticity
- Smooth feel to the touch
- Superior Clarity
- Formaldehyde Free
- Max Dry Film Build: 10 mils

INTERIOR ACRYLICS

LJA99 – Acrylic Sealer

Contains a UV inhibitor

Catalyst LNB99 // 20% // 3 HR Pot Life

LUA118 – Natural Look Self-Sealing Top Coat

5 Sheen

Catalyst LNB99 // 25% // 4 HR Pot Life

LUA4 Series – Acrylic Self-Sealing Top Coat

24 Hour Pot Life. Available in 2, 5, 10, 20, and 40 Sheens

4 Hour Pot Life. Available in 65 Sheen

Catalyst LNB99 // 10% // 24 HR Pot Life

LLA6020 – Acrylic Clear Gloss

100 Sheen

Catalyst LNB99 // 80% // 3 HR Pot Life

PIGMENTED ACRYLICS

LUR201 Series – Acrylic White Converters

3 Hour Pot Life. Available in 5 and 25 Sheens

Catalyst LNB99 // 25% // 3 HR Pot Life

Hardener	LNB99 - For all acrylic polyurethanes
Reducers	Fast - LZC1026 Medium - LZC70 Slow - LZC2A12 Retarder - LTC40
Initial Reduction	10%
Max Reduction	40%
Cleanup	Acetone